

# MED10-6655

## Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations  
Revision Date: 05/13/2019 Date of Issue: 02/10/2015



Version 3.0

## SECTION 1: Identification

### 1.1. Product Identifier

Product Form Mixture  
Product Name MED10-6655  
Synonyms Fluorosilicone Dispersion

### 1.2. Relevant Identified Uses of the Substance or Mixture and Uses Advised Against

Use of the Substance/Mixture For professional use only.

### 1.3. Details of the Supplier of the Safety Data Sheet

NuSil Technology LLC  
1050 Cindy Lane  
Carpinteria, California 93013  
USA  
(805) 684-8780  
[ehs@nusil.com](mailto:ehs@nusil.com)  
[www.nusil.com](http://www.nusil.com)

### 1.4. Emergency Telephone Number

Emergency Number 800-424-9300 CHEMTREC (in US); +1 703-527-3887 CHEMTREC (International and Maritime)

## SECTION 2: Hazards Identification

### 2.1. Classification of the Substance or Mixture

#### GHS-US Classification

Flam. Liq. 2 H225  
Skin Irrit. 2 H315  
Eye Dam. 1 H318  
STOT SE 3 H335  
STOT SE 3 H336

Full text of hazard classes and H-statements : see section 1.6

### 2.2. Label Elements

#### GHS-US Labeling

Hazard Pictograms (GHS-US)



GHS02 GHS05 GHS07

Signal Word (GHS-US)

Hazard Statements (GHS-US)

Danger  
H225 - Highly flammable liquid and vapor  
H315 - Causes skin irritation  
H318 - Causes serious eye damage  
H335 - May cause respiratory irritation  
H336 - May cause drowsiness or dizziness

# MED10-6655

## Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### Precautionary Statements (GHS-US)

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P233 - Keep container tightly closed.  
P240 - Ground/Bond container and receiving equipment.  
P241 - Use explosion-proof electrical, lighting, ventilating equipment.  
P242 - Use only non-sparking tools.  
P243 - Take precautionary measures against static discharge.  
P261 - Avoid breathing mist, spray, vapors.  
P264 - Wash hands, forearms, and exposed areas thoroughly after handling.  
P271 - Use only outdoors or in a well-ventilated area.  
P273 - Avoid release to the environment.  
P280 - Wear eye protection, protective clothing, protective gloves.  
P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.  
P304+P340 - If inhaled: Remove person to fresh air and keep at rest in a position comfortable for breathing.  
P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P310 - Immediately call a poison center or doctor.  
P321 - Specific treatment (see Section 4 on this SDS).  
P332+P313 - If skin irritation occurs: Get medical advice/attention.  
P362+P364 - Take off contaminated clothing and wash it before reuse.  
P370+P378 - In case of fire: Use dry chemical powder, alcohol-resistant foam, carbon dioxide (CO<sub>2</sub>) to extinguish.  
P403+P233+P235 - Store in a well-ventilated place. Keep container tightly closed. Keep cool.  
P405 - Store locked up.  
P501 - Dispose of contents/container in accordance with local, regional, national, and international regulations.

### 2.3. Other Hazards

Other Hazards Not Contributing to the Classification

Exposure may aggravate pre-existing eye, skin, or respiratory conditions.

### 2.4. Unknown Acute Toxicity (GHS-US)

No data available

## SECTION 3: Composition/Information On Ingredients

### 3.1. Substances

Not applicable

### 3.2. Mixture

Name	Product Identifier	%	GHS-US Classification
Siloxanes and Silicones, methyl 3,3,3-trifluoropropyl, hydroxy-terminated	(CAS-No.) 68607-77-2	40 - 60	Skin Irrit. 2, H315 Eye Irrit. 2A, H319 STOT SE 3, H335

# MED10-6655

## Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

tert-Butyl acetate	(CAS-No.) 540-88-5	30 - 50	Flam. Liq. 2, H225 Acute Tox. 4 (Inhalation:vapor), H332 STOT SE 3, H336 STOT SE 3, H335
Silanetriol, ethyl-, triacetate	(CAS-No.) 17689-77-9	< 5	Acute Tox. 4 (Oral), H302 Skin Corr. 1B, H314 Eye Dam. 1, H318
Silanetriol, methyl-, triacetate	(CAS-No.) 4253-34-3	< 5	Acute Tox. 4 (Oral), H302 Skin Corr. 1C, H314 Eye Dam. 1, H318

Full text of H-phrases: see section 16

## SECTION 4: First Aid Measures

### 4.1. Description of First-aid Measures

First-aid Measures General	Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).
First-aid Measures After Inhalation	Remove to fresh air and keep at rest in a position comfortable for breathing. Obtain medical attention if breathing difficulty persists.
First-aid Measures After Skin Contact	Remove contaminated clothing. Drench affected area with water or soap and water for at least 15 minutes. Wash contaminated clothing before reuse. Obtain medical attention if irritation develops or persists.
First-aid Measures After Eye Contact	Rinse cautiously with water for at least 30 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get immediate medical advice/attention.
First-aid Measures After Ingestion	Seek medical attention if a large amount is swallowed. Rinse mouth. Do NOT induce vomiting.

### 4.2. Most Important Symptoms and Effects Both Acute and Delayed

Symptoms/Injuries	Causes skin irritation. Causes serious eye damage. May cause drowsiness and dizziness. May cause respiratory irritation.
Symptoms/Injuries After Inhalation	May cause irritation to the respiratory tract, sneezing, coughing, burning sensation of throat with constricting sensation of the larynx and difficulty in breathing. High concentrations may cause central nervous system depression such as dizziness, vomiting, numbness, drowsiness, headache, and similar narcotic symptoms.
Symptoms/Injuries After Skin Contact	Redness, pain, swelling, itching, burning, dryness, and dermatitis.
Symptoms/Injuries After Eye Contact	Causes permanent damage to the cornea, iris, or conjunctiva.
Symptoms/Injuries After Ingestion	Ingestion is likely to be harmful or have adverse effects.
Chronic Symptoms	Repeated exposure may cause skin dryness or cracking.

### 4.3. Indication of Any Immediate Medical Attention and Special Treatment Needed

If you feel unwell, seek medical advice (show the label where possible).

## SECTION 5: Fire-Fighting Measures

### 5.1. Extinguishing Media

- Suitable Extinguishing Media : Water spray, fog, carbon dioxide, foam, dry chemical.  
Unsuitable Extinguishing Media : Do not use a heavy water stream. Use of heavy stream of water may spread fire. Application of water stream to hot product may cause frothing and increase fire intensity.

### 5.2. Special Hazards Arising From the Substance or Mixture

- Fire Hazard Highly flammable liquid and vapor.  
Explosion Hazard May form flammable/explosive vapor-air mixture.  
Reactivity Reacts violently with (strong) oxidizers: (increased) risk of fire/explosion.

### 5.3. Advice for Firefighters

- Precautionary Measures Fire Exercise caution when fighting any chemical fire.  
Firefighting Instructions Do not breathe fumes from fires or vapors from decomposition.  
Protection During Firefighting Do not enter fire area without proper protective equipment, including respiratory protection.

## SECTION 6: Accidental Release Measures

### 6.1. Personal Precautions, Protective Equipment And Emergency Procedures

- General Measures Use special care to avoid static electric charges. Keep away from heat, sparks, open flames, hot surfaces. – No smoking. Avoid contact with skin, eyes and clothing. Avoid breathing (vapor, mist, spray).

#### 6.1.1. For Non-Emergency Personnel

- Protective Equipment Use appropriate personal protective equipment (PPE).  
Emergency Procedures Evacuate unnecessary personnel.

#### 6.1.2. For emergency responders

- Protective Equipment Equip cleanup crew with proper protection.  
Emergency Procedures Stop leak if safe to do so. Eliminate ignition sources. Ventilate area.

### 6.2. Environmental Precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

### 6.3. Methods and Materials for Containment and Cleaning Up

- For Containment Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.  
Methods for Cleaning Up Clean up spills immediately and dispose of waste safely. Spills should be contained with mechanical barriers. Transfer spilled material to a suitable container for disposal. Do not take up in combustible material such as: saw dust or cellulosic material. Use only non-sparking tools. Contact competent authorities after a spill.

### 6.4. Reference to Other Sections

See Section 8 for advice on personal protective equipment and Section 13 for disposal considerations.

## SECTION 7: Handling And Storage

### 7.1. Precautions for Safe Handling

Additional Hazards When Processed	Handle empty containers with care because residual vapors are flammable.
Precautions for Safe Handling	Avoid contact with skin and eyes. Take precautionary measures against static discharge. Use only non-sparking tools. Keep away from heat, sparks, open flames, hot surfaces. – No smoking.
Hygiene Measures	Handle in accordance with good industrial hygiene and safety procedures. Wash hands and other exposed areas with mild soap and water before eating, drinking, or smoking and again when leaving work.

### 7.2. Conditions for Safe Storage, Including Any Incompatibilities

Technical Measures	Proper grounding procedures to avoid static electricity should be followed. Ground/bond container and receiving equipment. Use explosion-proof electrical, ventilating, and lighting equipment. Comply with applicable regulations.
Storage Conditions	Store in a dry, cool and well-ventilated place. Keep container closed when not in use. Keep/Store away from direct sunlight, extremely high or low temperatures and incompatible materials. Keep in fireproof place.
Incompatible Materials	Strong acids. Strong bases. Strong oxidizers.

### 7.3. Specific End Use(S)

For professional use only.

## SECTION 8: Exposure Controls/Personal Protection

### 8.1. Control Parameters

For substances listed in section 3 that are not listed here, there are no established exposure limits from the manufacturer, supplier, importer, or the appropriate advisory agency including: ACGIH (TLV), or OSHA (PEL).

tert-Butyl acetate (540-88-5)		
USA ACGIH	ACGIH TWA (ppm)	50 ppm (Butyl acetates, all isomers)
USA ACGIH	ACGIH STEL (ppm)	150 ppm (Butyl acetates, all isomers)
USA OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	950 mg/m <sup>3</sup>
USA OSHA	OSHA PEL (TWA) (ppm)	200 ppm

### 8.2. Exposure Controls

Appropriate Engineering Controls	Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Ensure adequate ventilation, especially in confined areas. Gas detectors should be used when flammable gases/vapors may be released. Take precautionary measures against static discharges. Proper grounding procedures to avoid static electricity should be followed. Use explosion-proof equipment. Ensure all national/local regulations are observed.
----------------------------------	---

# MED10-6655

## Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### Personal Protective Equipment

Protective goggles. Gloves. Protective clothing. Insufficient ventilation: wear respiratory protection.



### Materials For Protective Clothing

Chemically resistant materials and fabrics. Wear fire/flammable resistant/retardant clothing.

### Hand Protection

Wear chemically resistant protective gloves.

### Eye And Face Protection

Chemical safety goggles.

### Skin And Body Protection

Wear suitable protective clothing.

### Respiratory Protection

Use a NIOSH-approved respirator or self-contained breathing apparatus whenever exposure may exceed established Occupational Exposure Limits.

### Environmental Exposure Controls

Do not allow the product to be released into the environment.

### Consumer Exposure Controls

Do not eat, drink or smoke during use.

## SECTION 9: Physical and Chemical Properties

### 9.1. Information on Basic Physical and Chemical Properties

Physical State	Liquid
Appearance	White
Odor	No data available
Odor Threshold	No data available
pH	No data available
Evaporation Rate	No data available
Melting Point	No data available
Freezing Point	No data available
Boiling Point	98 °C (208 °F)
Flash Point	4.4 °C (40 °F)
Auto-ignition Temperature	No data available
Decomposition Temperature	No data available
Flammability (solid, gas)	No data available
Vapor Pressure	No data available
Relative Vapor Density at 20°C	No data available
Specific Gravity	< 1
Solubility	No data available
Partition Coefficient n-Octanol/Water	No data available
Viscosity	No data available

### 9.2. Other Information

VOC Content 30 - 50 %

## SECTION 10: Stability and Reactivity

### 10.1. Reactivity

Reacts violently with (strong) oxidizers: (increased) risk of fire/explosion.

### 10.2. Chemical Stability

Highly flammable liquid and vapor.

# MED10-6655

## Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 10.3. Possibility of Hazardous Reactions

Hazardous polymerization will not occur.

### 10.4. Conditions to Avoid

Direct sunlight. Extremely high or low temperatures. Ignition sources. Incompatible materials.

### 10.5. Incompatible Materials

Strong acids. Strong bases. Strong oxidizers.

### 10.6. Hazardous Decomposition Products

Carbon oxides (CO, CO<sub>2</sub>). Silicon oxides. Will decompose above 150 °C (> 300 °F) releasing formaldehyde vapors. Formaldehyde is a potential carcinogen and can act as a skin and respiratory sensitizer. Formaldehyde can also cause respiratory and eye irritation. Isobutylene. Acetic acid. Oxides of tin.

## SECTION 11: Toxicological Information

### 11.1. Information on Toxicological Effects

Acute Toxicity (Oral) : Not classified

Acute Toxicity (Dermal) : Not classified

Acute Toxicity (Inhalation) : Not classified

tert-Butyl acetate (540-88-5)	
LD50 Oral Rat	4500 mg/kg
LD50 Dermal Rabbit	> 2000
LC50 Inhalation Rat	> 9482 mg/m <sup>3</sup> (Exposure time: 4 h)
LC50 Inhalation Rat	13.3 mg/l/4h
LC50 Inhalation Rat	5157 ppm/4h

Silanetriol, ethyl-, triacetate (17689-77-9)	
LD50 Oral Rat	1460 mg/kg

Silanetriol, methyl-, triacetate (4253-34-3)	
LD50 Oral Rat	1437 - 1780 mg/kg

Skin Corrosion/Irritation Causes skin irritation.

Serious Eye Damage/Irritation Causes serious eye damage.

Respiratory or Skin Sensitization Not classified

Germ Cell Mutagenicity Not classified

Carcinogenicity Not classified

Reproductive Toxicity : Not classified

Specific Target Organ Toxicity (Single Exposure) : May cause respiratory irritation. May cause drowsiness or dizziness.

Specific Target Organ Toxicity (Repeated Exposure) : Not classified

Aspiration Hazard Not classified

Symptoms/Injuries After Inhalation May cause irritation to the respiratory tract, sneezing, coughing, burning sensation of throat with constricting sensation of the larynx and difficulty in breathing. High concentrations may cause central nervous system depression such as dizziness, vomiting, numbness, drowsiness, headache, and similar narcotic symptoms.

Symptoms/Injuries After Skin Contact Redness, pain, swelling, itching, burning, dryness, and dermatitis.

Symptoms/Injuries After Eye Contact Causes permanent damage to the cornea, iris, or conjunctiva.

# MED10-6655

## Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Symptoms/Injuries After Ingestion is likely to be harmful or have adverse effects.  
Ingestion  
Chronic Symptoms Repeated exposure may cause skin dryness or cracking.

## SECTION 12: Ecological Information

### 12.1. Toxicity

Ecology - General Harmful to aquatic life.

tert-Butyl acetate (540-88-5)	
LC50 Fish 1	296 - 362 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])

### 12.2. Persistence and Degradability

MED10-6655	
Persistence and Degradability	Not established.

### 12.3. Bioaccumulative Potential

MED10-6655	
Bioaccumulative Potential	Not established.
tert-Butyl acetate (540-88-5)	
Log Pow	1.38
Silanetriol, methyl-, triacetate (4253-34-3)	
Log Pow	0.25 KowWin

### 12.4. Mobility In Soil

No additional information available

### 12.5. Other Adverse Effects

Other Information Avoid release to the environment.

## SECTION 13: Disposal Considerations

### 13.1. Waste Treatment Methods

Waste Disposal Dispose of waste material in accordance with all local, regional, national, and international regulations.  
Recommendations  
Additional Information Handle empty containers with care because residual vapors are flammable.  
Ecology - Waste Materials Avoid release to the environment.

## SECTION 14: Transport Information

The shipping description(s) stated herein were prepared in accordance with certain assumptions at the time the SDS was authored, and can vary based on a number of variables that may or may not have been known at the time the SDS was issued.

### 14.1. In Accordance with DOT

Proper Shipping Name BUTYL ACETATES  
Hazard Class 3  
Identification Number UN1123  
Label Codes 3  
Packing Group II  
ERG Number 129





# MED10-6655

## Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 14.2. In Accordance with IMDG

Proper Shipping Name BUTYL ACETATES  
Hazard Class 3  
Identification Number UN1123  
Packing Group II  
Label Codes 3  
EmS-No. (Fire) F-E  
EmS-No. (Spillage) S-D  
MFAG Number 129



### 14.3. In Accordance with IATA

Proper Shipping Name BUTYL ACETATES  
Packing Group II  
Identification Number UN1123  
Hazard Class 3  
Label Codes 3  
ERG Code (IATA) 3L



## SECTION 15: Regulatory Information

### 15.1. US Federal Regulations

All components in this mixture are listed on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory, have been exempted, are not listed, not disclosed due to CBI requirements or disclosure rules according to the relevant regulation.

MED10-6655	
SARA Section 311/312 Hazard Classes	Physical hazard - Flammable (gases, aerosols, liquids, or solids) Health hazard - Serious eye damage or eye irritation Health hazard - Skin corrosion or Irritation Health hazard - Specific target organ toxicity (single or repeated exposure)
tert-Butyl acetate (540-88-5)	
CERCLA RQ	5000 lb listed under Butyl acetate

### 15.2. US State Regulations

Siloxanes and Silicones, methyl 3,3,3-trifluoropropyl, hydroxy-terminated (68607-77-2)
U.S. - Texas - Effects Screening Levels - Long Term
U.S. - Texas - Effects Screening Levels - Short Term
tert-Butyl acetate (540-88-5)

# MED10-6655

## Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

U.S. - Connecticut - Hazardous Air Pollutants - HLVs (30 min)  
U.S. - Connecticut - Hazardous Air Pollutants - HLVs (8 hr)  
U.S. - Delaware - Pollutant Discharge Requirements - Reportable Quantities  
U.S. - Delaware - Volatile Organic Compounds Exempt from Requirements  
U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Acceptable Ambient Concentrations  
U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Emission Levels (ELs)  
U.S. - Idaho - Occupational Exposure Limits - TWAs  
U.S. - Massachusetts - Oil & Hazardous Material List - Groundwater Reportable Concentration - Reporting Category 1  
U.S. - Massachusetts - Oil & Hazardous Material List - Groundwater Reportable Concentration - Reporting Category 2  
U.S. - Massachusetts - Oil & Hazardous Material List - Reportable Quantity  
U.S. - Massachusetts - Oil & Hazardous Material List - Soil Reportable Concentration - Reporting Category 1  
U.S. - Massachusetts - Oil & Hazardous Material List - Soil Reportable Concentration - Reporting Category 2  
RTK - U.S. - Massachusetts - Right To Know List  
U.S. - Massachusetts - Toxics Use Reduction Act  
U.S. - Massachusetts - Volatile Organic Compounds Exempt From Requirements  
U.S. - Michigan - Occupational Exposure Limits - TWAs  
U.S. - Michigan - Polluting Materials List  
U.S. - Minnesota - Hazardous Substance List  
U.S. - Minnesota - Permissible Exposure Limits - TWAs  
U.S. - New Jersey - Discharge Prevention - List of Hazardous Substances  
RTK - U.S. - New Jersey - Right to Know Hazardous Substance List  
U.S. - New Jersey - Special Health Hazards Substances List  
U.S. - New York - Occupational Exposure Limits - TWAs  
U.S. - New York - Reporting of Releases Part 597 - List of Hazardous Substances  
U.S. - North Dakota - Air Pollutants - Guideline Concentrations - 8-Hour  
U.S. - Oregon - Permissible Exposure Limits - TWAs  
RTK - U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List  
RTK - U.S. - Pennsylvania - RTK (Right to Know) List  
U.S. - Tennessee - Occupational Exposure Limits - TWAs  
U.S. - Texas - Effects Screening Levels - Long Term  
U.S. - Texas - Effects Screening Levels - Short Term  
U.S. - Vermont - Permissible Exposure Limits - TWAs  
U.S. - Washington - Permissible Exposure Limits - STELs  
U.S. - Washington - Permissible Exposure Limits - TWAs

Silanetriol, ethyl-, triacetate (17689-77-9)

U.S. - Texas - Effects Screening Levels - Long Term

U.S. - Texas - Effects Screening Levels - Short Term

Silanetriol, methyl-, triacetate (4253-34-3)

U.S. - Texas - Effects Screening Levels - Long Term

U.S. - Texas - Effects Screening Levels - Short Term

## SECTION 16: Other Information, Including Date of Preparation or Last Revision

Date of Preparation or Latest Revision 05/13/2019

Revision

# MED10-6655

## Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### Other Information

This Document Has Been Prepared In Accordance With The Sds Requirements Of The Osha Hazard Communication Standard 29 Cfr 1910.1200 This document has been prepared in accordance with the SDS requirements of the OSHA Hazard Communication Standard 29 CFR 1910.1200.

### GHS Full Text Phrases:

Acute Tox. 4 (Inhalation:vapor)	Acute toxicity (inhalation:vapor) Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral) Category 4
Aquatic Acute 3	Hazardous to the aquatic environment - Acute Hazard Category 3
Eye Dam. 1	Serious eye damage/eye irritation Category 1
Eye Irrit. 2A	Serious eye damage/eye irritation Category 2A
Flam. Liq. 2	Flammable liquids Category 2
Skin Corr. 1B	Skin corrosion/irritation Category 1B
Skin Corr. 1C	Skin corrosion/irritation Category 1C
Skin Irrit. 2	Skin corrosion/irritation Category 2
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
H225	Highly flammable liquid and vapor
H302	Harmful if swallowed
H314	Causes severe skin burns and eye damage
H315	Causes skin irritation
H318	Causes serious eye damage
H319	Causes serious eye irritation
H332	Harmful if inhaled
H335	May cause respiratory irritation
H336	May cause drowsiness or dizziness
H402	Harmful to aquatic life

### NFPA Health Hazard

3 - Materials that, under emergency conditions, can cause serious or permanent injury.

### NFPA Fire Hazard

3 - Liquids and solids (including finely divided suspended solids) that can be ignited under almost all ambient temperature conditions.

### NFPA Reactivity Hazard


1 - Materials that in themselves are normally stable but can become unstable at elevated temperatures and pressures.

### HMIS III Rating Health

3 Serious Hazard - Major injury likely unless prompt action is taken and medical treatment is given

### Flammability Physical

3 Serious Hazard  
1 Slight Hazard



The information provided in this Safety Data Sheet (SDS) was prepared based on data believed to

# MED10-6655

## Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

---

be accurate as of the date of this SDS. TO THE GREATEST EXTENT PERMITTED BY LAW, NUSIL TECHNOLOGY LLC AND ITS AFFILIATED COMPANIES ("NUSIL") EXPRESSLY DISCLAIMS ANY AND ALL REPRESENTATIONS AND WARRANTIES REGARDING THE INFORMATION CONTAINED HEREIN INCLUDING, WITHOUT LIMITATION, AS TO ACCURACY, COMPLETENESS, FITNESS FOR PURPOSE OR USE, MERCHANTABILITY, NON-INFRINGEMENT, PERFORMANCE, SAFETY, SUITABILITY AND STABILITY. This SDS is intended as a guide to the appropriate use, handling, storage and disposal of the product to which it relates by properly trained personnel, and is not intended to be comprehensive. Users of NuSil's products are advised to perform their own tests and to exercise their own judgment to determine the safety, suitability and appropriate use, handling, storage and disposal of each product and product combination for their own purposes and uses. TO THE GREATEST EXTENT PERMITTED BY LAW, NUSIL DISCLAIMS LIABILITY FOR, AND BY USING NUSIL'S PRODUCTS PURCHASER AGREES THAT UNDER NO CIRCUMSTANCES SHALL NUSIL BE LIABLE FOR, SPECIAL, INDIRECT, INCIDENTAL, PUNITIVE OR CONSEQUENTIAL DAMAGES OF ANY TYPE OR KIND, INCLUDING WITHOUT LIMITATION, FOR LOSS OF PROFITS, REPUTATIONAL DAMAGE, PRODUCT RECALL OR BUSINESS INTERRUPTION.

Nusil US GHS SDS