R-1008-5





Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations Revision Date:: 05/15/2020 Date of Issue: 07/10/2014

Version 4.0

SECTION 1: Identification

Product Identifier 1.1.

Product Form Mixture Product Name R-1008-5 Synonyms Silicone Ink

1.2. Relevant Identified Uses of the Substance or Mixture and Uses Advised Against

Use of the Substance/Mixture For professional use only.

1.3. Details of the Supplier of the Safety Data Sheet

NuSil Technology LLC 1050 Cindy Lane

Carpinteria, California 93013

USA

(805) 684-8780

ehs@nusil.com

www.nusil.com

Emergency Telephone Number

Emergency 800-424-9300 CHEMTREC (in US); +1 703-527-3887 CHEMTREC (International

Number and Maritime)

SECTION 2: Hazards Identification

Classification of the Substance or Mixture 2.1.

GHS-US Classification

Flam. Liq. 3 H226 Skin Irrit. 2 H315 Eve Irrit, 2A H319 Skin Sens. 1 H317 Repr. 1B H360 STOT SE 3 H336 STOT RE 2 H373 Asp. Tox. 1 H304 Aquatic Acute 2 H401

Full text of hazard classes and H-statements: see section 16

2.2. Label Elements

GHS-US Labeling

Hazard Pictograms (GHS-US)



GHS07



GHS02

Danger

Signal Word (GHS-US)

05/15/2020 EN (English US)

Hazard Statements (GHS-US)

H226 - Flammable liquid and vapor

H304 - May be fatal if swallowed and enters airways

H315 - Causes skin irritation

H317 - May cause an allergic skin reaction

H319 - Causes serious eye irritation

H336 - May cause drowsiness or dizziness

H360 - May damage fertility or the unborn child

H373 - May cause damage to organs through prolonged or repeated exposure

H401 - Toxic to aquatic life

05/15/2020 EN (English US) 2/18

Precautionary Statements (GHS-US)

P201 - Obtain special instructions before use.

P202 - Do not handle until all safety precautions have been read and understood.

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P233 - Keep container tightly closed.

P240 - Ground/Bond container and receiving equipment.

P241 - Use explosion-proof electrical, lighting, ventilating equipment.

P242 - Use only non-sparking tools.

P243 - Take precautionary measures against static discharge.

P260 - Do not breathe vapors, mist, spray.

P264 - Wash hands, forearms, and exposed areas thoroughly after handling.

P271 - Use only outdoors or in a well-ventilated area.

P272 - Contaminated work clothing must not be allowed out of the workplace.

P273 - Avoid release to the environment.

P280 - Wear eye protection, protective clothing, protective gloves.

P301+P310 - If swallowed: Immediately call a poison center or doctor.

P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P304+P340 - If inhaled: Remove person to fresh air and keep at rest in a position comfortable for breathing.

P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P308+P313 - If exposed or concerned: Get medical advice/attention.

P314 - Get medical advice/attention if you feel unwell.

P321 - Specific treatment (see Section 4 on this SDS).

P331 - Do NOT induce vomiting.

P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.

P337+P313 - If eye irritation persists: Get medical advice/attention.

P362+P364 - Take off contaminated clothing and wash it before reuse.

P370+P378 - In case of fire: Use appropriate media to extinguish.

P403+P233+P235 - Store in a well-ventilated place. Keep container tightly closed. Keep cool.

P405 - Store locked up.

P501 - Dispose of contents/container in accordance with local, regional, national, and international regulations.

2.3. Other Hazards

Other Hazards Not Contributing to the Classification

Exposure may aggravate pre-existing eye, skin, or respiratory conditions.

05/15/2020 EN (English US) 3/18

2.4. Unknown Acute Toxicity (GHS-US)

No data available

SECTION 3: Composition/Information On Ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product Identifier	%	GHS-US Classification
Xylenes (o-, m-, p- isomers)	(CAS-No.) 1330-20-7	10 - 30	Flam. Liq. 3, H226 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation:vapor), H332 Skin Irrit. 2, H315 Eye Irrit. 2A, H319 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Acute 2, H401
2-Butanone, O,O',O"- (methylsilylidyne)trioxime	(CAS-No.) 22984-54-9	< 15	Eye Irrit. 2A, H319 Skin Sens. 1B, H317 STOT RE 2, H373
C.I. Pigment Yellow 35	(CAS-No.) 8048-07-5	10 - 20	Comb. Dust
Silanamine, 1,1,1-trimethyl- N-(trimethylsilyl)-, hydrolysis products with silica	(CAS No) 68909-20-6	< 10	Not classified
Dibutyltin dilaurate	(CAS-No.) 77-58-7	< 1	Skin Corr. 1C, H314 Eye Dam. 1, H318 Skin Sens. 1, H317 Muta. 2, H341 Repr. 1B, H360 STOT SE 1, H370 STOT RE 1, H372 Aquatic Acute 1, H400 Aquatic Chronic 1, H410

Full text of H-phrases: see section 16

SECTION 4: First Aid Measures

4.1. Description of First-gid Measures

4.1. Description of filst-dia Measures		
First-aid Measures General	Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).	
	possible).	
First-aid Measures After	When symptoms occur: go into open air and ventilate	
Inhalation	suspected area. Obtain medical attention if breathing difficulty persists.	
First-aid Measures After Skin	Immediately remove contaminated clothing. Immediately	
Contact	drench affected area with water for at least 15 minutes. Obtain medical attention if irritation/rash develops or persists.	

05/15/2020 EN (English US) 4/18

Ingestion

First-aid Measures After Eye Immediately rinse with water for at least 15 minutes. Remove

Contact contact lenses, if present and easy to do. Continue rinsing.

Obtain medical attention.

First-aid Measures After Do NOT induce vomiting. Rinse mouth. Immediately call a

POISON CENTER or doctor/physician. Inaestion

4.2. Most Important Symptoms and Effects Both Acute and Delayed

May cause drowsiness and dizziness. May cause damage to Symptoms/Injuries

organs through prolonged or repeated exposure. Skin

sensitization. Causes skin irritation. Causes serious eye irritation. May damage fertility. May damage the unborn child. May be

fatal if swallowed and enters airways.

Symptoms/Injuries After High concentrations may cause central nervous system

Inhalation depression such as dizziness, vomiting, numbness, drowsiness,

headache, and similar narcotic symptoms.

May cause an allergic skin reaction. Redness, pain, swelling, Symptoms/Injuries After Skin

Contact

itching, burning, dryness, and dermatitis.

Contact causes severe irritation with redness and swelling of the Symptoms/Injuries After Eye Contact

conjunctiva.

Symptoms/Injuries After Aspiration into the lungs can occur during ingestion or vomiting

and may cause lung injury.

Chronic Symptoms May cause damage to organs through prolonged or repeated

exposure. May damage fertility or the unborn child.

Indication of Any Immediate Medical Attention and Special Treatment Needed 4.3.

If exposed or concerned, get medical advice and attention. If medical advice is needed, have product container or label at hand.

SECTION 5: Fire-Fighting Measures

5.1. **Extinguishing Media**

Suitable Extinguishing Media : Dry chemical powder, alcohol-resistant foam, carbon dioxide

(CO₂). Water may be ineffective but water should be used to

keep fire-exposed container cool.

Unsuitable Extinguishing Media : Do not use a heavy water stream. A heavy water stream may

spread burning liquid.

5.2. Special Hazards Arising From the Substance or Mixture

Fire Hazard Flammable liquid and vapor.

Explosion Hazard May form flammable or explosive vapor-air mixture.

Reactivity Reacts violently with strong oxidizers. Increased risk of fire or

explosion.

5.3. **Advice for Firefighters**

Precautionary Measures Fire Exercise caution when fighting any chemical fire.

Firefighting Instructions Use water spray or fog for cooling exposed containers. In case

of major fire and large quantities: Evacuate area. Fight fire

Carbon oxides (CO, CO₂). Silicon oxides. Hydrocarbons.

remotely due to the risk of explosion.

Do not enter fire area without proper protective equipment, **Protection During Firefighting**

including respiratory protection.

Hazardous Combustion

Products

Other Information Do not allow run-off from fire fighting to enter drains or water

courses.

05/15/2020 EN (English US) 5/18

SECTION 6: Accidental Release Measures

6.1. Personal Precautions, Protective Equipment And Emergency Procedures

General Measures Do not get in eyes, on skin, or on clothing. Keep away from

heat, hot surfaces, sparks, open flames, and other ignition sources. No smoking. Use special care to avoid static electric

charges. Do not breathe vapor, mist or spray.

6.1.1. For Non-Emergency Personnel

Protective Equipment Use appropriate personal protective equipment (PPE). Emergency Procedures Evacuate unnecessary personnel. Stop leak if safe to do so.

6.1.2. For emergency responders

Protective Equipment Equip cleanup crew with proper protection.

Emergency Procedures Upon arrival at the scene, a first responder is expected to

recognize the presence of dangerous goods, protect oneself and the public, secure the area, and call for the assistance of trained personnel as soon as conditions permit. Ventilate area.

Eliminate ignition sources.

6.2. Environmental Precautions

Prevent entry to sewers and public waters. Avoid release to the environment.

6.3. Methods and Materials for Containment and Cleaning Up

For Containment Contain any spills with dikes or absorbents to prevent migration

and entry into sewers or streams. As an immediate precautionary measure, isolate spill or leak area in all

directions.

Methods for Cleaning Up Clean up spills immediately and dispose of waste safely.

Transfer spilled material to a suitable container for disposal. Contact competent authorities after a spill. Absorb and/or contain spill with inert material. Do not take up in combustible material such as: saw dust or cellulosic material. Use only non-

sparking tools.

6.4. Reference to Other Sections

See Section 8 for exposure controls and personal protection and Section 13 for disposal considerations.

SECTION 7: Handling And Storage

7.1. Precautions for Safe Handling

Additional Hazards When Handle empty containers with care because residual vapors

Processed are flammable.

Precautions for Safe Handling Wash hands and other exposed areas with mild soap and

water before eating, drinking or smoking and when leaving work. Take precautionary measures against static discharge. Use only non-sparking tools. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not breathe vapors, mist, spray. Avoid

contact with skin, eyes and clothing.

Hygiene Measures Handle in accordance with good industrial hygiene and safety

procedures.

05/15/2020 EN (English US) 6/18

7.2. Conditions for Safe Storage, Including Any Incompatibilities

Technical Measures Comply with applicable regulations. Take action to prevent

static discharges. Ground and bond container and receiving equipment. Use explosion-proof electrical, ventilating, and

lighting equipment.

Storage Conditions Store in a dry, cool place. Keep/Store away from direct sunlight,

extremely high or low temperatures and incompatible materials. Store locked up/in a secure area. Store in a well-ventilated place. Keep container tightly closed. Keep in

fireproof place.

Incompatible Materials Strong acids, strong bases, strong oxidizers.

7.3. Specific End Use(S)

As a marking ink for silicone rubber parts and other components where the coating must maintain long term stability. For professional use only.

SECTION 8: Exposure Controls/Personal Protection

8.1. Control Parameters

For substances listed in section 3 that are not listed here, there are no established exposure limits from the manufacturer, supplier, importer, or the appropriate advisory agency including: ACGIH (TLV), or OSHA (PEL).

Xylenes (o-, m-, p- isomers) (1330-20-7)		
USA ACGIH	ACGIH TWA (ppm)	100 ppm
USA ACGIH	ACGIH STEL (ppm)	150 ppm
USA ACGIH	ACGIH chemical category	Not Classifiable as a Human
		Carcinogen
USA ACGIH	Biological Exposure Indices (BEI)	1.5 g/g Kreatinin Parameter:
		Methylhippuric acids - Medium: urine -
		Sampling time: end of shift
USA OSHA	OSHA PEL (TWA) (mg/m³)	435 mg/m³
USA OSHA	OSHA PEL (TWA) (ppm)	100 ppm
Silanamine, 1,1,1	-trimethyl-N-(trimethylsilyl)-, hydrolysis pro	oducts with silica (68909-20-6)
USA OSHA	OSHA PEL (TWA) (mg/m³)	6 mg/m³
USA OSHA	OSHA PEL (TWA) (ppm)	20 mppcf (80mg/m³/%SiO ₂)
Tin organic comp	pounds	
USA ACGIH	ACGIH TWA (mg/m³)	0.1 mg/m³
USA ACGIH	ACGIH STEL (mg/m³)	0.2 mg/m³
USA ACGIH	ACGIH chemical category	Skin - potential significant contribution
		to overall exposure by the cutaneous
		route,Not Classifiable as a Human
		Carcinogen
USA OSHA	OSHA PEL (TWA) (mg/m³)	0.1 mg/m³
Cadmium comp	ounds	
USA ACGIH	ACGIH TWA (mg/m³)	0.01 mg/m³
		0.002 mg/m³ (respirable particulate matter)
USA ACGIH	ACGIH chemical category	Suspected Human Carcinogen

05/15/2020 EN (English US) 7/1

8.2. Exposure Controls

Appropriate Engineering Emergency eye wash fountains and safety showers should be Controls available in the immediate vicinity of any potential exposure.

Ensure adequate ventilation, especially in confined areas. Ensure all national/local regulations are observed. Gas

detectors should be used when flammable gases or vapors may be released. Proper grounding procedures to avoid static electricity should be followed. Use explosion-proof equipment.

Gloves. Protective clothing. Protective goggles. Insufficient

ventilation: wear respiratory protection.









Materials For Protective

Personal Protective Equipment

Clothing

Hand Protection Eye And Face Protection Skin And Body Protection Respiratory Protection Chemically resistant materials and fabrics. Wear fire/flame resistant/retardant clothing

resistant/retardant clothing. Wear protective gloves.

Chemical safety goggles.

Wear suitable protective clothing.

If exposure limits are exceeded or irritation is experienced, approved respiratory protection should be worn. In case of inadequate ventilation, oxygen deficient atmosphere, or where exposure levels are not known wear approved

respiratory protection.

Other Information When using, do not eat, drink or smoke.

SECTION 9: Physical and Chemical Properties

9.1. Information on Basic Physical and Chemical Properties

Physical State Liquid
Appearance Yellow
Odor Solvent

Odor Threshold

pH

No data available

27 °C (81 °F)

Auto-ignition Temperature

Decomposition Temperature

No data available

Specific Gravity > 1

Solubility
Partition Coefficient n-Octanol/Water
Viscosity
No data available
No data available
No data available

05/15/2020 EN (English US) 8/18

9.2. Other Information

VOC Content 10 - 30 %

SECTION 10: Stability and Reactivity

10.1. Reactivity

Reacts violently with strong oxidizers. Increased risk of fire or explosion.

10.2. Chemical Stability

Flammable liquid and vapor. May form flammable or explosive vapor-air mixture.

10.3. Possibility of Hazardous Reactions

Hazardous polymerization will not occur.

10.4. Conditions to Avoid

Direct sunlight, extremely high or low temperatures, heat, hot surfaces, sparks, open flames, incompatible materials, and other ignition sources.

10.5. Incompatible Materials

Strong acids, strong bases, strong oxidizers.

10.6. Hazardous Decomposition Products

None expected under normal conditions of use.

SECTION 11: Toxicological Information

11.1. Information on Toxicological Effects

Acute Toxicity (Oral) : Not classified Acute Toxicity (Dermal) : Not classified Acute Toxicity (Inhalation) : Not classified

Xylenes (o-, m-, p- isomers) (1330-20-7)		
LD50 Oral Rat	> 5000 mg/kg	
LC50 Inhalation Rat	6247 ppm/4h (species: Sprague-Dawley)	
ATE (Dermal)	1,100.00 mg/kg body weight	
ATE (Vapors)	11.00 mg/l/4h	
2-Butanone, O,O',O"-(methylsilylidyne)trioxime (22984-54-9)		
LD50 Oral Rat	2463 mg/kg	
LD50 Dermal Rat	> 2000 mg/kg	
Dibutyltin dilaurate (77-58-7)		
LD50 Dermal Rat	> 2 g/kg	

Skin Corrosion/Irritation Causes skin irritation.

Serious Eye Damage/Irritation Causes serious eye irritation.

Respiratory or Skin Sensitization May cause an allergic skin reaction.

Germ Cell Mutagenicity Not classified Carcinogenicity Not classified

Xylenes (o-, m-, p- isomers) (1330	-20-7)
IARC Group	3

Reproductive Toxicity : May damage fertility or the unborn child.

Specific Target Organ Toxicity (Single : May cause drowsiness or dizziness.

Exposure)

Aspiration Hazard

Specific Target Organ Toxicity (Repeated : May cause damage to organs through prolonged

Exposure) or repeated exposure.

05/15/2020 EN (English US) 9/18

May be fatal if swallowed and enters airways.

R-1008-5

Contact

Ingestion

Safety Data Sheet

Symptoms/Injuries After Eye

Symptoms/Injuries After

Chronic Symptoms

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulation

Symptoms/Injuries After High concentrations may cause central nervous system

Inhalation depression such as dizziness, vomiting, numbness, drowsiness,

headache, and similar narcotic symptoms.

Symptoms/Injuries After Skin May cause an allergic skin reaction. Redness, pain, swelling, Contact

itching, burning, dryness, and dermatitis.

Contact causes severe irritation with redness and swelling of

the conjunctiva.

Aspiration into the lungs can occur during ingestion or vomiting

and may cause lung injury.

May cause damage to organs through prolonged or repeated

exposure. May damage fertility or the unborn child.

SECTION 12: Ecological Information

12.1. Toxicity

Ecology - General Toxic to aquatic life.

Xylenes (o-, m-, p- isomers) (1330-20-7)		
LC50 Fish 1	3.3 mg/l	
EC50 Daphnia 1	3.82 mg/l (Exposure time: 48 h - Species: water flea)	
LC50 Fish 2	2.661 (2.661 - 4.093) mg/l (Exposure time: 96 h - Species:	
	Oncorhynchus mykiss [static])	
2-Butanone, O,O',O"-(methylsilylidyne)trioxime (22984-54-9)		
EC50 Daphnia 1	120 mg/l (Exposure time: 48h - Species: Daphnia magna)	
Dibutyltin dilaurate (77-58-7)		
EC50 Daphnia 1	0.463 mg/l (Daphnia magna)	

12.2. Persistence and Degradability

R-1008-5	•
Persistence and Degradability	Not established.

12.3. Bioaccumulative Potential

R-1008-5		
Bioaccumulative Potential	Not established.	
Xylenes (o-, m-, p- isomers) (1330-20-7)		
BCF Fish 1	0.6 (0.6 - 15)	
Log Pow	2.77 - 3.15	
Dibutyltin dilaurate (77-58-7)		
Log Pow	4.44	

12.4. Mobility In Soil

No additional information available

12.5. Other Adverse Effects

Other Information Avoid release to the environment.

SECTION 13: Disposal Considerations

13.1. Waste Treatment Methods

Waste Disposal	Dispose of contents/container in accordance with local,
Recommendations	regional, national, and international regulations.

Additional Information Handle empty containers with care because residual vapors

are flammable.

05/15/2020 EN (English US) 10/18 **Ecology - Waste Materials**

Avoid release to the environment. This material is hazardous to the aquatic environment. Keep out of sewers and waterways.

SECTION 14: Transport Information

The shipping description(s) stated herein were prepared in accordance with certain assumptions at the time the SDS was authored, and can vary based on a number of variables that may or may not have been known at the time the SDS was issued.

14.1. In Accordance with DOT

Proper Shipping Name XYLENES SOLUTION

Hazard Class 3

Identification Number UN1307

Label Codes 3
Packing Group III
ERG Number 130



14.2. In Accordance with IMDG

Proper Shipping Name XYLENES SOLUTION

Hazard Class 3

Identification Number UN1307

Packing Group III
Label Codes 3
EmS-No. (Fire) F-E
EmS-No. (Spillage) S-D
MFAG Number 130



14.3. In Accordance with IATA

Proper Shipping Name XYLENES SOLUTION

Packing Group III

Identification Number UN1307

Hazard Class 3 Label Codes 3 ERG Code (IATA) 3L



SECTION 15: Regulatory Information

15.1. US Federal Regulations

All components in this mixture are listed on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory, have been exempted, are not listed, not disclosed due to CBI requirements or disclosure rules according to the relevant regulation.

R-1008-5	
SARA Section 311/312 Hazard	Health hazard - Specific target organ toxicity (single or repeated
Classes	exposure)
	Health hazard - Respiratory or skin sensitization
	Health hazard - Skin corrosion or Irritation
	Physical hazard - Flammable (gases, aerosols, liquids, or solids)
	Health hazard - Serious eye damage or eye irritation
	Health hazard - Reproductive toxicity
	Health hazard - Aspiration hazard
Xylenes (o-, m-, p- isomers) (1330-20-7)	

05/15/2020 EN (English US) 11/18

R-1008-5

Safety Data Sheet According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Subject to reporting requirements of United States SARA Section 313		
CERCLA RQ	100 lb	
SARA Section 313 - Emission	1 %	
Reporting		
Cadmium compounds		
Subject to reporting requirements of United States SARA Section 313		
SARA Section 313 - Emission	0.1 %	
Reporting		

15.2 **US State Regulations**

13.2. US Sidie Regulations		
Xylenes (o-, m-, p- isomers) (1330-20-7)		
U.S California - Proposition 65 - Carcinogens List	WARNING: This product contains chemicals known to the State of California to cause	
	cancer.	
Cadmium compounds		
U.S California - Proposition 65 - Carcinogens List	WARNING: This product contains chemicals known to the State of California to cause cancer.	
Xylenes (o-, m-, p- isomers) (1330-20-7)		

05/15/2020 EN (English US) 12/18

- U.S. California SCAQMD Toxic Air Contaminants Non-Cancer Acute
- U.S. California SCAQMD Toxic Air Contaminants Non-Cancer Chronic
- U.S. California Toxic Air Contaminant List (AB 1807, AB 2728)
- U.S. Colorado Groundwater Quality Standards
- U.S. Colorado Hazardous Wastes Discarded Chemical Products, Off-Specification Species, Container and Spill Residues
- U.S. Colorado Primary Drinking Water Regulations Maximum Contaminant Level Goals (MCLGs)
- U.S. Colorado Primary Drinking Water Regulations Maximum Contaminant Levels (MCLs)
- U.S. Connecticut Drinking Water Quality Standards Maximum Contaminant Levels
- U.S. Delaware Pollutant Discharge Requirements Reportable Quantities
- U.S. Florida Drinking Water Standards Volatile Organic Contaminants Maximum Contaminant Levels (MCLs)
- U.S. Georgia Drinking Water Maximum Contaminant Levels (MCLs)
- U.S. Idaho Non-Carcinogenic Toxic Air Pollutants Acceptable Ambient Concentrations
- U.S. Idaho Non-Carcinogenic Toxic Air Pollutants Emission Levels (ELs)
- U.S. Idaho Occupational Exposure Limits TWAs
- U.S. Illinois Toxic Air Contaminants
- U.S. Louisiana Reportable Quantity List for Pollutants
- U.S. Maine Air Pollutants Hazardous Air Pollutants
- U.S. Massachusetts Allowable Ambient Limits (AALs)
- U.S. Massachusetts Allowable Threshold Concentrations (ATCs)
- U.S. Massachusetts Drinking Water Maximum Contaminant Levels (MCLs)
- U.S. Massachusetts Oil & Hazardous Material List Groundwater Reportable Concentration Reporting Category 1
- U.S. Massachusetts Oil & Hazardous Material List Groundwater Reportable Concentration Reporting Category 2
- U.S. Massachusetts Oil & Hazardous Material List Reportable Quantity
- U.S. Massachusetts Oil & Hazardous Material List Soil Reportable Concentration Reporting Category 1
- U.S. Massachusetts Oil & Hazardous Material List Soil Reportable Concentration Reporting Category 2
- RTK U.S. Massachusetts Right To Know List
- U.S. Massachusetts Threshold Effects Exposure Limits (TELs)
- U.S. Massachusetts Toxics Use Reduction Act
- U.S. Michigan Occupational Exposure Limits STELs
- U.S. Michigan Occupational Exposure Limits TWAs
- U.S. Michigan Polluting Materials List
- U.S. Minnesota Chemicals of High Concern
- U.S. Minnesota Groundwater Health Risk Limits
- U.S. Minnesota Hazardous Substance List
- U.S. Minnesota Permissible Exposure Limits STELs
- U.S. Minnesota Permissible Exposure Limits TWAs
- U.S. Missouri Drinking Water Maximum Contaminant Levels (MCLs)
- U.S. Nebraska Drinking Water Maximum Contaminant Levels (MCLs)
- U.S. New Hampshire Drinking Water Maximum Contaminant Levels (MCLs)
- U.S. New Hampshire Regulated Toxic Air Pollutants Ambient Air Levels (AALs) 24-Hour
- U.S. New Hampshire Regulated Toxic Air Pollutants Ambient Air Levels (AALs) Annual
- U.S. New Jersey Discharge Prevention List of Hazardous Substances
- U.S. New Jersey Environmental Hazardous Substances List
- U.S. New Jersey Primary Drinking Water Standards Maximum Contaminant Levels MCLs

05/15/2020 EN (English US) 13/18

- RTK U.S. New Jersey Right to Know Hazardous Substance List
- U.S. New Jersey Special Health Hazards Substances List
- U.S. New Jersey Water Quality Ground Water Quality Criteria
- U.S. New Jersey Water Quality Practical Quantitation Levels (PQLs)
- U.S. New Mexico Water Quality Standards for Ground Water of 10,000 mg/L TDS Concentration or Less
- U.S. New York Occupational Exposure Limits TWAs
- U.S. New York Reporting of Releases Part 597 List of Hazardous Substances
- U.S. North Carolina Control of Toxic Air Pollutants
- U.S. North Dakota Air Pollutants Guideline Concentrations 1-Hour
- U.S. North Dakota Air Pollutants Guideline Concentrations 8-Hour
- U.S. North Dakota Hazardous Wastes Discarded Chemical Products, Off-Specification Species, Container and Spill Residues
- U.S. North Dakota Water Quality Standards Human Health Value for Classes I, IA, II
- U.S. Oregon Permissible Exposure Limits TWAs
- U.S. California Safer Consumer Products Initial List of Candidate Chemicals and Chemical Groups
- U.S. Pennsylvania Drinking Water Maximum Contaminant Levels (MCLs)
- RTK U.S. Pennsylvania RTK (Right to Know) Environmental Hazard List
- RTK U.S. Pennsylvania RTK (Right to Know) List
- U.S. Rhode Island Air Toxics Acceptable Ambient Levels 1-Hour
- U.S. Rhode Island Air Toxics Acceptable Ambient Levels 24-Hour
- U.S. Rhode Island Air Toxics Acceptable Ambient Levels Annual
- U.S. Rhode Island Water Quality Standards Acute Freshwater Aquatic Life Criteria

All concentrations are expressed as percentages by weight unless the ingredient is a gas.

- U.S. South Carolina Maximum Contaminant Levels (MCLs)
- U.S. South Carolina Toxic Air Pollutants Maximum Allowable Concentrations
- U.S. South Carolina Toxic Air Pollutants Pollutant Categories
- U.S. Tennessee Occupational Exposure Limits STELs
- U.S. Tennessee Occupational Exposure Limits TWAs
- U.S. Texas City of Austin Aerosol Paint and Glue Restrictions
- U.S. Texas Drinking Water Standards Maximum Contaminant Levels (MCLs)
- U.S. Texas Effects Screening Levels Long Term
- U.S. Texas Effects Screening Levels Short Term
- U.S. Utah Drinking Water Maximum Contaminant Levels (MCLs)
- U.S. Washington Dangerous Waste Discarded Chemical Products List
- U.S. Washington Permissible Exposure Limits STELs
- U.S. Washington Permissible Exposure Limits TWAs
- U.S. West Virginia Water Quality Groundwater Standards Ceiling Concentrations
- U.S. Wisconsin Hazardous Air Contaminants All Sources Emissions From Stack Heights 25 Feet to Less Than 40 Feet
- U.S. Wisconsin Hazardous Air Contaminants All Sources Emissions From Stack Heights 40 Feet to Less Than 75 Feet
- U.S. Wisconsin Hazardous Air Contaminants All Sources Emissions From Stack Heights 75 Feet or Greater
- U.S. Wisconsin Hazardous Air Contaminants All Sources Emissions From Stack Heights Less Than 25 Feet
- 2-Butanone, O,O',O"-(methylsilylidyne)trioxime (22984-54-9)
- U.S. Texas Effects Screening Levels Long Term
- U.S. Texas Effects Screening Levels Short Term

05/15/2020 EN (English US) 14/18

Dibutyltin dilaurate (77-58-7)

- U.S. New Hampshire Regulated Toxic Air Pollutants Ambient Air Levels (AALs) 24-Hour
- U.S. New Hampshire Regulated Toxic Air Pollutants Ambient Air Levels (AALs) Annual
- U.S. California Safer Consumer Products Initial List of Candidate Chemicals and Chemical Groups
- U.S. Texas Effects Screening Levels Long Term
- U.S. Texas Effects Screening Levels Short Term

Tin organic compounds

- U.S. Connecticut Hazardous Air Pollutants HLVs (30 min)
- U.S. Connecticut Hazardous Air Pollutants HLVs (8 hr)
- U.S. Idaho Non-Carcinogenic Toxic Air Pollutants Acceptable Ambient Concentrations
- U.S. Idaho Non-Carcinogenic Toxic Air Pollutants Emission Levels (ELs)
- U.S. Idaho Occupational Exposure Limits TWAs
- U.S. Michigan Occupational Exposure Limits Skin Designations
- U.S. Michigan Occupational Exposure Limits TWAs
- U.S. Minnesota Hazardous Substance List
- U.S. Minnesota Permissible Exposure Limits Skin Designations
- U.S. Minnesota Permissible Exposure Limits TWAs
- U.S. New Hampshire Regulated Toxic Air Pollutants Ambient Air Levels (AALs) 24-Hour
- U.S. New Hampshire Regulated Toxic Air Pollutants Ambient Air Levels (AALs) Annual
- U.S. New York Occupational Exposure Limits Skin Designations
- U.S. New York Occupational Exposure Limits TWAs
- U.S. North Dakota Air Pollutants Guideline Concentrations 1-Hour
- U.S. North Dakota Air Pollutants Guideline Concentrations 8-Hour
- U.S. Oregon Permissible Exposure Limits TWAs
- U.S. Tennessee Occupational Exposure Limits Skin Designations
- U.S. Tennessee Occupational Exposure Limits TWAs
- U.S. Texas Effects Screening Levels Long Term
- U.S. Texas Effects Screening Levels Short Term
- U.S. Vermont Permissible Exposure Limits Skin Designations
- U.S. Vermont Permissible Exposure Limits TWAs
- U.S. Washington Permissible Exposure Limits Skin Designations
- U.S. Washington Permissible Exposure Limits STELs
- U.S. Washington Permissible Exposure Limits TWAs
- U.S. Wisconsin Hazardous Air Contaminants All Sources Emissions From Stack Heights 25 Feet to Less Than 40 Feet
- U.S. Wisconsin Hazardous Air Contaminants All Sources Emissions From Stack Heights 40 Feet to Less Than 75 Feet
- U.S. Wisconsin Hazardous Air Contaminants All Sources Emissions From Stack Heights 75 Feet or Greater
- U.S. Wisconsin Hazardous Air Contaminants All Sources Emissions From Stack Heights Less Than 25 Feet

Cadmium compounds

05/15/2020 EN (English US) 15/18

- U.S. California SCAQMD Toxic Air Contaminants Carcinogens
- U.S. California SCAQMD Toxic Air Contaminants Non-Cancer Chronic
- U.S. California SDAPCD Toxic Air Contaminants Carcinogenic Impacts Must Be Calculated
- U.S. California Toxic Air Contaminant List (AB 1807, AB 2728)
- U.S. Idaho Carcinogenic Toxic Air Pollutants Acceptable Ambient Concentrations
- U.S. Idaho Carcinogenic Toxic Air Pollutants Emission Levels (ELs)
- U.S. Illinois Toxic Air Contaminant Carcinogens
- U.S. Illinois Toxic Air Contaminants
- U.S. Maine Air Pollutants Hazardous Air Pollutants
- U.S. Maine Chemicals of Concern
- U.S. Massachusetts Oil & Hazardous Material List Groundwater Reportable Concentration Reporting Category 1
- U.S. Massachusetts Oil & Hazardous Material List Groundwater Reportable Concentration Reporting Category 2
- U.S. Massachusetts Oil & Hazardous Material List Reportable Quantity
- U.S. Massachusetts Oil & Hazardous Material List Soil Reportable Concentration Reporting Category 1
- U.S. Massachusetts Oil & Hazardous Material List Soil Reportable Concentration Reporting Category 2
- U.S. Massachusetts Toxics Use Reduction Act
- U.S. Michigan Polluting Materials List
- U.S. Minnesota Hazardous Substance List
- U.S. New Hampshire Prohibited Volatile Organic Compounds
- U.S. New Hampshire Regulated Toxic Air Pollutants Ambient Air Levels (AALs) 24-Hour
- U.S. New Hampshire Regulated Toxic Air Pollutants Ambient Air Levels (AALs) Annual
- U.S. New Jersey Discharge Prevention List of Hazardous Substances
- U.S. New Jersey Environmental Hazardous Substances List
- RTK U.S. New Jersey Right to Know Hazardous Substance List
- U.S. New Jersey Special Health Hazards Substances List
- U.S. North Dakota Air Pollutants Guideline Concentrations 8-Hour
- U.S. North Dakota Air Pollutants Unit Risk Factors
- U.S. Oregon Priority Persistent Pollutant Tier I Persistent Pollutants
- U.S. California Safer Consumer Products Initial List of Candidate Chemicals and Chemical Groups
- RTK U.S. Pennsylvania RTK (Right to Know) Environmental Hazard List
- RTK U.S. Pennsylvania RTK (Right to Know) List
- U.S. Rhode Island Air Toxics Acceptable Ambient Levels 24-Hour
- U.S. Rhode Island Air Toxics Acceptable Ambient Levels Annual
- U.S. Texas Effects Screening Levels Short Term
- U.S. Vermont Hazardous Waste Hazardous Constituents
- U.S. Washington Dangerous Waste Dangerous Waste Constituents List
- U.S. Wisconsin Hazardous Air Contaminants All Sources Emissions From Stack Heights 25 Feet to Less Than 40 Feet
- U.S. Wisconsin Hazardous Air Contaminants All Sources Emissions From Stack Heights 40 Feet to Less Than 75 Feet
- U.S. Wisconsin Hazardous Air Contaminants All Sources Emissions From Stack Heights 75 Feet or Greater
- U.S. Wisconsin Hazardous Air Contaminants All Sources Emissions From Stack Heights Less Than 25 Feet

05/15/2020 EN (English US) 16/18

Silanamine, 1,1,1-trimethyl-N-(trimethylsilyl)-, hydrolysis products with silica (68909-20-6)

U.S. - Texas - Effects Screening Levels - Long Term U.S. - Texas - Effects Screening Levels - Short Term

SECTION 16: Other Information, Including Date of Preparation or Last Revision

Date of Preparation or Latest

SŤ

Revision

Other Information This document has been prepared in accordance with the SDS

requirements of the OSHA Hazard Communication Standard 29

CFR 1910.1200.

05/15/2020

GHS Full Text Phrases:

ruii text rituses.	
Acute Tox. 4 (Dermal)	Acute toxicity (dermal) Category 4
Acute Tox. 4 (Inhalation)	Acute toxicity (inhalation) Category 4
Acute Tox. 4 (Inhalation:vapor)	Acute toxicity (inhalation:vapor) Category 4
Aquatic Acute 1	Hazardous to the aquatic environment - Acute
	Hazard Category 1
Aquatic Acute 2	Hazardous to the aquatic environment - Acute
	Hazard Category 2
Aquatic Chronic 1	Hazardous to the aquatic environment - Chronic
	Hazard Category 1
Asp. Tox. 1	Aspiration hazard Category 1
Comb. Dust	Combustible Dust
Eye Dam. 1	Serious eye damage/eye irritation Category 1
Eye Irrit. 2A	Serious eye damage/eye irritation Category 2A
Flam. Liq. 3	Flammable liquids Category 3
Muta. 2	Germ cell mutagenicity Category 2
Repr. 1B	Reproductive toxicity Category 1B
Skin Corr. 1C	Skin corrosion/irritation Category 1C
Skin Irrit. 2	Skin corrosion/irritation Category 2
Skin Sens. 1	Skin sensitization, Category 1
Skin Sens. 1B	Skin sensitization, category 1B
STOT RE 1	Specific target organ toxicity (repeated exposure) Category 1
STOT RE 2	Specific target organ toxicity (repeated exposure)
STOTIKE Z	Category 2
STOT SE 1	Specific target organ toxicity (single exposure)
	Category 1
STOT SE 3	Specific target organ toxicity (single exposure)
	Category 3
H226	Flammable liquid and vapor
H304	May be fatal if swallowed and enters airways
H312	Harmful in contact with skin
H314	Causes severe skin burns and eye damage
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H318	Causes serious eye damage
-	

05/15/2020 EN (English US) 17/18

	-
H319	Causes serious eye irritation
H332	Harmful if inhaled
H336	May cause drowsiness or dizziness
H341	Suspected of causing genetic defects
H360	May damage fertility or the unborn child
H370	Causes damage to organs
H372	Causes damage to organs through prolonged or
	repeated exposure
H373	May cause damage to organs through prolonged
	or repeated exposure
H400	Very toxic to aquatic life
H401	Toxic to aquatic life
H410	Very toxic to aquatic life with long lasting effects

NFPA Health Hazard 2 - Materials that, under emergency

conditions, can cause temporary incapacitation or residual injury.

NFPA Fire Hazard 3 - Liquids and solids (including finely

divided suspended solids) that can be ignited under almost all ambient

temperature conditions.

NFPA Reactivity Hazard 0 - Material that in themselves are

normally stable, even under fire

conditions.

HMIS III Rating

Health 2 Moderate Hazard

* Chronic - Chronic (long-term) health effects may result from

repeated overexposure

Flammability 3 Serious Hazard
Physical 0 Minimal Hazard

The information provided in this Safety Data Sheet (SDS) was prepared based on data believed to be accurate as of the date of this SDS. TO THE GREATEST EXTENT PERMITTED BY LAW, NUSIL TECHNOLOGY LLC AND ITS AFFILIATED COMPANIES ("NUSIL") EXPRESSLYDISCLAIMS ANY AND ALL REPRESENTATIONS AND WARRANTIES REGARDING THE INFORMATION CONTAINED HEREIN INCLUDING, WITHOUT LIMITATION, AS TO ACCURACY, COMPLETENESS, FITNESS FOR PURPOSE OR USE, MERCHANTABILITY, NON-INFRINGEMENT, PERFORMANCE, SAFETY, SUITABILITY AND STABILITY. This SDS is intended as a guide to the appropriate use, handling, storage and disposal of the product to which it relates by properly trained personnel, and is not intended to be comprehensive. Users of NuSil's products are advised to perform their own tests and to exercise their own judgment to determine the safety, suitability and appropriate use, handling, storage and disposal of each product and product combination for their own purposes and uses. TO THE GREATEST EXTENT PERMITTED BY LAW, NUSIL DISCLAIMS LIABILITY FOR, AND BY USING NUSIL'S PRODUCTS PURCHASER AGREES THAT UNDER NO CIRCUMSTANCES SHALL NUSIL BE LIABLE FOR, SPECIAL, INDIRECT, INCIDENTAL, PUNITIVE OR CONSEQUENTIAL DAMAGES OF ANY TYPE OR KIND. INCLUDING WITHOUT LIMITATION, FOR LOSS OF PROFITS, REPUTATIONAL DAMAGE, PRODUCT RECALL OR BUSINESS INTERRUPTION.

Nusil US GHS SDS

05/15/2020 EN (English US) 18/1