

MED16-6606

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations
Revision Date: 10/12/2022 Date of Issue: 05/15/2014

SECTION 1: Identification

1.1. Product Identifier

Product Form Mixture
Product Name MED16-6606
Synonyms Silicone Dispersion

1.2. Relevant Identified Uses of the Substance or Mixture and Uses Advised Against

Use of the Substance/Mixture For professional use only.

1.3. Details of the Supplier of the Safety Data Sheet

NuSil Technology LLC
1050 Cindy Lane
Carpinteria, California 93013
USA
(805) 684-8780
productstewardship@avantorsciencesgcc.com
www.nusil.com

1.4. Emergency Telephone Number

Emergency Number 800-424-9300 CHEMTREC (in US)
+1 703-527-3887 CHEMTREC (International and Maritime)

SECTION 2: Hazards Identification

2.1. Classification of the Substance or Mixture

GHS-US Classification

Flammable liquids Category 2	H225
Skin corrosion/irritation Category 2	H315
Serious eye damage/eye irritation Category 1	H318
Reproductive toxicity Category 2	H361
Specific target organ toxicity — Single exposure, Category 3, Narcosis	H336
Aspiration hazard Category 1	H304
Hazardous to the aquatic environment - Chronic Hazard Category 1	H410

2.2. Label Elements

GHS-US Labeling

Hazard Pictograms (GHS-US)



GHS02

GHS05

GHS07

GHS08

GHS09

Signal Word (GHS-US)

Danger

Hazard Statements (GHS-US)

H225 - Highly flammable liquid and vapor
H304 - May be fatal if swallowed and enters airways
H315 - Causes skin irritation
H318 - Causes serious eye damage
H336 - May cause drowsiness or dizziness
H361 - Suspected of damaging fertility or the unborn child
H410 - Very toxic to aquatic life with long lasting effects
P201 - Obtain special instructions before use.
P202 - Do not handle until all safety precautions have been

Precautionary Statements (GHS-US)

MED16-6606

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

read and understood.

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P233 - Keep container tightly closed.

P240 - Ground/Bond container and receiving equipment.

P241 - Use explosion-proof electrical, lighting, ventilating equipment.

P242 - Use only non-sparking tools.

P243 - Take precautionary measures against static discharge.

P261 - Avoid breathing vapors, mist, or spray.

P264 - Wash hands, forearms, and exposed areas thoroughly after handling.

P271 - Use only outdoors or in a well-ventilated area.

P273 - Avoid release to the environment.

P280 - Wear eye protection, protective clothing, protective gloves, face protection.

P301+P310 - If swallowed: Immediately call a poison center or doctor.

P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P304+P340 - If inhaled: Remove person to fresh air and keep at rest in a position comfortable for breathing.

P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P308+P313 - If exposed or concerned: Get medical advice/attention.

P310 - Immediately call a poison center or doctor.

P321 - Specific treatment (see Section 4 on this SDS).

P331 - Do NOT induce vomiting.

P332+P313 - If skin irritation occurs: Get medical advice/attention.

P362+P364 - Take off contaminated clothing and wash it before reuse.

P370+P378 - In case of fire: Use appropriate media to extinguish.

P391 - Collect spillage.

P403+P235 - Store in a well-ventilated place. Keep cool.

P405 - Store locked up.

P501 - Dispose of contents/container in accordance with local, regional, national, and international regulations.

2.3. Other Hazards

Other Hazards Not Contributing to the Classification

Exposure may aggravate pre-existing eye, skin, or respiratory conditions.

2.4. Unknown Acute Toxicity (GHS-US)

No additional information available

MED16-6606

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 3: Composition/Information On Ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product Identifier	%	GHS-US Classification
Heptane, branched, cyclic and linear	(CAS-No.) 426260-76-6	60 – 70	Flam. Liq. 2, H225 Skin Irrit. 2, H315 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Chronic 1, H410
Silanamine, 1,1,1-trimethyl-N-(trimethylsilyl)-, hydrolysis products with silica	(CAS-No.) 68909-20-6	5 – 10	Not classified
Silanetriol, ethyl-, triacetate	(CAS-No.) 17689-77-9	< 5	Acute Tox. 4 (Oral), H302 Skin Corr. 1B, H314 Eye Dam. 1, H318
Glycidoxypropyltrimethoxysilane	(CAS-No.) 2530-83-8	< 1	Eye Dam. 1, H318 Aquatic Acute 3, H402 Aquatic Chronic 3, H412
Octamethylcyclotetrasiloxane	(CAS-No.) 556-67-2	< 1	Flam. Liq. 3, H226 Repr. 2, H361 Aquatic Chronic 1, H410
Dibutyltin diacetate	(CAS-No.) 1067-33-0	< 0.1	Skin Corr. 1B, H314 Eye Dam. 1, H318 Skin Sens. 1B, H317 Muta. 2, H341 Repr. 1B, H360 STOT SE 1, H370 STOT RE 1, H372 Aquatic Acute 1, H400 Aquatic Chronic 1, H410

Full text of H-phrases: see section 1.6

SECTION 4: First Aid Measures

4.1. Description of First-aid Measures

First-aid Measures General

Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

First-aid Measures After Inhalation

If inhaled, remove to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER/doctor/physician if you feel unwell.

First-aid Measures After Skin Contact

Remove contaminated clothing. Gently wash with plenty of soap and water followed by rinsing with water for at least 15 minutes. Call a POISON CENTER or doctor/physician if you feel unwell. Wash contaminated clothing before reuse. If exposed or concerned: Get medical advice/attention.

MED16-6606

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

First-aid Measures After Eye Contact Immediately rinse with water for at least 30 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get immediate medical advice/attention.

First-aid Measures After Ingestion Place affected person on their side. Do NOT induce vomiting. Rinse mouth. Immediately call a POISON CENTER or doctor/physician.

4.2. Most Important Symptoms and Effects Both Acute and Delayed

Symptoms/Injuries Causes skin irritation. Causes serious eye damage. May cause drowsiness and dizziness. May be fatal if swallowed and enters airways. Suspected of damaging fertility or the unborn child. Symptoms/Injuries After Inhalation High concentrations may cause central nervous system depression such as dizziness, vomiting, numbness, drowsiness, headache, and similar narcotic symptoms.

Symptoms/Injuries After Skin Contact Redness, pain, swelling, itching, burning, dryness, and dermatitis.

Symptoms/Injuries After Eye Contact Causes permanent damage to the cornea, iris, or conjunctiva.

Symptoms/Injuries After Ingestion Aspiration into the lungs can occur during ingestion or vomiting and may cause lung injury.

Chronic Symptoms Suspected of damaging fertility or the unborn child.

4.3. Indication of Any Immediate Medical Attention and Special Treatment Needed

If medical advice is needed, have product container or label at hand. If exposed or concerned, get medical advice and attention.

SECTION 5: Fire-Fighting Measures

5.1. Extinguishing Media

Suitable Extinguishing Media : Dry chemical powder, alcohol-resistant foam, carbon dioxide (CO₂). Water may be ineffective but water should be used to keep fire-exposed container cool.

Unsuitable Extinguishing Media : Do not use a heavy water stream. A heavy water stream may spread burning liquid.

5.2. Special Hazards Arising From the Substance or Mixture

Fire Hazard Highly flammable liquid and vapor. Most vapors are heavier than air. They will spread along ground and collect in low or confined areas (sewers, basements, tanks). Will float and can be reignited on water surface.

Explosion Hazard May form flammable or explosive vapor-air mixture.

Reactivity Highly flammable liquid and vapor. Reacts violently with strong oxidizers. Increased risk of fire or explosion.

5.3. Advice for Firefighters

Precautionary Measures Fire Exercise caution when fighting any chemical fire. Under fire conditions, hazardous fumes will be present.

Firefighting Instructions Use water spray or fog for cooling exposed containers. In case of major fire and large quantities: Evacuate area. Fight fire remotely due to the risk of explosion. Avoid release to the environment.

Protection During Firefighting Do not enter fire area without proper protective equipment, including respiratory protection.

MED16-6606

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Hazardous Combustion Products	Carbon oxides (CO, CO ₂). Formaldehyde. Silicon oxides.
Other Information	Do not allow run-off from fire fighting to enter drains or water courses.

SECTION 6: Accidental Release Measures

6.1. Personal Precautions, Protective Equipment And Emergency Procedures

General Measures Keep away from heat, sparks, open flames, hot surfaces. – No smoking. Use special care to avoid static electric charges. Do not get in eyes, on skin, or on clothing. Keep away from heat, hot surfaces, sparks, open flames, and other ignition sources. No smoking. Do not breathe vapor, mist or spray.

6.1.1. For Non-Emergency Personnel

Protective Equipment Use appropriate personal protective equipment (PPE).
Emergency Procedures Evacuate unnecessary personnel. Stop leak if safe to do so.

6.1.2. For emergency responders

Protective Equipment Equip cleanup crew with proper protection.
Emergency Procedures Upon arrival at the scene, a first responder is expected to recognize the presence of dangerous goods, protect oneself and the public, secure the area, and call for the assistance of trained personnel as soon as conditions permit. Eliminate ignition sources first, then ventilate the area.

6.2. Environmental Precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters. Avoid release to the environment. Collect spillage.

6.3. Methods and Materials for Containment and Cleaning Up

For Containment Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. As an immediate precautionary measure, isolate spill or leak area in all directions.

Methods for Cleaning Up Clean up spills immediately and dispose of waste safely. Use only non-sparking tools. Absorb and/or contain spill with inert material. Do not take up in combustible material such as: saw dust or cellulosic material. Transfer spilled material to a suitable container for disposal. Contact competent authorities after a spill.

6.4. Reference to Other Sections

See Section 8 for exposure controls and personal protection and Section 13 for disposal considerations.

SECTION 7: Handling And Storage

7.1. Precautions for Safe Handling

Additional Hazards When Processed Handle empty containers with care because residual vapors are flammable. When heated, material emits irritating fumes. Will decompose above 150 °C (> 300 °F) releasing formaldehyde vapors.

Precautions for Safe Handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Provide good ventilation in process area to prevent formation of vapor. Keep away from heat, sparks, open flames, hot surfaces. – No smoking. Take precautionary measures against static discharge. Use only non-sparking tools. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Do not get in eyes, on skin, or on clothing. Do NOT breathe (dust, vapor, mist, gas). Handle in accordance with good industrial hygiene and safety procedures. Wash hands and other exposed areas with mild soap and water before eating, drinking, or smoking and again when leaving work.

Hygiene Measures

7.2. Conditions for Safe Storage, Including Any Incompatibilities

Technical Measures

Ground and bond container and receiving equipment. Take action to prevent static discharges. Use explosion-proof electrical, ventilating, and lighting equipment. Comply with applicable regulations.

Storage Conditions

Keep in fireproof place. Store in a dry, cool place. Store in a well-ventilated place. Keep container tightly closed. Keep/Store away from direct sunlight, extremely high or low temperatures and incompatible materials. Store locked up/in a secure area.

Incompatible Materials

Strong acids, strong bases, strong oxidizers.

7.3. Specific End Use(s)

For professional use only.

SECTION 8: Exposure Controls/Personal Protection

8.1. Control Parameters

For substances listed in section 3 that are not listed here, there are no established exposure limits from the manufacturer, supplier, importer, or the appropriate advisory agency including: ACGIH (TLV), or OSHA (PEL).

Silanamine, 1,1,1-trimethyl-N-(trimethylsilyl)-, hydrolysis products with silica (68909-20-6)		
USA OSHA	OSHA PEL TWA	6 mg/m ³
USA OSHA	OSHA PEL TWA	20 mppcf (80mg/m ³ /%SiO ₂)
Tin organic compounds		
USA ACGIH	ACGIH OEL TWA	0.1 mg/m ³
USA ACGIH	ACGIH OEL STEL	0.2 mg/m ³
USA ACGIH	ACGIH chemical category	Not Classifiable as a Human Carcinogen, Skin - potential significant contribution to overall exposure by the cutaneous route
USA NIOSH	NIOSH REL TWA	0.1 mg/m ³ (except Cyhexatin)
USA OSHA	OSHA PEL TWA	0.1 mg/m ³

8.2. Exposure Controls

Appropriate Engineering Controls

Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Ensure adequate ventilation, especially in confined areas. Gas detectors should be used when flammable gases/vapors may be released. Proper grounding procedures to avoid static electricity should be followed. Ensure all national/local regulations are observed. Gas detectors should be used when flammable gases or vapors may be released. Use explosion-proof equipment.

Personal Protective Equipment

Gloves. Protective clothing. Protective goggles. Insufficient ventilation: wear respiratory protection.



Materials For Protective Clothing
Hand Protection
Eye And Face Protection
Skin And Body Protection

Wear fire/flare resistant/retardant clothing. Chemically resistant materials and fabrics.

Wear protective gloves.

Chemical safety goggles.

Wear suitable protective clothing. Wash contaminated clothing before reuse.

Respiratory Protection

If exposure limits are exceeded or irritation is experienced, approved respiratory protection should be worn. In case of inadequate ventilation, oxygen deficient atmosphere, or where exposure levels are not known wear approved respiratory protection.

Environmental Exposure Controls

Do not allow the product to be released into the environment.

Other Information

When using, do not eat, drink or smoke.

SECTION 9: Physical and Chemical Properties**9.1. Information on Basic Physical and Chemical Properties**

Physical State	Liquid
Appearance	Translucent
Color	Colorless
Odor	Solvent
Odor Threshold	No data available
pH	No data available
Evaporation Rate	No data available
Melting Point	No data available
Freezing Point	No data available
Boiling Point	88 – 100 °C (190.4 – 212 °F)
Flash Point	-8 °C (17.6 °F)
Auto-ignition Temperature	No data available
Decomposition Temperature	No data available
Flammability (Solid/Gas)	Not applicable
Vapor Pressure	No data available
Relative Vapor Density at 20°C	No data available

MED16-6606

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Relative Density	No data available
Specific Gravity	< 1
Density	< 1
Solubility	No data available
Partition Coefficient n-Octanol/Water	No data available
Viscosity	No data available

9.2. Other Information

VOC Content	60 – 70 %
-------------	-----------

SECTION 10: Stability and Reactivity

10.1. Reactivity

Highly flammable liquid and vapor. Reacts violently with strong oxidizers. Increased risk of fire or explosion.

10.2. Chemical Stability

Highly flammable liquid and vapor. May form flammable or explosive vapor-air mixture.

10.3. Possibility of Hazardous Reactions

Hazardous polymerization will not occur.

10.4. Conditions to Avoid

Direct sunlight, extremely high or low temperatures, heat, hot surfaces, sparks, open flames, incompatible materials, and other ignition sources.

10.5. Incompatible Materials

Strong acids, strong bases, strong oxidizers.

10.6. Hazardous Decomposition Products

Thermal decomposition may produce: Carbon oxides (CO, CO₂). Silicon oxides. May release flammable gases. Will decompose above 150 °C (>300° F) releasing formaldehyde vapors. Formaldehyde is a potential carcinogen and can act as a potential skin and respiratory sensitizer. Formaldehyde can also cause respiratory and eye irritation.

SECTION 11: Toxicological Information

11.1. Information on Toxicological Effects

Acute Toxicity (Oral)	Not classified
Acute Toxicity (Dermal)	Not classified
Acute Toxicity (Inhalation)	Not classified

Silanetriol, ethyl-, triacetate (17689-77-9)	
LD50 Oral Rat	1460 mg/kg

Glycidoxypropyltrimethoxysilane (2530-83-8)	
LD50 Oral Rat	8025 mg/kg
LD50 Dermal Rabbit	4250 mg/kg
LC50 Inhalation Rat	> 5.3 mg/l/4h
LC50 Inhalation Rat	> 5.3 mg/l/4h

Octamethylcyclotetrasiloxane (556-67-2)	
LD50 Oral Rat	> 4800 mg/kg (No mortality)
LD50 Dermal Rat	> 2375 mg/kg
LD50 Dermal Rabbit	> 2.5 ml/kg (No mortality)
LC50 Inhalation Rat	36 mg/l/4h

MED16-6606

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Skin Corrosion/Irritation	Causes skin irritation.
Serious Eye Damage/Irritation	Causes serious eye damage.
Respiratory or Skin Sensitization	Not classified
Germ Cell Mutagenicity	Not classified
Carcinogenicity	Not classified
Reproductive Toxicity	Suspected of damaging fertility or the unborn child.
Specific Target Organ Toxicity (Single Exposure)	May cause drowsiness or dizziness.
Specific Target Organ Toxicity (Repeated Exposure)	Not classified
Aspiration Hazard	May be fatal if swallowed and enters airways.
Symptoms/Injuries After Inhalation	High concentrations may cause central nervous system depression such as dizziness, vomiting, numbness, drowsiness, headache, and similar narcotic symptoms.
Symptoms/Injuries After Skin Contact	Redness, pain, swelling, itching, burning, dryness, and dermatitis.
Symptoms/Injuries After Eye Contact	Causes permanent damage to the cornea, iris, or conjunctiva.
Symptoms/Injuries After Ingestion	Aspiration into the lungs can occur during ingestion or vomiting and may cause lung injury.
Chronic Symptoms	Suspected of damaging fertility or the unborn child.

SECTION 12: Ecological Information

12.1. Toxicity

Ecology - General Very toxic to aquatic life with long lasting effects.

Glycidoxypropyltrimethoxysilane (2530-83-8)	
LC50 Fish	55 mg/l (Exposure time: 96 h - Species: <i>Cyprinus carpio</i>)
EC50 Crustacea	710 mg/l (Exposure time: 48 h - Species: <i>Daphnia magna</i>)
ErC50 Algae	350 mg/l Exposure time: 96 h - Species: <i>Pseudokirchnerella subcapitata</i>)
NOEC Chronic Crustacea	100 mg/l
Dibutyltin diacetate (1067-33-0)	
EC50 Crustacea	0.75 (0.65 – 0.86) mg/l Exposure time: 48-Hour (Species: <i>Daphnia magna</i>)
ErC50 Algae	0.1 mg/l
EC50 Chronic	0.035 mg/l Exposure time: 72 hour (Species: <i>Skeletonema costatum</i>)
NOEC (Acute)	0.65 mg/l
NOEC Chronic Crustacea	0.32 mg/l (48-Hour EC50 <i>Daphnia magna</i>)
Octamethylcyclotetrasiloxane (556-67-2)	
LC50 Fish	> 22 µg/l
NOEC Chronic Fish	0.0044 mg/l

12.2. Persistence and Degradability

MED16-6606	
Persistence and Degradability	May cause long-term adverse effects in the environment.

12.3. Bioaccumulative Potential

MED16-6606	
------------	--

MED16-6606

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Bioaccumulative Potential	Not established.
Dibutyltin diacetate (1067-33-0)	
Partition coefficient n-octanol/water (Log Pow)	3.39 (at 20 °C (at pH 5))
Octamethylcyclotetrasiloxane (556-67-2)	
BCF Fish	12400 (dimensionless)
Partition coefficient n-octanol/water (Log Pow)	6.488 (at 25.1 °C)

12.4. Mobility In Soil

No additional information available

12.5. Other Adverse Effects

Other Information Avoid release to the environment.

SECTION 13: Disposal Considerations

13.1. Waste Treatment Methods

Waste Disposal	Dispose of contents/container in accordance with local, regional, national, and international regulations.
Recommendations	
Additional Information	Handle empty containers with care because residual vapors are flammable.
Ecology - Waste Materials	This material is hazardous to the aquatic environment. Keep out of sewers and waterways. Avoid release to the environment.

SECTION 14: Transport Information

The shipping description(s) stated herein were prepared in accordance with certain assumptions at the time the SDS was authored, and can vary based on a number of variables that may or may not have been known at the time the SDS was issued.

14.1. In Accordance with DOT

Proper Shipping Name	HEPTANES Solution
Hazard Class	3
Identification Number	UN1206
Label Codes	3
Packing Group	II
Marine Pollutant	Marine pollutant
ERG Number	128



14.2. In Accordance with IMDG

Proper Shipping Name	HEPTANES Solution
Hazard Class	3
Identification Number	UN1206
Packing Group	II
Label Codes	3
EmS-No. (Fire)	F-E
EmS-No. (Spillage)	S-D
Marine Pollutant	Marine pollutant
MFAG Number	128



MED16-6606

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

14.3. In Accordance with IATA

Proper Shipping Name	HEPTANES Solution
Packing Group	II
Identification Number	UN1206
Hazard Class	3
Label Codes	3
ERG Code (IATA)	3H



SECTION 15: Regulatory Information

15.1. US Federal Regulations

All components in this mixture are listed on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory, have been exempted, are not listed, not disclosed due to CBI requirements or disclosure rules according to the relevant regulation.

MED16-6606	
SARA Section	Health hazard - Aspiration hazard
311/312 Hazard	Health hazard - Reproductive toxicity
Classes	Health hazard - Serious eye damage or eye irritation
	Health hazard - Skin corrosion or Irritation
	Health hazard - Specific target organ toxicity (single or repeated exposure)
	Physical hazard - Flammable (gases, aerosols, liquids, or solids)

15.2. US State Regulations

Heptane, branched, cyclic and linear (426260-76-6)
U.S. - Texas - Effects Screening Levels - Long Term
U.S. - Texas - Effects Screening Levels - Short Term
Silanamine, 1,1,1-trimethyl-N-(trimethylsilyl)-, hydrolysis products with silica (68909-20-6)
U.S. - Texas - Effects Screening Levels - Long Term
U.S. - Texas - Effects Screening Levels - Short Term
Silanetriol, ethyl-, triacetate (17689-77-9)
U.S. - Texas - Effects Screening Levels - Long Term
U.S. - Texas - Effects Screening Levels - Short Term
Glycidoxypropyltrimethoxysilane (2530-83-8)
U.S. - Texas - Effects Screening Levels - Long Term
U.S. - Texas - Effects Screening Levels - Short Term
Dibutyltin diacetate (1067-33-0)
RTK - U.S. - Massachusetts - Right To Know List
U.S. - Texas - Effects Screening Levels - Long Term
U.S. - Texas - Effects Screening Levels - Short Term
Tin organic compounds
U.S. - Minnesota - Hazardous Substance List
U.S. - Tennessee - Occupational Exposure Limits - TWAs
U.S. - Tennessee - Occupational Exposure Limits - Skin Designations
U.S. - Vermont - Permissible Exposure Limits - TWAs
U.S. - Connecticut - Hazardous Air Pollutants - HLVs (8 hr)
U.S. - Vermont - Permissible Exposure Limits - Skin Designations
U.S. - Washington - Permissible Exposure Limits - TWAs
U.S. - Connecticut - Hazardous Air Pollutants - HLVs (30 min)
U.S. - Washington - Permissible Exposure Limits - STELs

MED16-6606

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

U.S. - Washington - Permissible Exposure Limits - Skin Designations
U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Emission Levels (ELs)
U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Acceptable Ambient Concentrations
U.S. - New York - Occupational Exposure Limits - TWAs
U.S. - New York - Occupational Exposure Limits - Skin Designations
U.S. - Michigan - Occupational Exposure Limits - TWAs
U.S. - Michigan - Occupational Exposure Limits - Skin Designations
U.S. - Minnesota - Permissible Exposure Limits - Skin Designations
U.S. - Minnesota - Permissible Exposure Limits - TWAs
U.S. - Oregon - Permissible Exposure Limits - TWAs
U.S. - Texas - Effects Screening Levels - Long Term
U.S. - Texas - Effects Screening Levels - Short Term
U.S. - Wisconsin - Hazardous Air Contaminants - All Sources - Emissions From Stack Heights 75 Feet or Greater
U.S. - Wisconsin - Hazardous Air Contaminants - All Sources - Emissions From Stack Heights 40 Feet to Less Than 75 Feet
U.S. - Wisconsin - Hazardous Air Contaminants - All Sources - Emissions From Stack Heights 25 Feet to Less Than 40 Feet
U.S. - Wisconsin - Hazardous Air Contaminants - All Sources - Emissions From Stack Heights Less Than 25 Feet
U.S. - North Dakota - Air Pollutants - Guideline Concentrations - 1-Hour
U.S. - North Dakota - Air Pollutants - Guideline Concentrations - 8-Hour
U.S. - New Hampshire - Regulated Toxic Air Pollutants - Ambient Air Levels (AALs) - 24-Hour
U.S. - New Hampshire - Regulated Toxic Air Pollutants - Ambient Air Levels (AALs) - Annual

Octamethylcyclotetrasiloxane (556-67-2)

U.S. - Texas - Effects Screening Levels - Long Term
U.S. - Texas - Effects Screening Levels - Short Term
U.S. - Maine - Chemicals of Concern
U.S. - Oregon - Priority Persistent Pollutant - Tier I - Persistent Pollutants
U.S. - Minnesota - Chemicals of High Concern
U.S. - Minnesota - Chemicals of High Concern - Persistent Bioaccumulative Toxins
U.S. - California - Safer Consumer Products - Initial List of Candidate Chemicals and Chemical Groups

SECTION 16: Other Information, Including Date of Preparation or Last Revision

Date of Preparation or Latest Revision 10/12/2022

Revision

Other Information

This document has been prepared in accordance with the SDS requirements of the OSHA Hazard Communication Standard 29 CFR 1910.1200.

GHS Full Text Phrases:

Flam. Liq. 2	Flammable liquids Category 2
Flam. Liq. 3	Flammable liquids Category 3
Acute Tox. 4 (Oral)	Acute toxicity (oral) Category 4
Asp. Tox. 1	Aspiration hazard Category 1
Skin Corr. 1B	Skin corrosion/irritation Category 1B
Skin Irrit. 2	Skin corrosion/irritation Category 2
Skin Sens. 1B	Skin Sensitization category 1B

MED16-6606

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Eye Dam. 1	Serious eye damage/eye irritation Category 1
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Narcosis
Muta. 2	Mutagenicity category 2
Repr. 1B	Reproductive toxicity category 1B
Repr. 2	Reproductive toxicity category 2
STOT SE 1	Specific target organ toxicity — Single exposure category 1
STOT RE 1	Specific target organ toxicity — Repeated exposure category 1
Aquatic Acute 1	Hazardous to the aquatic environment - Acute Hazard Category 1
Aquatic Acute 3	Hazardous to the aquatic environment - Acute Hazard Category 3
Aquatic Chronic 1	Hazardous to the aquatic environment - Chronic Hazard Category 1
Aquatic Chronic 3	Hazardous to the aquatic environment - Chronic Hazard Category 3
H225	Highly flammable liquid and vapor
H226	Flammable liquid and vapor
H302	Harmful if swallowed
H304	May be fatal if swallowed and enters airways
H314	Causes severe skin burns and eye damage
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H318	Causes serious eye damage
H336	May cause drowsiness or dizziness
H341	Suspected of causing genetic defects
H360	May damage fertility or the unborn child
H361	Suspected of damaging fertility or the unborn child
H370	Causes damage to organs
H372	Causes damage to organs through prolonged or repeated exposure
H400	Very toxic to aquatic life
H402	Harmful to aquatic life
H410	Very toxic to aquatic life with long lasting effects
H412	Harmful to aquatic life with long lasting effects

NFPA Health Hazard


2 - Materials that, under emergency conditions, can cause temporary incapacitation or residual injury.

NFPA Fire Hazard

3 - Liquids and solids (including finely divided suspended solids) that can be ignited under almost all ambient temperature conditions.

NFPA Reactivity Hazard

1 - Materials that in themselves are normally stable but can become unstable at elevated temperatures and pressures.



MED16-6606

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

HMIS III Rating

Health

2 Moderate Hazard

* Chronic - Chronic (long-term) health effects may result from repeated overexposure

Flammability

3 Serious Hazard

Physical

1 Slight Hazard

The information provided in this Safety Data Sheet (SDS) was prepared based on data believed to be accurate as of the date of this SDS. TO THE GREATEST EXTENT PERMITTED BY LAW, NUSIL TECHNOLOGY LLC AND ITS AFFILIATED COMPANIES ("NUSIL") EXPRESSLY DISCLAIMS ANY AND ALL REPRESENTATIONS AND WARRANTIES REGARDING THE INFORMATION CONTAINED HEREIN INCLUDING, WITHOUT LIMITATION, AS TO ACCURACY, COMPLETENESS, FITNESS FOR PURPOSE OR USE, MERCHANTABILITY, NON-INFRINGEMENT, PERFORMANCE, SAFETY, SUITABILITY AND STABILITY. This SDS is intended as a guide to the appropriate use, handling, storage and disposal of the product to which it relates by properly trained personnel, and is not intended to be comprehensive. Users of NuSil's products are advised to perform their own tests and to exercise their own judgment to determine the safety, suitability and appropriate use, handling, storage and disposal of each product and product combination for their own purposes and uses. TO THE GREATEST EXTENT PERMITTED BY LAW, NUSIL DISCLAIMS LIABILITY FOR, AND BY USING NUSIL'S PRODUCTS PURCHASER AGREES THAT UNDER NO CIRCUMSTANCES SHALL NUSIL BE LIABLE FOR, SPECIAL, INDIRECT, INCIDENTAL, PUNITIVE OR CONSEQUENTIAL DAMAGES OF ANY TYPE OR KIND, INCLUDING WITHOUT LIMITATION, FOR LOSS OF PROFITS, REPUTATIONAL DAMAGE, PRODUCT RECALL OR BUSINESS INTERRUPTION.

Nusil US GHS SDS