

# CV3-1144-1

## Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations  
Date of Revision: 01/11/2021 Date of Issue: 2/14/2014



Version: 3.0

## SECTION 1: Identification

### 1.1. Product Identifier

Product Form Mixture  
Product Name CV3-1144-1  
Synonyms Silicone Dispersion

### 1.2. Relevant Identified Uses of the Substance or Mixture and Uses Advised Against

Use of the Substance/Mixture For professional use only.

### 1.3. Details of the Supplier of the Safety Data Sheet

NuSil Technology LLC  
1050 Cindy Lane  
Carpinteria, California 93013  
USA  
(805) 684-8780  
[ehs@nusil.com](mailto:ehs@nusil.com)  
[www.nusil.com](http://www.nusil.com)

### 1.4. Emergency Telephone Number

Emergency Number 800-424-9300 CHEMTREC (in US); +1 703-527-3887 CHEMTREC (International and Maritime)

## SECTION 2: Hazards Identification

### 2.1. Classification of the Substance or Mixture

#### GHS-US Classification

Flam. Liq. 2 H225  
Skin Irrit. 2 H315  
Eye Dam. 1 H318  
Skin Sens. 1 H317  
Repr. 1B H360  
STOT RE 2 H373  
Asp. Tox. 1 H304  
Aquatic Acute 3 H402

Full text of hazard classes and H-statements: see section 16

### 2.2. Label Elements

#### GHS-US Labeling

Hazard Pictograms (GHS-US)



GHS02



GHS05



GHS07



GHS08

Signal Word (GHS-US)

Danger

# CV3-1144-1

## Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

---

### Hazard Statements (GHS-US)

H225 - Highly flammable liquid and vapor  
H304 - May be fatal if swallowed and enters airways  
H315 - Causes skin irritation  
H317 - May cause an allergic skin reaction  
H318 - Causes serious eye damage  
H360 - May damage fertility or the unborn child  
H373 - May cause damage to organs through prolonged or repeated exposure  
H402 - Harmful to aquatic life

### Precautionary Statements (GHS-US)

P201 - Obtain special instructions before use.  
P202 - Do not handle until all safety precautions have been read and understood.  
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P240 - Ground/Bond container and receiving equipment.  
P241 - Use explosion-proof electrical, ventilating, and lighting equipment.  
P242 - Use only non-sparking tools.  
P243 - Take precautionary measures against static discharge.  
P260 - Do not breathe vapors, mist, or spray.  
P264 - Wash hands, forearms, and other exposed areas thoroughly after handling.  
P272 - Contaminated work clothing must not be allowed out of the workplace.  
P273 - Avoid release to the environment.  
P280 - Wear protective gloves, protective clothing, and eye protection.  
P301+P310 - If swallowed: Immediately call a poison center or doctor.  
P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.  
P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P308+310+313 - If exposed or concerned: Get medical advice/attention. Immediately call a poison center or doctor.  
P314 - Get medical advice/attention if you feel unwell.  
P321 - Specific treatment (see section 4 on this SDS).  
P331 - Do NOT induce vomiting.  
P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.  
P362+P364 - Take off contaminated clothing and wash it before reuse.  
P370+P378 - In case of fire: Use appropriate media (see section 5) to extinguish.  
P403+P233+P235 - Store in a well-ventilated place. Keep container tightly closed. Keep cool.  
P405 - Store locked up.  
P501 - Dispose of contents/container in accordance with local, regional, national, and international regulations.

# CV3-1144-1

## Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 2.3. Other Hazards

Other Hazards Not Contributing to the Classification Exposure may aggravate pre-existing eye, skin, or respiratory conditions.

### 2.4. Unknown Acute Toxicity (GHS-US)

No data available

## SECTION 3: Composition/Information On Ingredients

### 3.1. Substances

Not applicable

### 3.2. Mixtures

Name	Product Identifier	%	GHS-US Classification
Solvent naphtha, petroleum, light aliphatic	(CAS-No.) 64742-89-8	20 - 50	Flam. Liq. 2, H225 Skin Irrit. 2, H315 Asp. Tox. 1, H304 Aquatic Acute 3, H402
2-Butanone, O,O',O''-(methylsilyldiyl)trioxime	(CAS-No.) 22984-54-9	< 10	Eye Irrit. 2A, H319 Skin Sens. 1B, H317 STOT RE 2, H373
N-[3-(Trimethoxysilyl)propyl]-1,2-ethanediamine	(CAS-No.) 1760-24-3	< 5	Acute Tox. 4 (Inhalation:dust,mist), H332 Eye Dam. 1, H318 Skin Sens. 1, H317 Aquatic Acute 2, H401
Titanium dioxide	(CAS No) 13463-67-7	< 5	Not classified
Synthetic Amorphous, Pyrogenic Silica	(CAS No) 112945-52-5	< 5	Not classified
Dibutyltin dilaurate	(CAS-No.) 77-58-7	< 1	Skin Corr. 1C, H314 Eye Dam. 1, H318 Skin Sens. 1, H317 Muta. 2, H341 Repr. 1B, H360 STOT SE 1, H370 STOT RE 1, H372 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
C.I. Pigment Red 108	(CAS-No.) 58339-34-7	< 0.1	Not classified
Chromium oxide (Cr2O3)	(CAS-No.) 1308-38-9	< 0.1	Not classified
C.I. Pigment Yellow 35	(CAS-No.) 8048-07-5	< 0.1	Comb. Dust

Full text of H-phrases: see section 16

## SECTION 4: First Aid Measures

### 4.1. Description of First-aid Measures

First-aid Measures General Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

# CV3-1144-1

## Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

First-aid Measures After Inhalation	When symptoms occur: go into open air and ventilate suspected area. Obtain medical attention if breathing difficulty persists.
First-aid Measures After Skin Contact	Remove contaminated clothing. Drench affected area with water for at least 15 minutes. Obtain medical attention if irritation develops or persists.
First-aid Measures After Eye Contact	Rinse cautiously with water for at least 30 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get immediate medical advice/attention.
First-aid Measures After Ingestion	Do NOT induce vomiting. Rinse mouth. Immediately call a POISON CENTER or doctor/physician.

### 4.2. Most Important Symptoms and Effects Both Acute and Delayed

Symptoms/Injuries	Causes skin irritation. Causes serious eye damage. Skin sensitization. May be fatal if swallowed and enters airways. There are potential chronic health effects to consider. Prolonged exposure may cause irritation.
Symptoms/Injuries After Inhalation	
Symptoms/Injuries After Skin Contact	Redness, pain, swelling, itching, burning, dryness, and dermatitis. May cause an allergic skin reaction.
Symptoms/Injuries After Eye Contact	Causes permanent damage to the cornea, iris, or conjunctiva.
Symptoms/Injuries After Ingestion	Aspiration into the lungs can occur during ingestion or vomiting and may cause lung injury.
Chronic Symptoms	May damage fertility or the unborn child. May cause damage to organs (cardiovascular / hematological) through prolonged or repeated exposure.

### 4.3. Indication of Any Immediate Medical Attention and Special Treatment Needed

If exposed or concerned, get medical advice and attention. If medical advice is needed, have product container or label at hand.

## SECTION 5: Fire-Fighting Measures

### 5.1. Extinguishing Media

Suitable Extinguishing Media	: Dry chemical powder, alcohol-resistant foam, carbon dioxide (CO <sub>2</sub> ). Water may be ineffective but water should be used to keep fire-exposed container cool.
Unsuitable Extinguishing Media	: Do not use a heavy water stream. A heavy water stream may spread burning liquid.

### 5.2. Special Hazards Arising From the Substance or Mixture

Fire Hazard	Highly flammable liquid and vapor.
Explosion Hazard	May form flammable or explosive vapor-air mixture.
Reactivity	Reacts violently with strong oxidizers. Increased risk of fire or explosion.

### 5.3. Advice for Firefighters

Precautionary Measures Fire Fighting Instructions	Exercise caution when fighting any chemical fire. Use water spray or fog for cooling exposed containers. In case of major fire and large quantities: Evacuate area. Fight fire remotely due to the risk of explosion.
Protection During Firefighting	Do not enter fire area without proper protective equipment, including respiratory protection.

# CV3-1144-1

## Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

---

Hazardous Combustion  
Products  
Other Information

Carbon oxides (CO, CO<sub>2</sub>). Silicon oxides. Hydrocarbons.  
Nitrogen oxides. Metal oxides. Formaldehyde.  
Do not allow run-off from fire fighting to enter drains or water  
courses.

## SECTION 6: Accidental Release Measures

### 6.1. Personal Precautions, Protective Equipment And Emergency Procedures

General Measures

Do not get in eyes, on skin, or on clothing. Keep away from heat, hot surfaces, sparks, open flames, and other ignition sources. No smoking. Use special care to avoid static electric charges. Do not breathe vapor, mist or spray.

#### 6.1.1. For Non-Emergency Personnel

Protective Equipment  
Emergency Procedures

Use appropriate personal protective equipment (PPE).  
Evacuate unnecessary personnel. Stop leak if safe to do so.

#### 6.1.2. For emergency responders

Protective Equipment  
Emergency Procedures

Equip cleanup crew with proper protection.  
Upon arrival at the scene, a first responder is expected to recognize the presence of dangerous goods, protect oneself and the public, secure the area, and call for the assistance of trained personnel as soon as conditions permit. Ventilate area. Eliminate ignition sources.

### 6.2. Environmental Precautions

Prevent entry to sewers and public waters. Avoid release to the environment.

### 6.3. Methods and Materials for Containment and Cleaning Up

For Containment

Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. As an immediate precautionary measure, isolate spill or leak area in all directions.

Methods for Cleaning Up

Clean up spills immediately and dispose of waste safely. Transfer spilled material to a suitable container for disposal. Contact competent authorities after a spill. Absorb and/or contain spill with inert material. Do not take up in combustible material such as: saw dust or cellulosic material. Use only non-sparking tools.

### 6.4. Reference to Other Sections

See Section 8 for exposure controls and personal protection and Section 13 for disposal considerations.

## SECTION 7: Handling And Storage

### 7.1. Precautions for Safe Handling

Additional Hazards When  
Processed

Handle empty containers with care because residual vapors are flammable.

# CV3-1144-1

## Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### Precautions for Safe Handling

Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Take precautionary measures against static discharge. Use only non-sparking tools. Do not get in eyes, on skin, or on clothing. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not breathe vapors, mist, spray.

### Hygiene Measures

Handle in accordance with good industrial hygiene and safety procedures.

## 7.2. Conditions for Safe Storage, Including Any Incompatibilities

### Technical Measures

Comply with applicable regulations. Take action to prevent static discharges. Ground and bond container and receiving equipment. Use explosion-proof electrical, ventilating, and lighting equipment.

### Storage Conditions

Store in a dry, cool place. Keep/Store away from direct sunlight, extremely high or low temperatures and incompatible materials. Store in a well-ventilated place. Keep container tightly closed. Keep in fireproof place.

### Incompatible Materials

Strong acids, strong bases, strong oxidizers.

## 7.3. Specific End Use(S)

For professional use only.

## SECTION 8: Exposure Controls/Personal Protection

### 8.1. Control Parameters

Titanium dioxide (13463-67-7)		
USA ACGIH	ACGIH TWA (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup>
USA ACGIH	ACGIH chemical category	Not Classifiable as a Human Carcinogen
USA OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	15 mg/m <sup>3</sup> (total dust)
Synthetic Amorphous, Pyrogenic Silica (112945-52-5)		
USA OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	6 mg/m <sup>3</sup>
USA OSHA	OSHA PEL (TWA) (ppm)	20 mppcf (80 mg/m <sup>3</sup> /%SiO <sub>2</sub> )
Chromium oxide (Cr <sub>2</sub> O <sub>3</sub> ) (1308-38-9)		
USA ACGIH	ACGIH TWA (mg/m <sup>3</sup> )	0.05 mg/m <sup>3</sup> 0.5 (Cr II & Cr III Compounds) 0.05 (Cr VI Water Soluble)
USA OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	1 mg/m <sup>3</sup> (metal) 0.5 (Cr II & Cr III Compounds) 0.005 (Cr VI Compounds)
Cadmium compounds		
USA ACGIH	ACGIH TWA (mg/m <sup>3</sup> )	0.01 mg/m <sup>3</sup> 0.002 mg/m <sup>3</sup> (respirable particulate matter)
USA ACGIH	ACGIH chemical category	Suspected Human Carcinogen

# CV3-1144-1

## Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 8.2. Exposure Controls

Appropriate Engineering Controls

Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Ensure adequate ventilation, especially in confined areas. Ensure all national/local regulations are observed. Gas detectors should be used when flammable gases or vapors may be released. Proper grounding procedures to avoid static electricity should be followed. Use explosion-proof equipment. Gloves. Protective clothing. Protective goggles. Insufficient ventilation: wear respiratory protection.

Personal Protective Equipment



Materials For Protective Clothing  
Hand Protection  
Eye And Face Protection  
Skin And Body Protection  
Respiratory Protection

Chemically resistant materials and fabrics. Wear fire/flamm resistant/retardant clothing.

Wear protective gloves.

Chemical safety goggles.

Wear suitable protective clothing.

If exposure limits are exceeded or irritation is experienced, approved respiratory protection should be worn. In case of inadequate ventilation, oxygen deficient atmosphere, or where exposure levels are not known wear approved respiratory protection.

Other Information

When using, do not eat, drink or smoke.

## SECTION 9: Physical and Chemical Properties

### 9.1. Information on Basic Physical and Chemical Properties

Physical State	Liquid
Appearance	Off-white
Odor	Solvent
Odor Threshold	No data available
pH	No data available
Evaporation Rate	No data available
Melting Point	No data available
Freezing Point	No data available
Boiling Point	No data available
Flash Point	8.9 °C (48.02 °F)
Auto-ignition Temperature	No data available
Decomposition Temperature	No data available
Flammability (solid, gas)	Not applicable
Vapor Pressure	No data available
Relative Vapor Density at 20°C	No data available
Relative Density	No data available
Specific Gravity	> 1
Solubility	No data available
Partition Coefficient n-Octanol/Water	No data available

# CV3-1144-1

## Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Viscosity No data available

### 9.2. Other Information

VOC Content 25 - 35 %

## SECTION 10: Stability and Reactivity

### 10.1. Reactivity

Reacts violently with strong oxidizers. Increased risk of fire or explosion.

### 10.2. Chemical Stability

Highly flammable liquid and vapor. May form flammable or explosive vapor-air mixture.

### 10.3. Possibility of Hazardous Reactions

Hazardous polymerization will not occur.

### 10.4. Conditions to Avoid

Direct sunlight, extremely high or low temperatures, heat, hot surfaces, sparks, open flames, incompatible materials, and other ignition sources.

### 10.5. Incompatible Materials

Strong acids, strong bases, strong oxidizers.

### 10.6. Hazardous Decomposition Products

None expected under normal conditions of use.

## SECTION 11: Toxicological Information

### 11.1. Information on Toxicological Effects

Acute Toxicity (Oral) : Not classified

Acute Toxicity (Dermal) : Not classified

Acute Toxicity (Inhalation) : Not classified

Solvent naphtha, petroleum, light aliphatic (64742-89-8)	
LD50 Oral Rat	> 5000 mg/kg
LD50 Dermal Rabbit	3000 mg/kg
2-Butanone, O,O',O''-(methylsilylidyne)trioxime (22984-54-9)	
LD50 Oral Rat	2463 mg/kg
LD50 Dermal Rat	> 2000 mg/kg
N-[3-(Trimethoxysilyl)propyl]-1,2-ethanediamine (1760-24-3)	
LD50 Oral Rat	2295 mg/kg
LD50 Dermal Rabbit	> 2000 mg/kg
LC50 Inhalation Rat	> 1.49 mg/l/4h
Dibutyltin dilaurate (77-58-7)	
LD50 Dermal Rat	> 2 g/kg

Skin Corrosion/Irritation

Causes skin irritation.

Serious Eye Damage/Irritation

Causes serious eye damage.

Respiratory or Skin Sensitization

May cause an allergic skin reaction.

Germ Cell Mutagenicity

Not classified

Carcinogenicity

Not classified

Reproductive Toxicity

: May damage fertility or the unborn child.

Specific Target Organ Toxicity (Single Exposure)

: Not classified

Specific Target Organ Toxicity (Repeated Exposure)

: May cause damage to organs through prolonged or repeated exposure.



# CV3-1144-1

## Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Aspiration Hazard	May be fatal if swallowed and enters airways.
Symptoms/Injuries After Inhalation	Prolonged exposure may cause irritation.
Symptoms/Injuries After Skin Contact	Redness, pain, swelling, itching, burning, dryness, and dermatitis. May cause an allergic skin reaction.
Symptoms/Injuries After Eye Contact	Causes permanent damage to the cornea, iris, or conjunctiva.
Symptoms/Injuries After Ingestion	Aspiration into the lungs can occur during ingestion or vomiting and may cause lung injury.
Chronic Symptoms	May damage fertility or the unborn child. May cause damage to organs (cardiovascular / hematological) through prolonged or repeated exposure.

## SECTION 12: Ecological Information

### 12.1. Toxicity

Ecology - General Harmful to aquatic life.

2-Butanone, O,O',O''-(methylsilylydyne)trioxime (22984-54-9)	
EC50 Daphnia 1	120 mg/l (Exposure time: 48h - Species: Daphnia magna)
N-[3-(Trimethoxysilyl)propyl]-1,2-ethanediamine (1760-24-3)	
LC50 Fish 1	597 mg/l (Species: Danio rerio)
EC50 Daphnia 1	81 mg/l
ErC50 (Algae)	8.8 mg/l (Exposure time: 72 h - Species: Pseudokirchneriella subcapitata)
NOEC Chronic Fish	344 mg/l
NOEC Chronic Crustacea	35 mg/l
NOEC Chronic Algae	3.1 mg/l (Pseudokirchnerella subcapitata Exposure time: 96h)
Dibutyltin dilaurate (77-58-7)	
EC50 Daphnia 1	0.463 mg/l (Daphnia magna)

### 12.2. Persistence and Degradability

CV3-1144-1	
Persistence and Degradability	Not established.

### 12.3. Bioaccumulative Potential

CV3-1144-1	
Bioaccumulative Potential	Not established.
Dibutyltin dilaurate (77-58-7)	
Log Pow	4.44

### 12.4. Mobility In Soil

No additional information available

### 12.5. Other Adverse Effects

Other Information Avoid release to the environment.

## SECTION 13: Disposal Considerations

### 13.1. Waste Treatment Methods

Waste Disposal Recommendations Dispose of contents/container in accordance with local, regional, national, and international regulations.

# CV3-1144-1

## Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Additional Information	Handle empty containers with care because residual vapors are flammable.
Ecology - Waste Materials	Avoid release to the environment. This material is hazardous to the aquatic environment. Keep out of sewers and waterways.

### SECTION 14: Transport Information

The shipping description(s) stated herein were prepared in accordance with certain assumptions at the time the SDS was authored, and can vary based on a number of variables that may or may not have been known at the time the SDS was issued.

#### 14.1. In Accordance with DOT

Proper Shipping Name	PETROLEUM PRODUCTS, N.O.S (CONTAINS NAPHTHA)
Hazard Class	3
Identification Number	UN1268
Label Codes	3
Packing Group	II
ERG Number	128



#### 14.2. In Accordance with IMDG

Proper Shipping Name	PETROLEUM PRODUCTS, N.O.S. (CONTAINS NAPHTHA)
Hazard Class	3
Identification Number	UN1268
Packing Group	II
Label Codes	3
EmS-No. (Fire)	F-E
EmS-No. (Spillage)	S-E



#### 14.3. In Accordance with IATA

Proper Shipping Name	PETROLEUM DISTILLATES, N.O.S. (CONTAINS NAPHTHA)
Packing Group	II
Identification Number	UN1268
Hazard Class	3
Label Codes	3
ERG Code (IATA)	3H



### SECTION 15: Regulatory Information

#### 15.1. US Federal Regulations

All components in this mixture are listed on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory, have been exempted, are not listed, not disclosed due to CBI requirements or disclosure rules according to the relevant regulation.

CV3-1144-1	
SARA Section 311/312 Hazard Classes	Physical hazard - Flammable (gases, aerosols, liquids, or solids) Health hazard - Aspiration hazard Health hazard - Respiratory or skin sensitization Health hazard - Reproductive toxicity Health hazard - Serious eye damage or eye irritation Health hazard - Skin corrosion or Irritation Health hazard - Specific target organ toxicity (single or repeated exposure)

# CV3-1144-1

## Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 15.2. US State Regulations

Solvent naphtha, petroleum, light aliphatic (64742-89-8)	
U.S. - California - Safer Consumer Products - Initial List of Candidate Chemicals and Chemical Groups	
U.S. - Texas - Effects Screening Levels - Long Term	
U.S. - Texas - Effects Screening Levels - Short Term	
2-Butanone, O,O',O''-(methylsilyldiyl)trioxime (22984-54-9)	
U.S. - Texas - Effects Screening Levels - Long Term	
U.S. - Texas - Effects Screening Levels - Short Term	
N-[3-(Trimethoxysilyl)propyl]-1,2-ethanediamine (1760-24-3)	
U.S. - Texas - Effects Screening Levels - Long Term	
U.S. - Texas - Effects Screening Levels - Short Term	
Titanium dioxide (13463-67-7)	
U.S. - Connecticut - Hazardous Air Pollutants - HLVs (30 min)	
U.S. - Connecticut - Hazardous Air Pollutants - HLVs (8 hr)	
U.S. - Idaho - Occupational Exposure Limits - TWAs	
U.S. - Illinois - Toxic Air Contaminant Carcinogens	
RTK - U.S. - Massachusetts - Right To Know List	
U.S. - Michigan - Occupational Exposure Limits - TWAs	
U.S. - Minnesota - Chemicals of High Concern	
U.S. - Minnesota - Hazardous Substance List	
U.S. - Minnesota - Permissible Exposure Limits - TWAs	
U.S. - New Hampshire - Regulated Toxic Air Pollutants - Ambient Air Levels (AALs) - 24-Hour	
U.S. - New Hampshire - Regulated Toxic Air Pollutants - Ambient Air Levels (AALs) - Annual	
RTK - U.S. - New Jersey - Right to Know Hazardous Substance List	
U.S. - New York - Occupational Exposure Limits - TWAs	
U.S. - North Dakota - Air Pollutants - Guideline Concentrations - 8-Hour	
U.S. - Oregon - Permissible Exposure Limits - TWAs	
U.S. - California - Safer Consumer Products - Initial List of Candidate Chemicals and Chemical Groups	
RTK - U.S. - Pennsylvania - RTK (Right to Know) List	
U.S. - Tennessee - Occupational Exposure Limits - TWAs	
U.S. - Texas - Effects Screening Levels - Long Term	
U.S. - Texas - Effects Screening Levels - Short Term	
U.S. - Vermont - Permissible Exposure Limits - TWAs	
U.S. - Washington - Permissible Exposure Limits - STELs	
U.S. - Washington - Permissible Exposure Limits - TWAs	
Titanium dioxide (13463-67-7)	
U.S. - California - Proposition 65 - Carcinogens List	WARNING: This product contains chemicals known to the State of California to cause cancer.
Synthetic Amorphous, Pyrogenic Silica (112945-52-5)	
U.S. - Texas - Effects Screening Levels - Long Term	
U.S. - Texas - Effects Screening Levels - Short Term	

# CV3-1144-1

## Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Dibutyltin dilaurate (77-58-7)	
U.S. - New Hampshire - Regulated Toxic Air Pollutants - Ambient Air Levels (AALs) - 24-Hour U.S. - New Hampshire - Regulated Toxic Air Pollutants - Ambient Air Levels (AALs) - Annual U.S. - California - Safer Consumer Products - Initial List of Candidate Chemicals and Chemical Groups U.S. - Texas - Effects Screening Levels - Long Term U.S. - Texas - Effects Screening Levels - Short Term	
Chromium oxide (Cr <sub>2</sub> O <sub>3</sub> ) (1308-38-9)	
RTK - U.S. - Massachusetts - Right To Know List RTK - U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Texas - Effects Screening Levels - Long Term U.S. - Texas - Effects Screening Levels - Short Term	
Cadmium compounds	
U.S. - California - Proposition 65 - Carcinogens List	WARNING: This product contains chemicals known to the State of California to cause cancer.

## SECTION 16: Other Information, Including Date of Preparation or Last Revision

Date of Preparation or Latest Revision 01/11/2021

Revision

Other Information

This document has been prepared in accordance with the SDS requirements of the OSHA Hazard Communication Standard 29 CFR 1910.1200.

GHS Full Text Phrases:

Acute Tox. 4 (Inhalation:dust,mist)	Acute toxicity (inhalation:dust,mist) Category 4
Aquatic Acute 1	Hazardous to the aquatic environment - Acute Hazard Category 1
Aquatic Acute 2	Hazardous to the aquatic environment - Acute Hazard Category 2
Aquatic Acute 3	Hazardous to the aquatic environment - Acute Hazard Category 3
Aquatic Chronic 1	Hazardous to the aquatic environment - Chronic Hazard Category 1
Asp. Tox. 1	Aspiration hazard Category 1
Eye Dam. 1	Serious eye damage/eye irritation Category 1
Eye Irrit. 2A	Serious eye damage/eye irritation Category 2A
Flam. Liq. 2	Flammable liquids Category 2
Muta. 2	Germ cell mutagenicity Category 2
Repr. 1B	Reproductive toxicity Category 1B
Skin Corr. 1C	Skin corrosion/irritation Category 1C
Skin Irrit. 2	Skin corrosion/irritation Category 2
Skin Sens. 1	Skin sensitization, Category 1
Skin Sens. 1B	Skin sensitization, category 1B
STOT RE 1	Specific target organ toxicity (repeated exposure) Category 1

# CV3-1144-1

## Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

STOT RE 2	Specific target organ toxicity (repeated exposure) Category 2
STOT SE 1	Specific target organ toxicity (single exposure) Category 1
H225	Highly flammable liquid and vapor
H304	May be fatal if swallowed and enters airways
H314	Causes severe skin burns and eye damage
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H318	Causes serious eye damage
H319	Causes serious eye irritation
H332	Harmful if inhaled
H341	Suspected of causing genetic defects
H360	May damage fertility or the unborn child
H370	Causes damage to organs
H372	Causes damage to organs through prolonged or repeated exposure
H373	May cause damage to organs through prolonged or repeated exposure
H400	Very toxic to aquatic life
H401	Toxic to aquatic life
H402	Harmful to aquatic life
H410	Very toxic to aquatic life with long lasting effects

NFPA Health Hazard

3 - Materials that, under emergency conditions, can cause serious or permanent injury.

NFPA Fire Hazard

3 - Liquids and solids (including finely divided suspended solids) that can be ignited under almost all ambient temperature conditions.

NFPA Reactivity Hazard


0 - Material that in themselves are normally stable, even under fire conditions.

HMIS III Rating  
Health

3 Serious Hazard - Major injury likely unless prompt action is taken and medical treatment is given  
\* Chronic - Chronic (long-term) health effects may result from repeated overexposure

Flammability  
Physical

3 Serious Hazard  
0 Minimal Hazard



The information provided in this Safety Data Sheet (SDS) was prepared based on data believed to be accurate as of the date of this SDS. TO THE GREATEST EXTENT PERMITTED BY LAW, NUSIL TECHNOLOGY LLC AND ITS AFFILIATED COMPANIES ("NUSIL") EXPRESSLY DISCLAIMS ANY AND ALL REPRESENTATIONS AND WARRANTIES REGARDING THE INFORMATION CONTAINED HEREIN INCLUDING, WITHOUT LIMITATION, AS TO ACCURACY, COMPLETENESS, FITNESS FOR PURPOSE OR USE, MERCHANTABILITY, NON-INFRINGEMENT, PERFORMANCE, SAFETY, SUITABILITY AND

# CV3-1144-1

## Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

---

STABILITY. This SDS is intended as a guide to the appropriate use, handling, storage and disposal of the product to which it relates by properly trained personnel, and is not intended to be comprehensive. Users of NuSil's products are advised to perform their own tests and to exercise their own judgment to determine the safety, suitability and appropriate use, handling, storage and disposal of each product and product combination for their own purposes and uses. TO THE GREATEST EXTENT PERMITTED BY LAW, NUSIL DISCLAIMS LIABILITY FOR, AND BY USING NUSIL'S PRODUCTS PURCHASER AGREES THAT UNDER NO CIRCUMSTANCES SHALL NUSIL BE LIABLE FOR, SPECIAL, INDIRECT, INCIDENTAL, PUNITIVE OR CONSEQUENTIAL DAMAGES OF ANY TYPE OR KIND, INCLUDING WITHOUT LIMITATION, FOR LOSS OF PROFITS, REPUTATIONAL DAMAGE, PRODUCT RECALL OR BUSINESS INTERRUPTION.

NuSil US GHS SDS