

MED10-6400 Part A

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations
Revision Date: 05/29/2024 Date of Issue: 01/23/2014

Version: 5.0

SECTION 1: Identification

1.1. Product Identifier

Product Form Mixture
Product Name MED10-6400 Part A
Synonyms Silicone Dispersion

1.2. Relevant Identified Uses of the Substance or Mixture and Uses Advised Against

Use of the Substance/Mixture For professional use only.

1.3. Details of the Supplier of the Safety Data Sheet

NuSil Technology LLC
1050 Cindy Lane
Carpinteria, California 93013
USA
(805) 684-8780

productstewardship@avantorsciencesgcc.com

www.nusil.com

1.4. Emergency Telephone Number

Emergency Number 800-424-9300 CHEMTREC (in US); +1 703-527-3887 CHEMTREC (International and Maritime)

SECTION 2: Hazards Identification

2.1. Classification of the Substance or Mixture

GHS-US Classification

Flammable liquids Category 3	H226
Acute toxicity (dermal) Category 4	H312
Acute toxicity (inhalation:vapor) Category 4	H332
Skin corrosion/irritation Category 2	H315
Serious eye damage/eye irritation Category 2	H319
Reproductive toxicity Category 2	H361
Specific target organ toxicity – Single exposure, Category 3, Respiratory tract irritation	H335
Specific target organ toxicity (repeated exposure) Category 2	H373
Aspiration hazard Category 1	H304
Hazardous to the aquatic environment – Acute Hazard Category 2	H401
Hazardous to the aquatic environment – Chronic Hazard Category 3	H412

2.2. Label Elements

GHS-US Labeling

Hazard Pictograms (GHS-US)



GHS02

GHS07

GHS08

Signal Word (GHS-US)

Danger

Hazard Statements (GHS-US)

H226 - Flammable liquid and vapor
H304 - May be fatal if swallowed and enters airways
H312+H332 - Harmful in contact with skin or if inhaled
H315 - Causes skin irritation
H319 - Causes serious eye irritation

MED10-6400 Part A

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Precautionary Statements (GHS-US)

H335 - May cause respiratory irritation
H361 - Suspected of damaging fertility or the unborn child
H373 - May cause damage to organs (central nervous system, hearing organs, liver) through prolonged or repeated exposure
H401 - Toxic to aquatic life
H412 - Harmful to aquatic life with long lasting effects
P201 - Obtain special instructions before use.
P202 - Do not handle until all safety precautions have been read and understood.
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233 - Keep container tightly closed.
P240 - Ground/Bond container and receiving equipment.
P241 - Use explosion-proof electrical, ventilating, and lighting equipment.
P242 - Use only non-sparking tools.
P243 - Take precautionary measures against static discharge.
P260 - Do not breathe vapors, mist, or spray.
P264 - Wash hands, forearms, and other exposed areas thoroughly after handling.
P271 - Use only outdoors or in a well-ventilated area.
P273 - Avoid release to the environment.
P280 - Wear protective gloves, protective clothing, and eye protection.
P301+P310 - If swallowed: Immediately call a poison center or doctor.
P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304+P340 - If inhaled: Remove person to fresh air and keep at rest in a position comfortable for breathing.
P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308+P313 - If exposed or concerned: Get medical advice/attention.
P321 - Specific treatment (see section 4 on this SDS).
P331 - Do NOT induce vomiting.
P332+P313 - If skin irritation occurs: Get medical advice/attention.
P337+P313 - If eye irritation persists: Get medical advice/attention.
P362+P364 - Take off contaminated clothing and wash it before reuse.
P370+P378 - In case of fire: Use appropriate media (see section 5) to extinguish.
P403+P235 - Store in a well-ventilated place. Keep cool.
P405 - Store locked up.
P501 - Dispose of contents/container in accordance with local, regional, national, and international regulations.

MED10-6400 Part A

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

2.3. Other Hazards

Other Hazards Not Contributing to the Classification Exposure may aggravate pre-existing eye, skin, or respiratory conditions.

2.4. Unknown Acute Toxicity (GHS-US)

No additional information available

SECTION 3: Composition/Information On Ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product Identifier	%*	GHS-US Classification
Xylenes (o-, m-, p- isomers)	(CAS-No.) 1330-20-7	60 - 80	Flam. Liq. 3, H226 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation:vapour), H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335 STOT RE 2, H373 Asp. Tox. 1, H304 Aquatic Acute 2, H401
Silanamine, 1,1,1-trimethyl-N-(trimethylsilyl)-, hydrolysis products with silica	(CAS-No.) 68909-20-6	< 10	Not classified
Octamethylcyclotetrasiloxane	(CAS-No.) 556-67-2	< 0.25	Flam. Liq. 3, H226 Repr. 2, H361 Aquatic Chronic 1, H410

Full text of H-phrases: see section 16

*The specific chemical identity and/or exact percentage of composition have been withheld as a trade secret [29 CFR 1910.1200].

SECTION 4: First Aid Measures

4.1. Description of First-aid Measures

First-aid Measures General	Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).
First-aid Measures After Inhalation	Remove to fresh air and keep at rest in a position comfortable for breathing. Give oxygen or artificial respiration if necessary. Get medical advice/attention.
First-aid Measures After Skin Contact	Immediately remove contaminated clothing. Immediately drench affected area with water for at least 15 minutes. Immediately call a poison center or doctor/physician.
First-aid Measures After Eye Contact	Immediately rinse with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center or doctor/physician.

MED10-6400 Part A

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

First-aid Measures After Ingestion

Do NOT induce vomiting. Turn affected person(s) on their side and maintain in that position to prevent aspiration. Rinse mouth. Immediately call a POISON CENTER or doctor/physician.

4.2. Most Important Symptoms and Effects Both Acute and Delayed

Symptoms/Injuries

May be fatal if swallowed and enters airways. Harmful if inhaled. Harmful in contact with skin. Causes skin irritation. Causes serious eye irritation. May cause respiratory irritation. May cause damage to organs (central nervous system, hearing organs, liver) through prolonged or repeated exposure. Suspected of damaging fertility.

Symptoms/Injuries After Inhalation

Inhalation is likely to cause adverse health effects including but not limited to: irritation, difficulty breathing, and unconsciousness. Irritation of the respiratory tract and the other mucous membranes.

Symptoms/Injuries After Skin Contact

This material is harmful through skin contact, and can cause adverse health effects or death in significant amounts. This material may be absorbed through the skin and eyes. Redness, pain, swelling, itching, burning, dryness, and dermatitis.

Symptoms/Injuries After Eye Contact

Contact causes severe irritation with redness and swelling of the conjunctiva.

Symptoms/Injuries After Ingestion

Aspiration into the lungs can occur during ingestion or vomiting and may cause lung injury.

Chronic Symptoms

Suspected of damaging fertility. May cause damage to organs (central nervous system, hearing organs, liver) through prolonged or repeated exposure.

4.3. Indication of Any Immediate Medical Attention and Special Treatment Needed

If exposed or concerned, get medical advice and attention. If medical advice is needed, have product container or label at hand.

SECTION 5: Fire-Fighting Measures

5.1. Extinguishing Media

Suitable Extinguishing Media

: Dry chemical powder, alcohol-resistant foam, carbon dioxide (CO₂). Water may be ineffective but water should be used to keep fire-exposed container cool.

Unsuitable Extinguishing Media

: Do not use a heavy water stream. A heavy water stream may spread burning liquid.

5.2. Special Hazards Arising From the Substance or Mixture

Fire Hazard

Flammable liquid and vapor. Vapors may travel to source of ignition and flash back. Will float and can be reignited on water surface.

Explosion Hazard

May form flammable or explosive vapor-air mixture.

Reactivity

Reacts violently with strong oxidizers. Increased risk of fire or explosion.

5.3. Advice for Firefighters

Precautionary Measures Fire

Firefighting Instructions

Exercise caution when fighting any chemical fire.

Use water spray or fog for cooling exposed containers. In case of major fire and large quantities: Evacuate area. Fight fire remotely due to the risk of explosion.

MED10-6400 Part A

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Protection During Firefighting	Do not enter fire area without proper protective equipment, including respiratory protection.
Hazardous Combustion Products	Carbon oxides (CO, CO ₂). Nitrogen oxides. Silicon oxides. Oxides of platinum. Formaldehyde.
Other Information	Do not allow run-off from fire fighting to enter drains or water courses.

SECTION 6: Accidental Release Measures

6.1. Personal Precautions, Protective Equipment And Emergency Procedures

General Measures	Keep away from heat, hot surfaces, sparks, open flames, and other ignition sources. No smoking. Use special care to avoid static electric charges. Do not get in eyes, on skin, or on clothing. Do not breathe vapor, mist or spray.
------------------	--

6.1.1. For Non-Emergency Personnel

Protective Equipment	Use appropriate personal protective equipment (PPE).
Emergency Procedures	Evacuate unnecessary personnel. Stop leak if safe to do so.

6.1.2. For emergency responders

Protective Equipment	Equip cleanup crew with proper protection.
Emergency Procedures	Eliminate ignition sources first, then ventilate the area. Upon arrival at the scene, a first responder is expected to recognize the presence of dangerous goods, protect oneself and the public, secure the area, and call for the assistance of trained personnel as soon as conditions permit.

6.2. Environmental Precautions

Prevent entry to sewers and public waters. Avoid release to the environment.

6.3. Methods and Materials for Containment and Cleaning Up

For Containment	As an immediate precautionary measure, isolate spill or leak area in all directions. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.
Methods for Cleaning Up	Clean up spills immediately and dispose of waste safely. Use only non-sparking tools. Absorb and/or contain spill with inert material. Do not take up in combustible material such as: saw dust or cellulosic material. Transfer spilled material to a suitable container for disposal. Contact competent authorities after a spill.

6.4. Reference to Other Sections

See Section 8 for exposure controls and personal protection and Section 13 for disposal considerations.

SECTION 7: Handling And Storage

7.1. Precautions for Safe Handling

Additional Hazards When Processed	Will decompose above 150 °C (> 300 °F) releasing formaldehyde vapors. Handle empty containers with care because residual vapors are flammable.
-----------------------------------	--

MED10-6400 Part A

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Precautions for Safe Handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use only non-sparking tools. Take precautionary measures against static discharge. Do not breathe vapors, mist, spray. Do not get in eyes, on skin, or on clothing. Handle empty containers with care because they may still present a hazard. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

Hygiene Measures

Handle in accordance with good industrial hygiene and safety procedures.

7.2. Conditions for Safe Storage, Including Any Incompatibilities

Technical Measures

Use explosion-proof electrical, ventilating, and lighting equipment. Take action to prevent static discharges. Ground and bond container and receiving equipment. Comply with applicable regulations.

Storage Conditions

Store in a dry, cool place. Keep/Store away from direct sunlight, extremely high or low temperatures and incompatible materials. Store locked up/in a secure area. Store in a well-ventilated place. Keep container tightly closed. Keep in fireproof place.

Incompatible Materials

Strong acids, strong bases, strong oxidizers.

7.3. Specific End Use(s)

For professional use only.

SECTION 8: Exposure Controls/Personal Protection

8.1. Control Parameters

For substances listed in section 3 that are not listed here, there are no established exposure limits from the manufacturer, supplier, importer, or the appropriate advisory agency including: ACGIH (TLV), or OSHA (PEL).

Xylenes (o-, m-, p- isomers) (1330-20-7)		
USA ACGIH	ACGIH OEL TWA [ppm]	20 ppm
USA ACGIH	ACGIH chemical category	Not Classifiable as a Human Carcinogen
USA ACGIH	BEI (BLV)	1.5 g/g Kreatinin Parameter: Methylhippuric acids - Medium: urine - Sampling time: end of shift (technical or commercial grade)
USA OSHA	OSHA PEL (TWA) [1]	435 mg/m ³
USA OSHA	OSHA PEL (TWA) [2]	100 ppm
Silanamine, 1,1,1-trimethyl-N-(trimethylsilyl)-, hydrolysis products with silica (68909-20-6)		
USA NIOSH	NIOSH REL (TWA)	6 mg/m ³
USA OSHA	OSHA PEL (TWA) [1]	6 mg/m ³
USA OSHA	OSHA PEL (TWA) [2]	20 mppcf (80mg/m ³ /%SiO ₂)
Octamethylcyclotetrasiloxane (556-67-2)		
USA AIHA	WEEL TWA	10 ppm

MED10-6400 Part A

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

8.2. Exposure Controls

Appropriate Engineering Controls

Ensure adequate ventilation, especially in confined areas. Use explosion-proof equipment. Proper grounding procedures to avoid static electricity should be followed. Gas detectors should be used when flammable gases or vapors may be released. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Ensure all national/local regulations are observed. Gloves. Protective clothing. Protective goggles. Insufficient ventilation: wear respiratory protection.

Personal Protective Equipment



Materials For Protective Clothing

Chemically resistant materials and fabrics. Wear fire/flamm resistant/retardant clothing.

Hand Protection

Wear protective gloves.

Eye And Face Protection

Chemical safety goggles.

Skin And Body Protection

Wear suitable protective clothing.

Respiratory Protection

If exposure limits are exceeded or irritation is experienced, approved respiratory protection should be worn. In case of inadequate ventilation, oxygen deficient atmosphere, or where exposure levels are not known wear approved respiratory protection.

Other Information

When using, do not eat, drink or smoke.

SECTION 9: Physical and Chemical Properties

9.1. Information on Basic Physical and Chemical Properties

Physical State	Liquid
Appearance	Colorless
Odor	Solvent
Odor Threshold	No data available
pH	No data available
Evaporation Rate	No data available
Melting Point	No data available
Freezing Point	No data available
Boiling Point	140 °C (284 °F)
Flash Point	27 °C (81 °F)
Auto-ignition Temperature	No data available
Decomposition Temperature	No data available
Flammability (solid, gas)	Not applicable
Vapor Pressure	No data available
Relative Vapor Density at 20 °C	No data available
Relative Density	< 1 (Water = 1)
Specific Gravity	No data available
Solubility	No data available
Partition Coefficient n-Octanol/Water	No data available
Viscosity	No data available

MED10-6400 Part A

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

9.2. Other Information

VOC Content 60 – 80%

SECTION 10: Stability and Reactivity

10.1. Reactivity

Reacts violently with strong oxidizers. Increased risk of fire or explosion.

10.2. Chemical Stability

Flammable liquid and vapor. May form flammable or explosive vapor-air mixture.

10.3. Possibility of Hazardous Reactions

Hazardous polymerization will not occur.

10.4. Conditions to Avoid

Direct sunlight, extremely high or low temperatures, heat, hot surfaces, sparks, open flames, incompatible materials, and other ignition sources.

10.5. Incompatible Materials

Strong acids, strong bases, strong oxidizers.

10.6. Hazardous Decomposition Products

Thermal decomposition may produce: Carbon oxides (CO, CO₂). Nitrogen oxides. Silicon oxides.

Oxides of platinum. Will decompose above 150 °C (> 300 °F) releasing formaldehyde vapors.

Formaldehyde is a potential carcinogen and can act as a potential skin and respiratory sensitizer.

Formaldehyde can also cause respiratory and eye irritation.

SECTION 11: Toxicological Information

11.1. Information on Toxicological Effects

Acute Toxicity (Oral) Not classified
Acute Toxicity (Dermal) Harmful in contact with skin.
Acute Toxicity (Inhalation) Harmful if inhaled.

MED10-6400 Part A	
ATE (Dermal)	1,385.74 mg/kg body weight
ATE (Vapors)	13.81 mg/l/4h

Xylenes (o-, m-, p- isomers) (1330-20-7)	
LD50 Oral Rat	3523 mg/kg
LC50 Inhalation Rat	6247 ppm/4h (species: Sprague-Dawley)
ATE (Dermal)	1,100.00 mg/kg body weight
ATE (Vapors)	11.00 mg/l/4h

Octamethylcyclotetrasiloxane (556-67-2)	
LD50 Oral Rat	> 4800 mg/kg (No mortality)
LD50 Dermal Rat	> 2375 mg/kg
LD50 Dermal Rabbit	> 2.5 ml/kg (No mortality)
LC50 Inhalation Rat	36 mg/l/4h

Skin Corrosion/Irritation Causes skin irritation.
Serious Eye Damage/Irritation Causes serious eye irritation.
Respiratory or Skin Sensitization Not classified
Germ Cell Mutagenicity Not classified
Carcinogenicity Not classified

Xylenes (o-, m-, p- isomers) (1330-20-7)	
IARC Group	3

MED10-6400 Part A

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Reproductive Toxicity	Suspected of damaging fertility.
Specific Target Organ Toxicity (Single Exposure)	May cause respiratory irritation.
Specific Target Organ Toxicity (Repeated Exposure)	May cause damage to organs (central nervous system, hearing organs, liver) through prolonged or repeated exposure.
Aspiration Hazard	May be fatal if swallowed and enters airways.
Symptoms/Injuries After Inhalation	Inhalation is likely to cause adverse health effects including but not limited to: irritation, difficulty breathing, and unconsciousness. Irritation of the respiratory tract and the other mucous membranes.
Symptoms/Injuries After Skin Contact	This material is harmful through skin contact, and can cause adverse health effects or death in significant amounts. This material may be absorbed through the skin and eyes. Redness, pain, swelling, itching, burning, dryness, and dermatitis.
Symptoms/Injuries After Eye Contact	Contact causes severe irritation with redness and swelling of the conjunctiva.
Symptoms/Injuries After Ingestion	Aspiration into the lungs can occur during ingestion or vomiting and may cause lung injury.
Chronic Symptoms	Suspected of damaging fertility. May cause damage to organs (central nervous system, hearing organs, liver) through prolonged or repeated exposure.

SECTION 12: Ecological Information

12.1. Toxicity

Ecology - General Toxic to aquatic life. Harmful to aquatic life with long lasting effects.

Xylenes (o-, m-, p- isomers) (1330-20-7)	
LC50 Fish 1	3.3 mg/l
EC50 - Crustacea [1]	3.82 mg/l (Exposure time: 48 h - Species: water flea)
LC50 Fish 2	2.661 (2.661 – 4.093) mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [static])
Octamethylcyclotetrasiloxane (556-67-2)	
LC50 Fish 1	> 22 µg/l
NOEC Chronic Fish	0.0044 mg/l

12.2. Persistence and Degradability

MED10-6400 Part A	
Persistence and Degradability	May cause long-term adverse effects in the environment.

12.3. Bioaccumulative Potential

MED10-6400 Part A	
Bioaccumulative Potential	Not established.
Xylenes (o-, m-, p- isomers) (1330-20-7)	
BCF Fish 1	0.6 (0.6 – 15)
Partition coefficient n-octanol/water (Log Pow)	2.77 – 3.15
Octamethylcyclotetrasiloxane (556-67-2)	
BCF Fish 1	(12400 dimensionless)

MED10-6400 Part A

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 15: Regulatory Information

15.1. US Federal Regulations

All components in this mixture are listed on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory, have been exempted, or are not disclosed due to CBI requirements or disclosure rules according to the relevant regulation.

MED10-6400 Part A	
SARA Section 311/312 Hazard Classes	Health hazard - Specific target organ toxicity (single or repeated exposure) Health hazard - Reproductive toxicity Health hazard - Skin corrosion or Irritation Physical hazard - Flammable (gases, aerosols, liquids, or solids) Health hazard - Serious eye damage or eye irritation Health hazard - Acute toxicity (any route of exposure) Health hazard - Aspiration hazard
Xylenes (o-, m-, p- isomers) (1330-20-7)	
Subject to reporting requirements of United States SARA Section 313	
CERCLA RQ	100 lb
SARA Section 313 - Emission Reporting	1 %

15.2. US State Regulations

Xylenes (o-, m-, p- isomers) (1330-20-7)	
U.S. - California - Proposition 65 - Carcinogens List	WARNING: This product contains chemicals known to the State of California to cause cancer.
Xylenes (o-, m-, p- isomers) (1330-20-7)	
U.S. - California - SCAQMD - Toxic Air Contaminants - Non-Cancer Acute U.S. - California - SCAQMD - Toxic Air Contaminants - Non-Cancer Chronic U.S. - California - Toxic Air Contaminant List (AB 1807, AB 2728) U.S. - Colorado - Groundwater Quality Standards U.S. - Colorado - Hazardous Wastes - Discarded Chemical Products, Off-Specification Species, Container and Spill Residues U.S. - Colorado - Primary Drinking Water Regulations - Maximum Contaminant Level Goals (MCLGs) U.S. - Colorado - Primary Drinking Water Regulations - Maximum Contaminant Levels (MCLs) U.S. - Connecticut - Drinking Water Quality Standards - Maximum Contaminant Levels U.S. - Delaware - Pollutant Discharge Requirements - Reportable Quantities U.S. - Florida - Drinking Water Standards - Volatile Organic Contaminants - Maximum Contaminant Levels (MCLs) U.S. - Georgia - Drinking Water - Maximum Contaminant Levels (MCLs) U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Acceptable Ambient Concentrations U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Emission Levels (ELs) U.S. - Idaho - Occupational Exposure Limits - TWAs U.S. - Illinois - Toxic Air Contaminants	

MED10-6400 Part A

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

U.S. - Louisiana - Reportable Quantity List for Pollutants
U.S. - Maine - Air Pollutants - Hazardous Air Pollutants
U.S. - Massachusetts - Allowable Ambient Limits (AALs)
U.S. - Massachusetts - Allowable Threshold Concentrations (ATCs)
U.S. - Massachusetts - Drinking Water - Maximum Contaminant Levels (MCLs)
U.S. - Massachusetts - Oil & Hazardous Material List - Groundwater Reportable Concentration - Reporting Category 1
U.S. - Massachusetts - Oil & Hazardous Material List - Groundwater Reportable Concentration - Reporting Category 2
U.S. - Massachusetts - Oil & Hazardous Material List - Reportable Quantity
U.S. - Massachusetts - Oil & Hazardous Material List - Soil Reportable Concentration - Reporting Category 1
U.S. - Massachusetts - Oil & Hazardous Material List - Soil Reportable Concentration - Reporting Category 2
RTK - U.S. - Massachusetts - Right To Know List
U.S. - Massachusetts - Threshold Effects Exposure Limits (TELS)
U.S. - Massachusetts - Toxics Use Reduction Act
U.S. - Michigan - Occupational Exposure Limits - STELs
U.S. - Michigan - Occupational Exposure Limits - TWAs
U.S. - Michigan - Polluting Materials List
U.S. - Minnesota - Chemicals of High Concern
U.S. - Minnesota - Groundwater Health Risk Limits
U.S. - Minnesota - Hazardous Substance List
U.S. - Minnesota - Permissible Exposure Limits - STELs
U.S. - Minnesota - Permissible Exposure Limits - TWAs
U.S. - Missouri - Drinking Water - Maximum Contaminant Levels (MCLs)
U.S. - Nebraska - Drinking Water - Maximum Contaminant Levels (MCLs)
U.S. - New Hampshire - Drinking Water - Maximum Contaminant Levels (MCLs)
U.S. - New Hampshire - Regulated Toxic Air Pollutants - Ambient Air Levels (AALs) - 24-Hour
U.S. - New Hampshire - Regulated Toxic Air Pollutants - Ambient Air Levels (AALs) - Annual
U.S. - New Jersey - Discharge Prevention - List of Hazardous Substances
U.S. - New Jersey - Environmental Hazardous Substances List
U.S. - New Jersey - Primary Drinking Water Standards - Maximum Contaminant Levels - MCLs
RTK - U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - New Jersey - Special Health Hazards Substances List
U.S. - New Jersey - Water Quality - Ground Water Quality Criteria
U.S. - New Jersey - Water Quality - Practical Quantitation Levels (PQLs)
U.S. - New Mexico - Water Quality - Standards for Ground Water of 10,000 mg/L TDS Concentration or Less
U.S. - New York - Occupational Exposure Limits - TWAs
U.S. - New York - Reporting of Releases Part 597 - List of Hazardous Substances
U.S. - North Carolina - Control of Toxic Air Pollutants
U.S. - North Dakota - Air Pollutants - Guideline Concentrations - 1-Hour
U.S. - North Dakota - Air Pollutants - Guideline Concentrations - 8-Hour
U.S. - North Dakota - Hazardous Wastes - Discarded Chemical Products, Off-Specification Species, Container and Spill Residues
U.S. - North Dakota - Water Quality Standards - Human Health Value for Classes I, IA, II
U.S. - Oregon - Permissible Exposure Limits - TWAs
U.S. - California - Safer Consumer Products - Initial List of Candidate Chemicals and Chemical Groups
U.S. - Pennsylvania - Drinking Water - Maximum Contaminant Levels (MCLs)

MED10-6400 Part A

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

RTK - U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List
RTK - U.S. - Pennsylvania - RTK (Right to Know) List
U.S. - Rhode Island - Air Toxics - Acceptable Ambient Levels - 1-Hour
U.S. - Rhode Island - Air Toxics - Acceptable Ambient Levels - 24-Hour
U.S. - Rhode Island - Air Toxics - Acceptable Ambient Levels - Annual
U.S. - Rhode Island - Water Quality Standards - Acute Freshwater Aquatic Life Criteria
All concentrations are expressed as percentages by weight unless the ingredient is a gas.
U.S. - South Carolina - Maximum Contaminant Levels (MCLs)
U.S. - South Carolina - Toxic Air Pollutants - Maximum Allowable Concentrations
U.S. - South Carolina - Toxic Air Pollutants - Pollutant Categories
U.S. - Tennessee - Occupational Exposure Limits - STELs
U.S. - Tennessee - Occupational Exposure Limits - TWAs
U.S. - Texas - City of Austin - Aerosol Paint and Glue Restrictions
U.S. - Texas - Drinking Water Standards - Maximum Contaminant Levels (MCLs)
U.S. - Texas - Effects Screening Levels - Long Term
U.S. - Texas - Effects Screening Levels - Short Term
U.S. - Utah - Drinking Water - Maximum Contaminant Levels (MCLs)
U.S. - Washington - Dangerous Waste - Discarded Chemical Products List
U.S. - Washington - Permissible Exposure Limits - STELs
U.S. - Washington - Permissible Exposure Limits - TWAs
U.S. - West Virginia - Water Quality - Groundwater Standards - Ceiling Concentrations
U.S. - Wisconsin - Hazardous Air Contaminants - All Sources - Emissions From Stack Heights 25 Feet to Less Than 40 Feet
U.S. - Wisconsin - Hazardous Air Contaminants - All Sources - Emissions From Stack Heights 40 Feet to Less Than 75 Feet
U.S. - Wisconsin - Hazardous Air Contaminants - All Sources - Emissions From Stack Heights 75 Feet or Greater
U.S. - Wisconsin - Hazardous Air Contaminants - All Sources - Emissions From Stack Heights Less Than 25 Feet

Silanamine, 1,1,1-trimethyl-N-(trimethylsilyl)-, hydrolysis products with silica (68909-20-6)

U.S. - Texas - Effects Screening Levels - Long Term

U.S. - Texas - Effects Screening Levels - Short Term

Octamethylcyclotetrasiloxane (556-67-2)

U.S. - Texas - Effects Screening Levels - Long Term

U.S. - Texas - Effects Screening Levels - Short Term

U.S. - Maine - Chemicals of Concern

U.S. - Oregon - Priority Persistent Pollutant - Tier I - Persistent Pollutants

U.S. - Minnesota - Chemicals of High Concern

U.S. - Minnesota - Chemicals of High Concern - Persistent Bioaccumulative Toxins

U.S. - California - Safer Consumer Products - Initial List of Candidate Chemicals and Chemical Groups

SECTION 16: Other Information, Including Date of Preparation or Last Revision

Date of Preparation or Latest Revision 05/29/2024

Revision

Other Information

This document has been prepared in accordance with the SDS requirements of the OSHA Hazard Communication Standard 29 CFR 1910.1200.

GHS Full Text Phrases:

MED10-6400 Part A

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

H226	Flammable liquid and vapor
H227	Combustible liquid
H304	May be fatal if swallowed and enters airways
H312	Harmful in contact with skin
H315	Causes skin irritation
H319	Causes serious eye irritation
H332	Harmful if inhaled
H335	May cause respiratory irritation
H361	Suspected of damaging fertility or the unborn child
H373	May cause damage to organs through prolonged or repeated exposure
H401	Toxic to aquatic life
H410	Very toxic to aquatic life with long lasting effects
H412	Harmful to aquatic life with long lasting effects

NFPA Health Hazard

3 - Materials that, under emergency conditions, can cause serious or permanent injury.

NFPA Fire Hazard

3 - Liquids and solids (including finely divided suspended solids) that can be ignited under almost all ambient temperature conditions.

NFPA Reactivity Hazard


0 - Material that in themselves are normally stable, even under fire conditions.

HMIS III Rating
Health

3 Serious Hazard
* Chronic - Chronic (long-term) health effects may result from repeated overexposure

Flammability
Physical

3 Serious Hazard
0 Minimal Hazard



The information provided in this Safety Data Sheet (SDS) was prepared based on data believed to be accurate as of the date of this SDS. TO THE GREATEST EXTENT PERMITTED BY LAW, NUSIL TECHNOLOGY LLC AND ITS AFFILIATED COMPANIES ("NUSIL") EXPRESSLY DISCLAIMS ANY AND ALL REPRESENTATIONS AND WARRANTIES REGARDING THE INFORMATION CONTAINED HEREIN INCLUDING, WITHOUT LIMITATION, AS TO ACCURACY, COMPLETENESS, FITNESS FOR PURPOSE OR USE, MERCHANTABILITY, NON-INFRINGEMENT, PERFORMANCE, SAFETY, SUITABILITY AND STABILITY. This SDS is intended as a guide to the appropriate use, handling, storage and disposal of the product to which it relates by properly trained personnel, and is not intended to be comprehensive. Users of NuSil's products are advised to perform their own tests and to exercise their own judgment to determine the safety, suitability and appropriate use, handling, storage and disposal of each product and product combination for their own purposes and uses. TO THE GREATEST EXTENT PERMITTED BY LAW, NUSIL DISCLAIMS LIABILITY FOR, AND BY USING NUSIL'S PRODUCTS PURCHASER AGREES THAT UNDER NO CIRCUMSTANCES SHALL NUSIL BE LIABLE FOR, SPECIAL, INDIRECT, INCIDENTAL, PUNITIVE OR CONSEQUENTIAL DAMAGES OF ANY TYPE OR KIND, INCLUDING WITHOUT LIMITATION, FOR LOSS OF PROFITS, REPUTATIONAL DAMAGE, PRODUCT RECALL OR BUSINESS INTERRUPTION.

MED10-6400 Part B

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations
Revision Date: 05/29/2024 Date of Issue: 01/23/2014

Version 5.0

SECTION 1: Identification

1.1. Product Identifier

Product Form Mixture
Product Name MED10-6400 Part B
Synonyms Silicone Dispersion

1.2. Relevant Identified Uses of the Substance or Mixture and Uses Advised Against

Use of the Substance/Mixture For professional use only.

1.3. Details of the Supplier of the Safety Data Sheet

NuSil Technology LLC
1050 Cindy Lane
Carpinteria, California 93013
USA
(805) 684-8780

productstewardship@avantorsciencesgcc.com

www.nusil.com

1.4. Emergency Telephone Number

Emergency Number 800-424-9300 CHEMTREC (in US); +1 703-527-3887 CHEMTREC (International and Maritime)

SECTION 2: Hazards Identification

2.1. Classification of the Substance or Mixture

GHS-US Classification

Flammable liquids Category 3	H226
Acute toxicity (dermal) Category 4	H312
Acute toxicity (inhalation:vapor) Category 4	H332
Skin corrosion/irritation Category 2	H315
Serious eye damage/eye irritation Category 2	H319
Reproductive toxicity Category 2	H361
Specific target organ toxicity – Single exposure, Category 3, Respiratory tract irritation	H335
Specific target organ toxicity (repeated exposure) Category 2	H373
Aspiration hazard Category 1	H304
Hazardous to the aquatic environment – Acute Hazard Category 2	H401
Hazardous to the aquatic environment – Chronic Hazard Category 3	H412

2.2. Label Elements

GHS-US Labeling

Hazard Pictograms (GHS-US)



GHS02



GHS07



GHS08

Signal Word (GHS-US)

Danger

MED10-6400 Part B

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Hazard Statements (GHS-US)

H226 - Flammable liquid and vapor
H304 - May be fatal if swallowed and enters airways
H312+H332 - Harmful in contact with skin or if inhaled
H315 - Causes skin irritation
H319 - Causes serious eye irritation
H335 - May cause respiratory irritation
H361 - Suspected of damaging fertility or the unborn child
H373 - May cause damage to organs (central nervous system, hearing organs, liver) through prolonged or repeated exposure
H401 - Toxic to aquatic life
H412 - Harmful to aquatic life with long lasting effects

Precautionary Statements (GHS-US)

P201 - Obtain special instructions before use.
P202 - Do not handle until all safety precautions have been read and understood.
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233 - Keep container tightly closed.
P240 - Ground/Bond container and receiving equipment.
P241 - Use explosion-proof electrical, lighting, ventilating equipment.
P242 - Use only non-sparking tools.
P243 - Take precautionary measures against static discharge.
P260 - Do not breathe vapors, mist, or spray.
P264 - Wash hands, forearms, and exposed areas thoroughly after handling.
P271 - Use only outdoors or in a well-ventilated area.
P273 - Avoid release to the environment.
P280 - Wear eye protection, protective clothing, protective gloves.
P301+P310 - If swallowed: Immediately call a poison center or doctor.
P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304+P340 - If inhaled: Remove person to fresh air and keep at rest in a position comfortable for breathing.
P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308+P313 - If exposed or concerned: Get medical advice/attention.
P321 - Specific treatment (see Section 4 on this SDS).
P331 - Do NOT induce vomiting.
P332+P313 - If skin irritation occurs: Get medical advice/attention.
P337+P313 - If eye irritation persists: Get medical advice/attention.
P362+P364 - Take off contaminated clothing and wash it before reuse.

MED10-6400 Part B

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P370+P378 - In case of fire: Use dry chemical powder, alcohol-resistant foam, carbon dioxide (CO₂) to extinguish.
P403+P235 - Store in a well-ventilated place. Keep cool.
P405 - Store locked up.
P501 - Dispose of contents/container in accordance with local, regional, national, and international regulations.

2.3. Other Hazards

Other Hazards Not Contributing to the Classification Exposure may aggravate pre-existing eye, skin, or respiratory conditions.

2.4. Unknown Acute Toxicity (GHS-US)

No additional information available

SECTION 3: Composition/Information On Ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product Identifier	%	GHS-US Classification
Xylenes (o-, m-, p- isomers)	(CAS-No.) 1330-20-7	60 - 80	Flam. Liq. 3, H226 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation:vapour), H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335 STOT RE 2, H373 Asp. Tox. 1, H304 Aquatic Acute 2, H401
Silanamine, 1,1,1-trimethyl-N-(trimethylsilyl)-, hydrolysis products with silica	(CAS-No.) 68909-20-6	< 10	Not classified
Siloxanes and Silicones, dimethyl, methyl hydrogen	(CAS-No.) 68037-59-2	< 3	Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335
Octamethylcyclotetrasiloxane	(CAS-No.) 556-67-2	< 0.25	Flam. Liq. 3, H226 Repr. 2, H361 Aquatic Chronic 1, H410
3-Butyn-2-ol, 2-methyl-	(CAS-No.) 115-19-5	< 0.25	Flam. Liq. 2, H225 Acute Tox. 4 (Oral), H302 Eye Dam. 1, H318 Repr. 2, H361 STOT SE 3, H336

Full text of H-phrases: see section 1.6

MED10-6400 Part B

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 4: First Aid Measures

4.1. Description of First-aid Measures

First-aid Measures General	Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).
First-aid Measures After Inhalation	When symptoms occur: go into open air and ventilate suspected area. Remove to fresh air and keep at rest in a position comfortable for breathing. Get medical advice/attention.
First-aid Measures After Skin Contact	Immediately remove contaminated clothing. Immediately drench affected area with water for at least 15 minutes. Immediately call a poison center or doctor/physician.
First-aid Measures After Eye Contact	Immediately rinse with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center or doctor/physician.
First-aid Measures After Ingestion	Rinse mouth. Do NOT induce vomiting. Place affected person on their side. Immediately call a POISON CENTER or doctor/physician.

4.2. Most Important Symptoms and Effects Both Acute and Delayed

Symptoms/Injuries	May be fatal if swallowed and enters airways. Harmful in contact with skin. Harmful if inhaled. Causes skin irritation. Causes serious eye irritation. May cause respiratory irritation. May cause damage to organs (central nervous system, hearing organs, liver) through prolonged or repeated exposure. Suspected of damaging fertility or the unborn child.
Symptoms/Injuries After Inhalation	Inhalation is likely to cause adverse health effects including but not limited to: irritation, difficulty breathing, and unconsciousness.
Symptoms/Injuries After Skin Contact	Redness, pain, swelling, itching, burning, dryness, and dermatitis. This material is harmful through skin contact, and can cause adverse health effects or death in significant amounts. This material may be absorbed through the skin and eyes.
Symptoms/Injuries After Eye Contact	Contact causes severe irritation with redness and swelling of the conjunctiva.
Symptoms/Injuries After Ingestion	Aspiration into the lungs can occur during ingestion or vomiting and may cause lung injury.
Chronic Symptoms	May cause damage to organs (central nervous system, hearing organs, liver) through prolonged or repeated exposure. Suspected of damaging fertility or the unborn child.

4.3. Indication of Any Immediate Medical Attention and Special Treatment Needed

If exposed or concerned, get medical advice and attention. If medical advice is needed, have product container or label at hand.

MED10-6400 Part B

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 5: Fire-Fighting Measures

5.1. Extinguishing Media

Suitable Extinguishing Media : Dry chemical powder, alcohol-resistant foam, carbon dioxide (CO₂). Water may be ineffective but water should be used to keep fire-exposed container cool.

Unsuitable Extinguishing Media : Do not use a heavy water stream. A heavy water stream may spread burning liquid.

5.2. Special Hazards Arising From the Substance or Mixture

Fire Hazard Flammable liquid and vapor. Vapors may travel to source of ignition and flash back. Will float and can be reignited on water surface.

Explosion Hazard May form flammable or explosive vapor-air mixture.

Reactivity Contact with water, alcohols, acids or bases, and many metals or metallic compounds can liberate flammable Hydrogen gas which can form explosive mixtures in air. Reacts violently with strong oxidizers. Increased risk of fire or explosion.

5.3. Advice for Firefighters

Precautionary Measures Fire Firefighting Instructions Exercise caution when fighting any chemical fire. Use water spray or fog for cooling exposed containers. In case of major fire and large quantities: Evacuate area. Fight fire remotely due to the risk of explosion.

Protection During Firefighting Do not enter fire area without proper protective equipment, including respiratory protection.

Hazardous Combustion Products Carbon oxides (CO, CO₂). Silicon oxides. Formaldehyde. Explosive hydrogen gas.

Other Information Do not allow run-off from fire fighting to enter drains or water courses.

SECTION 6: Accidental Release Measures

6.1. Personal Precautions, Protective Equipment And Emergency Procedures

General Measures Keep away from heat, hot surfaces, sparks, open flames, and other ignition sources. No smoking. Use special care to avoid static electric charges. Do not get in eyes, on skin, or on clothing. Do not breathe vapor, mist or spray.

6.1.1. For Non-Emergency Personnel

Protective Equipment Use appropriate personal protective equipment (PPE).

Emergency Procedures Evacuate unnecessary personnel. Stop leak if safe to do so.

6.1.2. For emergency responders

Protective Equipment Equip cleanup crew with proper protection.

Emergency Procedures Eliminate ignition sources first, then ventilate the area. Upon arrival at the scene, a first responder is expected to recognize the presence of dangerous goods, protect oneself and the public, secure the area, and call for the assistance of trained personnel as soon as conditions permit.

6.2. Environmental Precautions

Prevent entry to sewers and public waters. Avoid release to the environment.

MED10-6400 Part B

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

6.3. Methods and Materials for Containment and Cleaning Up

For Containment

As an immediate precautionary measure, isolate spill or leak area in all directions. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. Ventilate area.

Methods for Cleaning Up

Clean up spills immediately and dispose of waste safely. Use only non-sparking tools. Absorb and/or contain spill with inert material. Do not take up in combustible material such as: saw dust or cellulosic material. Transfer spilled material to a suitable container for disposal. Contact competent authorities after a spill.

6.4. Reference to Other Sections

See Section 8 for exposure controls and personal protection and Section 13 for disposal considerations.

SECTION 7: Handling And Storage

7.1. Precautions for Safe Handling

Additional Hazards When Processed

Will decompose above 150 °C (> 300 °F) releasing formaldehyde vapors. Handle empty containers with care because residual vapors are flammable.

Precautions for Safe Handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use only outdoors or in a well-ventilated area. Use only non-sparking tools. Take precautionary measures against static discharge. Do not get in eyes, on skin, or on clothing. Do not breathe vapor, mist, or spray. Handle empty containers with care because they may still present a hazard. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

Hygiene Measures

Handle in accordance with good industrial hygiene and safety procedures.

7.2. Conditions for Safe Storage, Including Any Incompatibilities

Technical Measures

Use explosion-proof electrical, ventilating, and lighting equipment. Take action to prevent static discharges. Ground and bond container and receiving equipment. Comply with applicable regulations.

Storage Conditions

Store in a dry, cool place. Keep/Store away from direct sunlight, extremely high or low temperatures and incompatible materials. Store locked up/in a secure area. Store in a well-ventilated place. Keep container tightly closed. Keep in fireproof place.

Incompatible Materials

Alcohols. Metals. Strong acids, strong bases, strong oxidisers. Water.

7.3. Specific End Use(S)

For professional use only.

MED10-6400 Part B

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 8: Exposure Controls/Personal Protection

8.1. Control Parameters

For substances listed in section 3 that are not listed here, there are no established exposure limits from the manufacturer, supplier, importer, or the appropriate advisory agency including: ACGIH (TLV), or OSHA (PEL).

Xylenes (o-, m-, p- isomers) (1330-20-7)		
USA ACGIH	ACGIH OEL TWA [ppm]	20 ppm
USA ACGIH	ACGIH chemical category	Not Classifiable as a Human Carcinogen
USA ACGIH	BEI (BLV)	1.5 g/g Kreatinin Parameter: Methylhippuric acids - Medium: urine - Sampling time: end of shift (technical or commercial grade)
USA OSHA	OSHA PEL (TWA) [1]	435 mg/m ³
USA OSHA	OSHA PEL (TWA) [2]	100 ppm
Silanamine, 1,1,1-trimethyl-N-(trimethylsilyl)-, hydrolysis products with silica (68909-20-6)		
USA NIOSH	NIOSH REL (TWA)	6 mg/m ³
USA OSHA	OSHA PEL (TWA) [1]	6 mg/m ³
USA OSHA	OSHA PEL (TWA) [2]	20 mppcf (80mg/m ³ /%SiO ₂)
Octamethylcyclotetrasiloxane (556-67-2)		
USA AIHA	WEEL TWA	10 ppm

8.2. Exposure Controls

Appropriate Engineering Controls

Ensure adequate ventilation, especially in confined areas. Use explosion-proof equipment. Proper grounding procedures to avoid static electricity should be followed. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Gas detectors should be used when flammable gases or vapors may be released. Gas detectors should be used when toxic gases may be released. Ensure all national/local regulations are observed. Gloves. Protective clothing. Protective goggles. Insufficient ventilation: wear respiratory protection.

Personal Protective Equipment



Materials For Protective Clothing

Chemically resistant materials and fabrics. Wear fire/ flame resistant/retardant clothing.

Hand Protection

Wear protective gloves.

Eye And Face Protection

Chemical safety goggles.

Skin And Body Protection

Wear suitable protective clothing.

Respiratory Protection

If exposure limits are exceeded or irritation is experienced, approved respiratory protection should be worn. In case of inadequate ventilation, oxygen deficient atmosphere, or where exposure levels are not known wear approved respiratory protection.

Other Information

When using, do not eat, drink or smoke.

MED10-6400 Part B

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 9: Physical and Chemical Properties

9.1. Information on Basic Physical and Chemical Properties

Physical State	Liquid
Appearance	Colorless
Odor	Solvent
Odor Threshold	No data available
pH	No data available
Evaporation Rate	No data available
Melting Point	No data available
Freezing Point	No data available
Boiling Point	140 °C (284 °F)
Flash Point	27 °C (81 °F)
Auto-ignition Temperature	No data available
Decomposition Temperature	No data available
Flammability (solid, gas)	Not applicable
Vapor Pressure	No data available
Relative Vapor Density at 20°C	No data available
Relative Density	< 1 (water = 1)
Specific Gravity	No data available
Solubility	No data available
Partition Coefficient n-Octanol/Water	No data available
Viscosity	No data available

9.2. Other Information

VOC Content 60 – 80 %

SECTION 10: Stability and Reactivity

10.1. Reactivity

Contact with water, alcohols, acids or bases, and many metals or metallic compounds can liberate flammable Hydrogen gas which can form explosive mixtures in air. Reacts violently with strong oxidizers. Increased risk of fire or explosion.

10.2. Chemical Stability

Flammable liquid and vapor. May form flammable or explosive vapor-air mixture.

10.3. Possibility of Hazardous Reactions

Evolved hydrogen gas is flammable and may form explosive mixtures with air. Hazardous polymerization will not occur.

10.4. Conditions to Avoid

Direct sunlight, extremely high or low temperatures, heat, hot surfaces, sparks, open flames, incompatible materials, and other ignition sources.

10.5. Incompatible Materials

Alcohols. Metals. Strong acids, strong bases, strong oxidisers. Water.

10.6. Hazardous Decomposition Products

May produce explosive hydrogen gas on contact with incompatibilities or upon thermal decomposition. Thermal decomposition may produce: Carbon oxides (CO, CO₂). Silicon oxides. Will decompose above 150 °C (>300° F) releasing formaldehyde vapors. Formaldehyde is a potential carcinogen and can act as a potential skin and respiratory sensitizer. Formaldehyde can also cause respiratory and eye irritation.

MED10-6400 Part B

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 11: Toxicological Information

11.1. Information on Toxicological Effects

Acute Toxicity (Oral)	Not classified
Acute Toxicity (Dermal)	Harmful in contact with skin.
Acute Toxicity (Inhalation)	Harmful if inhaled.

MED10-6400 Part B	
ATE (Dermal)	1,375.00 mg/kg body weight
ATE (Vapors)	13.70 mg/l/4h

Xylenes (o-, m-, p- isomers) (1330-20-7)	
LD50 Oral Rat	3523 mg/kg
LC50 Inhalation Rat	6247 ppm/4h (species: Sprague-Dawley)
ATE (Dermal)	1,100.00 mg/kg body weight
ATE (Vapors)	11.00 mg/l/4h

3-Butyn-2-ol, 2-methyl- (115-19-5)	
LD50 Oral Rat	1950 mg/kg (Source: NLM_CIP)
LD50 Dermal Rat	> 2000 mg/kg (no deaths)
LC50 Inhalation Rat	> 21300 mg/m ³ (Exposure time: 4 h Source: OECD_SIDS)

Octamethylcyclotetrasiloxane (556-67-2)	
LD50 Oral Rat	> 4800 mg/kg (No mortality)
LD50 Dermal Rat	> 2375 mg/kg (Source: ECHA)
LD50 Dermal Rabbit	> 2.5 ml/kg (No mortality)
LC50 Inhalation Rat	36 mg/l/4h

Skin Corrosion/Irritation	Causes skin irritation.
Serious Eye Damage/Irritation	Causes serious eye irritation.
Respiratory or Skin Sensitization	Not classified
Germ Cell Mutagenicity	Not classified
Carcinogenicity	Not classified

Xylenes (o-, m-, p- isomers) (1330-20-7)	
IARC Group	3

Reproductive Toxicity	Suspected of damaging fertility or the unborn child.
Specific Target Organ Toxicity (Single Exposure)	May cause respiratory irritation.
Specific Target Organ Toxicity (Repeated Exposure)	May cause damage to organs (central nervous system, hearing organs, liver) through prolonged or repeated exposure.
Aspiration Hazard	May be fatal if swallowed and enters airways.
Symptoms/Injuries After Inhalation	Inhalation is likely to cause adverse health effects including but not limited to: irritation, difficulty breathing, and unconsciousness.
Symptoms/Injuries After Skin Contact	Redness, pain, swelling, itching, burning, dryness, and dermatitis. This material is harmful through skin contact, and can cause adverse health effects or death in significant amounts. This material may be absorbed through the skin and eyes.

MED10-6400 Part B

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Symptoms/Injuries After Eye Contact	Contact causes severe irritation with redness and swelling of the conjunctiva.
Symptoms/Injuries After Ingestion	Aspiration into the lungs can occur during ingestion or vomiting and may cause lung injury.
Chronic Symptoms	May cause damage to organs through prolonged or repeated exposure. Suspected of damaging fertility or the unborn child.

SECTION 12: Ecological Information

12.1. Toxicity

Ecology - General Toxic to aquatic life. Harmful to aquatic life with long lasting effects.

Xylenes (o-, m-, p- isomers) (1330-20-7)	
LC50 Fish 1	3.3 mg/l
EC50 - Crustacea [1]	3.82 mg/l (Exposure time: 48 h - Species: water flea)
LC50 Fish 2	2.661 (2.661 – 4.093) mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [static])
3-Butyn-2-ol, 2-methyl- (115-19-5)	
LC50 Fish 1	3120 (3120 – 3480) mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
EC50 - Crustacea [1]	500 mg/l (Exposure time: 48 h - Species: Daphnia magna)
EC50 Other Aquatic Organisms 1	500 mg/l (Exposure time: 72 h - Species: Desmodesmus subspicatus)
LC50 Fish 2	2200 (2200 – 4600) mg/l (Exposure time: 96 h - Species: Leuciscus idus [static])
EC50 Other Aquatic Organisms 2	500 mg/l (Exposure time: 96 h - Species: Desmodesmus subspicatus)
Octamethylcyclotetrasiloxane (556-67-2)	
LC50 Fish 1	> 22 µg/l
NOEC Chronic Fish	0.0044 mg/l

12.2. Persistence and Degradability

MED10-6400 Part B	
Persistence and Degradability	May cause long-term adverse effects in the environment.

12.3. Bioaccumulative Potential

MED10-6400 Part B	
Bioaccumulative Potential	Not established.
Xylenes (o-, m-, p- isomers) (1330-20-7)	
BCF Fish 1	0.6 (0.6 – 15)
Partition coefficient n-octanol/water (Log Pow)	2.77 – 3.15
3-Butyn-2-ol, 2-methyl- (115-19-5)	
Partition coefficient n-octanol/water (Log Pow)	0.318 (at 25 °C)
Octamethylcyclotetrasiloxane (556-67-2)	
BCF Fish 1	(12400 dimensionless)
Partition coefficient n-octanol/water (Log Pow)	6.488 (at 25.1 °C)

MED10-6400 Part B

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

12.4. Mobility In Soil

No additional information available

12.5. Other Adverse Effects

Other Information Avoid release to the environment.

SECTION 13: Disposal Considerations

13.1. Waste Treatment Methods

Waste Disposal	Dispose of contents/container in accordance with local, regional, national, and international regulations.
Recommendations	
Additional Information	Handle empty containers with care because residual vapors are flammable.
Ecology - Waste Materials	Avoid release to the environment. This material is hazardous to the aquatic environment. Keep out of sewers and waterways.

SECTION 14: Transport Information

The shipping description(s) stated herein were prepared in accordance with certain assumptions at the time the SDS was authored, and can vary based on a number of variables that may or may not have been known at the time the SDS was issued.

14.1. In Accordance with DOT

Proper Shipping Name	XYLENES SOLUTION
Hazard Class	3
Identification Number	UN1307
Label Codes	3
Packing Group	III
ERG Number	128



14.2. In Accordance with IMDG

Proper Shipping Name	XYLENES SOLUTION
Hazard Class	3
Identification Number	UN1307
Packing Group	III
Label Codes	3
EmS-No. (Fire)	F-E
EmS-No. (Spillage)	S-D
MFAG Number	130



14.3. In Accordance with IATA

Proper Shipping Name	XYLENES SOLUTION
Packing Group	III
Identification Number	UN1307
Hazard Class	3
Label Codes	3
ERG Code (IATA)	3L



MED10-6400 Part B

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 15: Regulatory Information

15.1. US Federal Regulations

All components in this mixture are listed on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory, have been exempted, are not listed, not disclosed due to CBI requirements or disclosure rules according to the relevant regulation.

MED10-6400 Part B	
SARA Section 311/312 Hazard Classes	Health hazard - Specific target organ toxicity (single or repeated exposure) Health hazard - Reproductive toxicity Health hazard - Skin corrosion or Irritation Physical hazard - Flammable (gases, aerosols, liquids, or solids) Health hazard - Serious eye damage or eye irritation Health hazard - Acute toxicity (any route of exposure) Health hazard - Aspiration hazard
Xylenes (o-, m-, p- isomers) (1330-20-7)	
Subject to reporting requirements of United States SARA Section 313	
CERCLA RQ	100 lb
SARA Section 313 - Emission Reporting	1 %

15.2. US State Regulations

Xylenes (o-, m-, p- isomers) (1330-20-7)	
U.S. - California - Proposition 65 - Carcinogens List	WARNING: This product contains chemicals known to the State of California to cause cancer.

Xylenes (o-, m-, p- isomers) (1330-20-7)	
U.S. - California - SCAQMD - Toxic Air Contaminants - Non-Cancer Acute U.S. - California - SCAQMD - Toxic Air Contaminants - Non-Cancer Chronic U.S. - California - Toxic Air Contaminant List (AB 1807, AB 2728) U.S. - Colorado - Groundwater Quality Standards U.S. - Colorado - Hazardous Wastes - Discarded Chemical Products, Off-Specification Species, Container and Spill Residues U.S. - Colorado - Primary Drinking Water Regulations - Maximum Contaminant Level Goals (MCLGs) U.S. - Colorado - Primary Drinking Water Regulations - Maximum Contaminant Levels (MCLs) U.S. - Connecticut - Drinking Water Quality Standards - Maximum Contaminant Levels U.S. - Delaware - Pollutant Discharge Requirements - Reportable Quantities U.S. - Florida - Drinking Water Standards - Volatile Organic Contaminants - Maximum Contaminant Levels (MCLs) U.S. - Georgia - Drinking Water - Maximum Contaminant Levels (MCLs) U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Acceptable Ambient Concentrations U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Emission Levels (ELs) U.S. - Idaho - Occupational Exposure Limits - TWAs	

MED10-6400 Part B

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

U.S. - Illinois - Toxic Air Contaminants
U.S. - Louisiana - Reportable Quantity List for Pollutants
U.S. - Maine - Air Pollutants - Hazardous Air Pollutants
U.S. - Massachusetts - Allowable Ambient Limits (AALs)
U.S. - Massachusetts - Allowable Threshold Concentrations (ATCs)
U.S. - Massachusetts - Drinking Water - Maximum Contaminant Levels (MCLs)
U.S. - Massachusetts - Oil & Hazardous Material List - Groundwater Reportable Concentration - Reporting Category 1
U.S. - Massachusetts - Oil & Hazardous Material List - Groundwater Reportable Concentration - Reporting Category 2
U.S. - Massachusetts - Oil & Hazardous Material List - Reportable Quantity
U.S. - Massachusetts - Oil & Hazardous Material List - Soil Reportable Concentration - Reporting Category 1
U.S. - Massachusetts - Oil & Hazardous Material List - Soil Reportable Concentration - Reporting Category 2
RTK - U.S. - Massachusetts - Right To Know List
U.S. - Massachusetts - Threshold Effects Exposure Limits (TEELs)
U.S. - Massachusetts - Toxics Use Reduction Act
U.S. - Michigan - Occupational Exposure Limits - STELs
U.S. - Michigan - Occupational Exposure Limits - TWAs
U.S. - Michigan - Polluting Materials List
U.S. - Minnesota - Chemicals of High Concern
U.S. - Minnesota - Groundwater Health Risk Limits
U.S. - Minnesota - Hazardous Substance List
U.S. - Minnesota - Permissible Exposure Limits - STELs
U.S. - Minnesota - Permissible Exposure Limits - TWAs
U.S. - Missouri - Drinking Water - Maximum Contaminant Levels (MCLs)
U.S. - Nebraska - Drinking Water - Maximum Contaminant Levels (MCLs)
U.S. - New Hampshire - Drinking Water - Maximum Contaminant Levels (MCLs)
U.S. - New Hampshire - Regulated Toxic Air Pollutants - Ambient Air Levels (AALs) - 24-Hour
U.S. - New Hampshire - Regulated Toxic Air Pollutants - Ambient Air Levels (AALs) - Annual
U.S. - New Jersey - Discharge Prevention - List of Hazardous Substances
U.S. - New Jersey - Environmental Hazardous Substances List
U.S. - New Jersey - Primary Drinking Water Standards - Maximum Contaminant Levels - MCLs
RTK - U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - New Jersey - Special Health Hazards Substances List
U.S. - New Jersey - Water Quality - Ground Water Quality Criteria
U.S. - New Jersey - Water Quality - Practical Quantitation Levels (PQLs)
U.S. - New Mexico - Water Quality - Standards for Ground Water of 10,000 mg/L TDS Concentration or Less
U.S. - New York - Occupational Exposure Limits - TWAs
U.S. - New York - Reporting of Releases Part 597 - List of Hazardous Substances
U.S. - North Carolina - Control of Toxic Air Pollutants
U.S. - North Dakota - Air Pollutants - Guideline Concentrations - 1-Hour
U.S. - North Dakota - Air Pollutants - Guideline Concentrations - 8-Hour
U.S. - North Dakota - Hazardous Wastes - Discarded Chemical Products, Off-Specification Species, Container and Spill Residues

MED10-6400 Part B

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

U.S. - North Dakota - Water Quality Standards - Human Health Value for Classes I, IA, II
U.S. - Oregon - Permissible Exposure Limits - TWAs
U.S. - California - Safer Consumer Products - Initial List of Candidate Chemicals and Chemical Groups
U.S. - Pennsylvania - Drinking Water - Maximum Contaminant Levels (MCLs)
RTK - U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List
RTK - U.S. - Pennsylvania - RTK (Right to Know) List
U.S. - Rhode Island - Air Toxics - Acceptable Ambient Levels - 1-Hour
U.S. - Rhode Island - Air Toxics - Acceptable Ambient Levels - 24-Hour
U.S. - Rhode Island - Air Toxics - Acceptable Ambient Levels - Annual
U.S. - Rhode Island - Water Quality Standards - Acute Freshwater Aquatic Life Criteria
All concentrations are expressed as percentages by weight unless the ingredient is a gas.
U.S. - South Carolina - Maximum Contaminant Levels (MCLs)
U.S. - South Carolina - Toxic Air Pollutants - Maximum Allowable Concentrations
U.S. - South Carolina - Toxic Air Pollutants - Pollutant Categories
U.S. - Tennessee - Occupational Exposure Limits - STELs
U.S. - Tennessee - Occupational Exposure Limits - TWAs
U.S. - Texas - City of Austin - Aerosol Paint and Glue Restrictions
U.S. - Texas - Drinking Water Standards - Maximum Contaminant Levels (MCLs)
U.S. - Texas - Effects Screening Levels - Long Term
U.S. - Texas - Effects Screening Levels - Short Term
U.S. - Utah - Drinking Water - Maximum Contaminant Levels (MCLs)
U.S. - Washington - Dangerous Waste - Discarded Chemical Products List
U.S. - Washington - Permissible Exposure Limits - STELs
U.S. - Washington - Permissible Exposure Limits - TWAs
U.S. - West Virginia - Water Quality - Groundwater Standards - Ceiling Concentrations
U.S. - Wisconsin - Hazardous Air Contaminants - All Sources - Emissions From Stack Heights 25 Feet to Less Than 40 Feet
U.S. - Wisconsin - Hazardous Air Contaminants - All Sources - Emissions From Stack Heights 40 Feet to Less Than 75 Feet
U.S. - Wisconsin - Hazardous Air Contaminants - All Sources - Emissions From Stack Heights 75 Feet or Greater
U.S. - Wisconsin - Hazardous Air Contaminants - All Sources - Emissions From Stack Heights Less Than 25 Feet

Siloxanes and Silicones, dimethyl, methyl hydrogen (68037-59-2)

U.S. - Texas - Effects Screening Levels - Long Term

U.S. - Texas - Effects Screening Levels - Short Term

3-Butyn-2-ol, 2-methyl- (115-19-5)

RTK - U.S. - New Jersey - Right to Know Hazardous Substance List

RTK - U.S. - Pennsylvania - RTK (Right to Know) List

RTK - U.S. - Massachusetts - Right To Know List

U.S. - New Jersey - Special Health Hazards Substances List

U.S. - Texas - Effects Screening Levels - Long Term

U.S. - Texas - Effects Screening Levels - Short Term

Silanamine, 1,1,1-trimethyl-N-(trimethylsilyl)-, hydrolysis products with silica (68909-20-6)

U.S. - Texas - Effects Screening Levels - Long Term

U.S. - Texas - Effects Screening Levels - Short Term

Octamethylcyclotetrasiloxane (556-67-2)

MED10-6400 Part B

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

U.S. - Texas - Effects Screening Levels - Long Term
U.S. - Texas - Effects Screening Levels - Short Term
U.S. - Maine - Chemicals of Concern
U.S. - Oregon - Priority Persistent Pollutant - Tier I - Persistent Pollutants
U.S. - Minnesota - Chemicals of High Concern
U.S. - Minnesota - Chemicals of High Concern - Persistent Bioaccumulative Toxins
U.S. - California - Safer Consumer Products - Initial List of Candidate Chemicals and Chemical Groups

SECTION 16: Other Information, Including Date of Preparation or Last Revision

Date of Preparation or Latest Revision 05/29/2024

Revision

Other Information

This document has been prepared in accordance with the SDS requirements of the OSHA Hazard Communication Standard 29 CFR 1910.1200.

GHS Full Text Phrases:

H225	Highly flammable liquid and vapor
H226	Flammable liquid and vapor
H302	Harmful if swallowed
H304	May be fatal if swallowed and enters airways
H312	Harmful in contact with skin
H315	Causes skin irritation
H318	Causes serious eye damage
H319	Causes serious eye irritation
H332	Harmful if inhaled
H335	May cause respiratory irritation
H336	May cause drowsiness or dizziness
H361	Suspected of damaging fertility or the unborn child
H373	May cause damage to organs through prolonged or repeated exposure
H401	Toxic to aquatic life
H410	Very toxic to aquatic life with long lasting effects
H412	Harmful to aquatic life with long lasting effects

NFPA Health Hazard

3 - Materials that, under emergency conditions, can cause serious or permanent injury.

NFPA Fire Hazard

3 - Liquids and solids (including finely divided suspended solids) that can be ignited under almost all ambient temperature conditions.


NFPA Reactivity Hazard

0 - Material that in themselves are normally stable, even under fire conditions.

HMIS III Rating
Health

3 Serious Hazard

* Chronic - Chronic (long-term) health effects may result from repeated overexposure



MED10-6400 Part B

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Flammability
Physical

3 Serious Hazard
0 Minimal Hazard

The information provided in this Safety Data Sheet (SDS) was prepared based on data believed to be accurate as of the date of this SDS. TO THE GREATEST EXTENT PERMITTED BY LAW, NUSIL TECHNOLOGY LLC AND ITS AFFILIATED COMPANIES ("NUSIL") EXPRESSLY DISCLAIMS ANY AND ALL REPRESENTATIONS AND WARRANTIES REGARDING THE INFORMATION CONTAINED HEREIN INCLUDING, WITHOUT LIMITATION, AS TO ACCURACY, COMPLETENESS, FITNESS FOR PURPOSE OR USE, MERCHANTABILITY, NON-INFRINGEMENT, PERFORMANCE, SAFETY, SUITABILITY AND STABILITY. This SDS is intended as a guide to the appropriate use, handling, storage and disposal of the product to which it relates by properly trained personnel, and is not intended to be comprehensive. Users of NuSil's products are advised to perform their own tests and to exercise their own judgment to determine the safety, suitability and appropriate use, handling, storage and disposal of each product and product combination for their own purposes and uses. TO THE GREATEST EXTENT PERMITTED BY LAW, NUSIL DISCLAIMS LIABILITY FOR, AND BY USING NUSIL'S PRODUCTS PURCHASER AGREES THAT UNDER NO CIRCUMSTANCES SHALL NUSIL BE LIABLE FOR, SPECIAL, INDIRECT, INCIDENTAL, PUNITIVE OR CONSEQUENTIAL DAMAGES OF ANY TYPE OR KIND, INCLUDING WITHOUT LIMITATION, FOR LOSS OF PROFITS, REPUTATIONAL DAMAGE, PRODUCT RECALL OR BUSINESS INTERRUPTION.

Nusil US GHS SDS