

MED-1011

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations
Revision Date: 01/30/2023 Date of Issue: 09/06/2012

SECTION 1: Identification

1.1. Product Identifier

Product Form Mixture
Product Name MED-1011
Synonyms Silicone Adhesive

1.2. Relevant Identified Uses of the Substance or Mixture and Uses Advised Against

Use of the Substance/Mixture For professional use only.

1.3. Details of the Supplier of the Safety Data Sheet

NuSil Technology LLC
1050 Cindy Lane
Carpinteria, California 93013
USA
(805) 684-8780
productstewardship@avantorsciencesgcc.com
www.nusil.com

1.4. Emergency Telephone Number

Emergency Number 800-424-9300 CHEMTREC (in US); +1 703-527-3887 CHEMTREC (International and Maritime)

SECTION 2: Hazards Identification

2.1. Classification of the Substance or Mixture

GHS-US Classification

Skin corrosion/irritation Category 1B H314
Serious eye damage/eye irritation Category 1 H318
Reproductive toxicity Category 2 H361
Hazardous to the aquatic environment - Chronic Hazard Category 3 H412

2.2. Label Elements

GHS-US Labeling

Hazard Pictograms (GHS-US)



GHS05 GHS08

Signal Word (GHS-US)

Danger

Hazard Statements (GHS-US)

H314 - Causes severe skin burns and eye damage
H318 - Causes serious eye damage
H361 - Suspected of damaging fertility or the unborn child
H412 - Harmful to aquatic life with long lasting effects
P201 - Obtain special instructions before use.
P202 - Do not handle until all safety precautions have been read and understood.
P260 - Do not breathe vapors, mist, or spray.
P264 - Wash hands, forearms, and other exposed areas thoroughly after handling.
P273 - Avoid release to the environment.
P280 - Wear protective gloves, protective clothing, and eye

MED-1011

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

protection.

P301+P330+P331 - If swallowed: rinse mouth. Do NOT induce vomiting.

P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P304+P340 - If inhaled: Remove person to fresh air and keep at rest in a position comfortable for breathing.

P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310 - Immediately call a poison center or doctor.

P321 - Specific treatment (see section 4 on this SDS).

P363 - Wash contaminated clothing before reuse.

P405 - Store locked up.

P501 - Dispose of contents/container in accordance with local, regional, national, and international regulations.

2.3. Other Hazards

Other Hazards Not Contributing to the Classification Exposure may aggravate pre-existing eye, skin, or respiratory conditions.

2.4. Unknown Acute Toxicity (GHS-US)

10 - 30% of the mixture consists of ingredients of unknown acute toxicity.

SECTION 3: Composition/Information On Ingredients

3.1. Substances

Not applicable

3.2. Mixtures

| Name | Product Identifier | %* | GHS-US Classification |
|--|----------------------|-----------|--|
| Silanamine, 1,1,1-trimethyl-N-(trimethylsilyl)-, hydrolysis products with silica | (CAS-No.) 68909-20-6 | 10 - 30 | Not classified |
| Silanetriol, ethyl-, triacetate | (CAS-No.) 17689-77-9 | 5 - 10 | Acute Tox. 4 (Oral), H302 Skin Corr. 1B, H314 Eye Dam. 1, H318 |
| Glycidoxypropyltrimethoxysilane | (CAS-No.) 2530-83-8 | 0.5 - 1.5 | Eye Dam. 1, H318 Aquatic Acute 3, H402 Aquatic Chronic 3, H412 |
| Octamethylcyclotetrasiloxane | (CAS-No.) 556-67-2 | < 0.25 | Flam. Liq. 3, H226 Repr. 2, H361 Aquatic Chronic 1, H410 |
| Dibutyltin diacetate | (CAS-No.) 1067-33-0 | < 0.1 | Skin Corr. 1B, H314 Eye Dam. 1, H318 Skin Sens. 1B, H317 Muta. 2, H341 Repr. 1B, H360 STOT SE 1, H370 STOT RE 1, H372 Aquatic Chronic 1, H410 |

Full text of H-phrases: see section 16

MED-1011

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

* The specific chemical identity and/or exact percentage of composition have been withheld as a trade secret [29 CFR 1910.1200].

SECTION 4: First Aid Measures

4.1. Description of First-aid Measures

| | |
|---------------------------------------|---|
| First-aid Measures General | Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible). |
| First-aid Measures After Inhalation | Remove to fresh air and keep at rest in a position comfortable for breathing. Immediately call a poison center or doctor/physician. |
| First-aid Measures After Skin Contact | Immediately remove contaminated clothing. Immediately flush skin with plenty of water for at least 30 minutes. Get immediate medical advice/attention. |
| First-aid Measures After Eye Contact | Immediately rinse with water for at least 30 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get immediate medical advice/attention. |
| First-aid Measures After Ingestion | Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention. |

4.2. Most Important Symptoms and Effects Both Acute and Delayed

| | |
|--------------------------------------|--|
| Symptoms/Injuries | Causes severe skin burns and eye damage. Suspected of damaging fertility. |
| Symptoms/Injuries After Inhalation | Prolonged exposure may cause irritation. |
| Symptoms/Injuries After Skin Contact | Causes severe irritation which will progress to chemical burns. |
| Symptoms/Injuries After Eye Contact | Causes permanent damage to the cornea, iris, or conjunctiva. |
| Symptoms/Injuries After Ingestion | May cause burns or irritation of the linings of the mouth, throat, and gastrointestinal tract. |
| Chronic Symptoms | Suspected of damaging fertility. |

4.3. Indication of Any Immediate Medical Attention and Special Treatment Needed

If exposed or concerned, get medical advice and attention. If medical advice is needed, have product container or label at hand.

SECTION 5: Fire-Fighting Measures

5.1. Extinguishing Media

| | |
|--------------------------------|---|
| Suitable Extinguishing Media | : Carbon dioxide, dry chemical, alcohol foam. |
| Unsuitable Extinguishing Media | : Reacts with water to form methanol and acetic acid. |

5.2. Special Hazards Arising From the Substance or Mixture

| | |
|------------------|---|
| Fire Hazard | Not considered flammable but may burn at high temperatures. |
| Explosion Hazard | Product is not explosive. |
| Reactivity | Reacts with water to form methanol. Reacts with water, alcohols or bases to form acetic acid. |

5.3. Advice for Firefighters

| | |
|-----------------------------|--|
| Precautionary Measures Fire | Exercise caution when fighting any chemical fire. |
| Firefighting Instructions | Use water spray or fog for cooling exposed containers. |

MED-1011

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

| | |
|--------------------------------|---|
| Protection During Firefighting | Do not enter fire area without proper protective equipment, including respiratory protection. |
| Hazardous Combustion Products | Carbon oxides (CO, CO ₂). Silicon oxides. Tin oxides. Formaldehyde. |
| Other Information | Do not allow run-off from fire fighting to enter drains or water courses. |

SECTION 6: Accidental Release Measures

6.1. Personal Precautions, Protective Equipment And Emergency Procedures

General Measures Do not get in eyes, on skin, or on clothing. Do not breathe vapor, mist or spray.

6.1.1. For Non-Emergency Personnel

Protective Equipment Use appropriate personal protective equipment (PPE).
Emergency Procedures Evacuate unnecessary personnel.

6.1.2. For emergency responders

Protective Equipment Equip cleanup crew with proper protection.
Emergency Procedures Upon arrival at the scene, a first responder is expected to recognize the presence of dangerous goods, protect oneself and the public, secure the area, and call for the assistance of trained personnel as soon as conditions permit. Ventilate area.

6.2. Environmental Precautions

Prevent entry to sewers and public waters. Avoid release to the environment.

6.3. Methods and Materials for Containment and Cleaning Up

For Containment As an immediate precautionary measure, isolate spill or leak area in all directions. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.
Methods for Cleaning Up Clean up spills immediately and dispose of waste safely. Transfer spilled material to a suitable container for disposal. Absorb and/or contain spill with inert material. Contact competent authorities after a spill.

6.4. Reference to Other Sections

See Section 8 for exposure controls and personal protection and Section 13 for disposal considerations.

SECTION 7: Handling And Storage

7.1. Precautions for Safe Handling

Additional Hazards When Processed Will decompose above 150 °C (> 300 °F) releasing formaldehyde vapors. Reacts with water to form methanol and acetic acid.
Precautions for Safe Handling Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not breathe vapors, mist, spray. Do not get in eyes, on skin, or on clothing. Handle empty containers with care because they may still present a hazard. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.
Hygiene Measures Handle in accordance with good industrial hygiene and safety procedures.

MED-1011

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

7.2. Conditions for Safe Storage, Including Any Incompatibilities

Technical Measures

Comply with applicable regulations.

Storage Conditions

Keep container closed when not in use. Store in a dry, cool place. Keep/Store away from direct sunlight, extremely high or low temperatures and incompatible materials. Store locked up/in a secure area. Store in original container or corrosive resistant and/or lined container.

Incompatible Materials

Strong acids, strong bases, strong oxidizers. Water. Alcohols.

7.3. Specific End Use(S)

For bonding silicone elastomers to each other and some synthetics and metals. For professional use only.

SECTION 8: Exposure Controls/Personal Protection

8.1. Control Parameters

For substances listed in section 3 that are not listed here, there are no established exposure limits from the manufacturer, supplier, importer, or the appropriate advisory agency including: ACGIH (TLV), or OSHA (PEL).

| Silanamine, 1,1,1-trimethyl-N-(trimethylsilyl)-, hydrolysis products with silica (68909-20-6) | | |
|---|-------------------------|--|
| USA OSHA | OSHA PEL (TWA) [1] | 6 mg/m ³ |
| USA OSHA | OSHA PEL (TWA) [2] | 20 mppcf (80mg/m ³ /%SiO ₂) |
| Tin organic compounds | | |
| USA ACGIH | ACGIH OEL TWA | 0.1 mg/m ³ |
| USA ACGIH | ACGIH OEL STEL | 0.2 mg/m ³ |
| USA ACGIH | ACGIH chemical category | Not Classifiable as a Human Carcinogen, Skin - potential significant contribution to overall exposure by the cutaneous route |
| USA NIOSH | NIOSH REL (TWA) | 0.1 mg/m ³ (except Cyhexatin) |
| USA OSHA | OSHA PEL (TWA) [1] | 0.1 mg/m ³ |

8.2. Exposure Controls

Appropriate Engineering Controls

Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Ensure adequate ventilation, especially in confined areas. Ensure all national/local regulations are observed.

Personal Protective Equipment

Gloves. Protective clothing. Protective goggles. Insufficient ventilation: wear respiratory protection. Face shield.



Materials For Protective Clothing

Chemically resistant materials and fabrics. Corrosion-proof clothing.

Hand Protection

Wear protective gloves.

Eye And Face Protection

Chemical safety goggles and face shield.

Skin And Body Protection

Wear suitable protective clothing.

MED-1011

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Respiratory Protection

If exposure limits are exceeded or irritation is experienced, approved respiratory protection should be worn. In case of inadequate ventilation, oxygen deficient atmosphere, or where exposure levels are not known wear approved respiratory protection.

Other Information

When using, do not eat, drink or smoke.

SECTION 9: Physical and Chemical Properties

9.1. Information on Basic Physical and Chemical Properties

| | |
|---------------------------------------|-------------------|
| Physical State | Liquid |
| Appearance | Colorless |
| Odor | Odorless |
| Odor Threshold | No data available |
| pH | No data available |
| Evaporation Rate | No data available |
| Melting Point | No data available |
| Freezing Point | No data available |
| Boiling Point | No data available |
| Flash Point | > 135 °C (275 °F) |
| Auto-ignition Temperature | No data available |
| Decomposition Temperature | No data available |
| Flammability (solid, gas) | Not applicable |
| Vapor Pressure | No data available |
| Relative Vapor Density at 20°C | No data available |
| Relative Density | No data available |
| Specific Gravity | 1.12 |
| Solubility | No data available |
| Partition Coefficient n-Octanol/Water | No data available |
| Viscosity | No data available |

9.2. Other Information

VOC Content < 1 %

SECTION 10: Stability and Reactivity

10.1. Reactivity

Reacts with water to form methanol. Reacts with water, alcohols or bases to form acetic acid.

10.2. Chemical Stability

Stable under recommended handling and storage conditions (see section 7).

10.3. Possibility of Hazardous Reactions

Hazardous polymerization will not occur.

10.4. Conditions to Avoid

Direct sunlight, extremely high or low temperatures, and incompatible materials.

10.5. Incompatible Materials

Strong acids, strong bases, strong oxidizers. Water. Alcohols.

MED-1011

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

10.6. Hazardous Decomposition Products

Thermal decomposition may produce: Carbon oxides (CO, CO₂). Silicon oxides. Tin oxides. Will decompose above 150 °C (>300° F) releasing formaldehyde vapors. Formaldehyde is a potential carcinogen and can act as a potential skin and respiratory sensitizer. Formaldehyde can also cause respiratory and eye irritation. From hydrolysis: acetic acid, methanol.

SECTION 11: Toxicological Information

11.1. Information on Toxicological Effects

Acute Toxicity (Oral) Not classified

Acute Toxicity (Dermal) Not classified

Acute Toxicity (Inhalation) Not classified

| Silanetriol, ethyl-, triacetate (17689-77-9) | |
|--|------------|
| LD50 Oral Rat | 1460 mg/kg |

| Glycidoxypropyltrimethoxysilane (2530-83-8) | |
|---|---------------|
| LD50 Oral Rat | 8025 mg/kg |
| LD50 Dermal Rabbit | 4250 mg/kg |
| LC50 Inhalation Rat | > 5.3 mg/l/4h |

| Octamethylcyclotetrasiloxane (556-67-2) | |
|---|-----------------------------|
| LD50 Oral Rat | > 4800 mg/kg (No mortality) |
| LD50 Dermal Rabbit | > 2.5 ml/kg (No mortality) |
| LC50 Inhalation Rat | 36 mg/l/4h |

| | |
|--|--|
| Skin Corrosion/Irritation | Causes severe skin burns. |
| Serious Eye Damage/Irritation | Causes serious eye damage. |
| Respiratory or Skin Sensitization | Not classified |
| Germ Cell Mutagenicity | Not classified |
| Carcinogenicity | Not classified |
| Reproductive Toxicity | Suspected of damaging fertility. |
| Specific Target Organ Toxicity (Single Exposure) | Not classified |
| Specific Target Organ Toxicity (Repeated Exposure) | Not classified |
| Aspiration Hazard | Not classified |
| Symptoms/Injuries After Inhalation | Prolonged exposure may cause irritation. |
| Symptoms/Injuries After Skin Contact | Causes severe irritation which will progress to chemical burns. |
| Symptoms/Injuries After Eye Contact | Causes permanent damage to the cornea, iris, or conjunctiva. |
| Symptoms/Injuries After Ingestion | May cause burns or irritation of the linings of the mouth, throat, and gastrointestinal tract. |
| Chronic Symptoms | Suspected of damaging fertility. |

MED-1011

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 12: Ecological Information

12.1. Toxicity

Ecology - General

Harmful to aquatic life with long lasting effects.

| | |
|---|---|
| Glycidoxypropyltrimethoxysilane (2530-83-8) | |
| LC50 Fish 1 | 55 mg/l (Exposure time: 96 h - Species: Cyprinus carpio) |
| EC50 - Crustacea [1] | 710 mg/l (Exposure time: 48 h - Species: Daphnia magna) |
| ErC50 (Algae) | 350 mg/l Exposure time: 96 h - Species: Pseudokirchnerella subcapitata) |
| NOEC Chronic Crustacea | 100 mg/l |
| Dibutyltin diacetate (1067-33-0) | |
| EC50 Chronic | 0.035 mg/l Exposure time: 72 hour (Species: Skeletonema costatum) |
| NOEC (Acute) | 0.65 mg/l |
| NOEC Chronic Crustacea | 0.32 mg/l (48-Hour EC50 Daphnia magna) |
| Octamethylcyclotetrasiloxane (556-67-2) | |
| LC50 Fish 1 | > 22 µg/l |
| NOEC Chronic Fish | 0.0044 mg/l |

12.2. Persistence and Degradability

| | |
|-------------------------------|---|
| MED-1011 | |
| Persistence and Degradability | May cause long-term adverse effects in the environment. |

12.3. Bioaccumulative Potential

| | |
|---|-------------------------|
| MED-1011 | |
| Bioaccumulative Potential | Not established. |
| Dibutyltin diacetate (1067-33-0) | |
| Partition coefficient n-octanol/water (Log Pow) | 3.39 at 20 °C (at pH 5) |
| Octamethylcyclotetrasiloxane (556-67-2) | |
| BCF Fish 1 | 12400 (dimensionless) |
| Partition coefficient n-octanol/water (Log Pow) | 6.488 (at 25.1 °C) |

12.4. Mobility In Soil

No additional information available

12.5. Other Adverse Effects

Other Information

Avoid release to the environment.

SECTION 13: Disposal Considerations

13.1. Waste Treatment Methods

Waste Disposal

Recommendations

Additional Information

Ecology - Waste Materials

Dispose of contents/container in accordance with local, regional, national, and international regulations.

Container may remain hazardous when empty. Continue to observe all precautions.

Avoid release to the environment. This material is hazardous to the aquatic environment. Keep out of sewers and waterways.

MED-1011

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 14: Transport Information

The shipping description(s) stated herein were prepared in accordance with certain assumptions at the time the SDS was authored, and can vary based on a number of variables that may or may not have been known at the time the SDS was issued.

14.1. In Accordance with DOT

Proper Shipping Name CORROSIVE LIQUIDS, N.O.S. (Silanetriol, ethyl-, triacetate)
Hazard Class 8
Identification Number UN1760
Label Codes 8
Packing Group II
ERG Number 154



14.2. In Accordance with IMDG

Proper Shipping Name CORROSIVE LIQUID, N.O.S. (Silanetriol, ethyl-, triacetate)
Hazard Class 8
Identification Number UN1760
Packing Group II
Label Codes 8
EmS-No. (Fire) F-A
EmS-No. (Spillage) S-B



14.3. In Accordance with IATA

Proper Shipping Name CORROSIVE LIQUID, N.O.S. (Silanetriol, ethyl-, triacetate)
Packing Group II
Identification Number UN1760
Hazard Class 8
Label Codes 8
ERG Code (IATA) 8L



SECTION 15: Regulatory Information

15.1. US Federal Regulations

All components in this mixture are listed on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory, have been exempted, are not listed, not disclosed due to CBI requirements or disclosure rules according to the relevant regulation.

| | |
|-------------------------------------|---|
| MED-1011 | |
| SARA Section 311/312 Hazard Classes | Health hazard - Serious eye damage or eye irritation Health hazard - Skin corrosion or Irritation Health hazard - Reproductive toxicity |

15.2. US State Regulations

| |
|---|
| Silanamine, 1,1,1-trimethyl-N-(trimethylsilyl)-, hydrolysis products with silica (68909-20-6) |
| U.S. - Texas - Effects Screening Levels - Long Term |
| U.S. - Texas - Effects Screening Levels - Short Term |
| Silanetriol, ethyl-, triacetate (17689-77-9) |
| U.S. - Texas - Effects Screening Levels - Long Term |
| U.S. - Texas - Effects Screening Levels - Short Term |
| Glycidoxypropyltrimethoxysilane (2530-83-8) |

MED-1011

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

| |
|---|
| U.S. - Texas - Effects Screening Levels - Long Term U.S. - Texas - Effects Screening Levels - Short Term |
| Dibutyltin diacetate (1067-33-0) |
| RTK - U.S. - Massachusetts - Right To Know List U.S. - Texas - Effects Screening Levels - Long Term U.S. - Texas - Effects Screening Levels - Short Term |
| Octamethylcyclotetrasiloxane (556-67-2) |
| U.S. - Texas - Effects Screening Levels - Long Term U.S. - Texas - Effects Screening Levels - Short Term U.S. - Maine - Chemicals of Concern U.S. - Oregon - Priority Persistent Pollutant - Tier I - Persistent Pollutants U.S. - Minnesota - Chemicals of High Concern U.S. - Minnesota - Chemicals of High Concern - Persistent Bioaccumulative Toxins U.S. - California - Safer Consumer Products - Initial List of Candidate Chemicals and Chemical Groups |
| Tin organic compounds |
| U.S. - Minnesota - Hazardous Substance List U.S. - Tennessee - Occupational Exposure Limits - TWAs U.S. - Tennessee - Occupational Exposure Limits - Skin Designations U.S. - Vermont - Permissible Exposure Limits - TWAs U.S. - Connecticut - Hazardous Air Pollutants - HLVs (8 hr) U.S. - Vermont - Permissible Exposure Limits - Skin Designations U.S. - Washington - Permissible Exposure Limits - TWAs U.S. - Connecticut - Hazardous Air Pollutants - HLVs (30 min) U.S. - Washington - Permissible Exposure Limits - STELs U.S. - Washington - Permissible Exposure Limits - Skin Designations U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Emission Levels (ELs) U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Acceptable Ambient Concentrations U.S. - New York - Occupational Exposure Limits - TWAs U.S. - New York - Occupational Exposure Limits - Skin Designations U.S. - Michigan - Occupational Exposure Limits - TWAs U.S. - Michigan - Occupational Exposure Limits - Skin Designations U.S. - Minnesota - Permissible Exposure Limits - Skin Designations U.S. - Minnesota - Permissible Exposure Limits - TWAs U.S. - Oregon - Permissible Exposure Limits - TWAs U.S. - Texas - Effects Screening Levels - Long Term U.S. - Texas - Effects Screening Levels - Short Term U.S. - Wisconsin - Hazardous Air Contaminants - All Sources - Emissions From Stack Heights 75 Feet or Greater U.S. - Wisconsin - Hazardous Air Contaminants - All Sources - Emissions From Stack Heights 40 Feet to Less Than 75 Feet U.S. - Wisconsin - Hazardous Air Contaminants - All Sources - Emissions From Stack Heights 25 Feet to Less Than 40 Feet U.S. - Wisconsin - Hazardous Air Contaminants - All Sources - Emissions From Stack Heights Less Than 25 Feet U.S. - North Dakota - Air Pollutants - Guideline Concentrations - 1-Hour U.S. - North Dakota - Air Pollutants - Guideline Concentrations - 8-Hour U.S. - New Hampshire - Regulated Toxic Air Pollutants - Ambient Air Levels (AALs) - 24-Hour U.S. - New Hampshire - Regulated Toxic Air Pollutants - Ambient Air Levels (AALs) - Annual |

MED-1011

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 16: Other Information, Including Date of Preparation or Last Revision

Date of Preparation or Latest Revision 01/30/2023

Other Information This document has been prepared in accordance with the SDS requirements of the OSHA Hazard Communication Standard 29 CFR 1910.1200.

GHS Full Text Phrases:

| | |
|------|--|
| H226 | Flammable liquid and vapor |
| H302 | Harmful if swallowed |
| H314 | Causes severe skin burns and eye damage |
| H318 | Causes serious eye damage |
| H361 | Suspected of damaging fertility or the unborn child |
| H402 | Harmful to aquatic life |
| H410 | Very toxic to aquatic life with long lasting effects |
| H412 | Harmful to aquatic life with long lasting effects |

NFPA Health Hazard 3 - Materials that, under emergency conditions, can cause serious or permanent injury.

NFPA Fire Hazard 1 - Materials that must be preheated before ignition can occur.


NFPA Reactivity Hazard 0 - Material that in themselves are normally stable, even under fire conditions.

HMIS III Rating Health

3 Serious Hazard

* Chronic - Chronic (long-term) health effects may result from repeated overexposure

Flammability Physical 1 Slight Hazard 1 Slight Hazard



The information provided in this Safety Data Sheet (SDS) was prepared based on data believed to be accurate as of the date of this SDS. TO THE GREATEST EXTENT PERMITTED BY LAW, NUSIL TECHNOLOGY LLC AND ITS AFFILIATED COMPANIES ("NUSIL") EXPRESSLY DISCLAIMS ANY AND ALL REPRESENTATIONS AND WARRANTIES REGARDING THE INFORMATION CONTAINED HEREIN INCLUDING, WITHOUT LIMITATION, AS TO ACCURACY, COMPLETENESS, FITNESS FOR PURPOSE OR USE, MERCHANTABILITY, NON-INFRINGEMENT, PERFORMANCE, SAFETY, SUITABILITY AND STABILITY. This SDS is intended as a guide to the appropriate use, handling, storage and disposal of the product to which it relates by properly trained personnel, and is not intended to be comprehensive. Users of NuSil's products are advised to perform their own tests and to exercise their own judgment to determine the safety, suitability and appropriate use, handling, storage and disposal of each product and product combination for their own purposes and uses. TO THE GREATEST EXTENT PERMITTED BY LAW, NUSIL DISCLAIMS LIABILITY FOR, AND BY USING NUSIL'S PRODUCTS PURCHASER AGREES THAT UNDER NO CIRCUMSTANCES SHALL NUSIL BE LIABLE FOR, SPECIAL, INDIRECT, INCIDENTAL, PUNITIVE OR CONSEQUENTIAL DAMAGES OF ANY TYPE OR KIND, INCLUDING WITHOUT LIMITATION, FOR LOSS OF PROFITS, REPUTATIONAL DAMAGE, PRODUCT RECALL OR BUSINESS INTERRUPTION.

Nusil US GHS SDS